

General Purpose Corded Area Imager Bar Code Reader

The Gryphon™ 4000 series represents the premium level of data collection devices from Datalogic Scanning for general purpose applications. Designed with people in mind, the Gryphon™ I GD4400-B All-in-One imager blends advanced 2D decoding with motion sensing technology, producing a user-friendly device with outstanding performance.

Featuring Datalogic's Motionix™ motionsensing technology, the Gryphon I GD4400-B imager senses the actions of the operator to automatically switch the device into handheld or presentation mode scanning. When picked up or set down, Motionix technology transitions the device seamlessly, eliminating the need to scan a label or rely on a mechanical switch.

As an All-in-One device, the Gryphon I GD4400-B scanner's permanent tilting stand is joined with an ergonomic handheld reader for handheld and presentation reading. The All-in-One imager adjusts to any angle to fit individual scanning preferences. The cable connection

is positioned well above the counter to avoid damage caused by spills.

User comfort is maximized with the Gryphon I GD4400-B imager's steady, deep red illumination light. Easier on the eyes than competitive products with flicker illumination, the highly visible 4-Dot aimer defines a precise reading zone and reduces accidental reads. The aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.

The Gryphon I GD4400-B imager provides snappy, omnidirectional reading performance on all common 1D and 2D codes as well as postal, stacked and composite codes like PDF417. For mobile marketing or ticketing applications, this scanner also offers excellent reading performance on bar codes from mobile devices.

With enhanced optics, the Gryphon I GD4400-B imager boasts improved motion tolerance and high speed imaging to read fast moving codes. This reader also eliminates the need for separate equipment for signature capture and document scanning applications.

Features

- Motionix[™] motion-sensing technology for seamless reading mode transitions
- Highly visible 4-Dot aimer with center cross for targeted scanning
- Permanent tilting stand for handheld or presentation omnidirectional reading
- Tilt Angle: + 30° / 15°
- Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads 1D, 2D and postal codes plus stacked and composite codes
- Multi-interface options: RS-232 / IBM 46XX / USB or RS-232 / USB / Keyboard Wedge / Wand
- Datalogic's patented 'Green Spot' for good-read feedback











www.scanning.datalogic.com



Specifications

DECODING CAPABILITY

1D / LINEAR CODES

2D CODES

POSTAL CODES

STACKED CODES

STACKED CODES

ELECTRICAL

CURRENT

STANDBY/IDLE (TYPICAL)

INPUT VOLTAGE

ENVIRONMENTAL

AMBIENT LIGHT DROP RESISTANCE ESD PROTECTION (AIR DISCHARGE) HUMIDITY (NON-CONDENSING)

PARTICULATE AND WATER SEALING TEMPERATURE

INTERFACES

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE DIMENSIONS

DIMENSIONS WEIGHT

READING PERFORMANCE

IMAGE CAPTURE IMAGER SENSOR LIGHT SOURCE MOTION TOLERANCE

PRINT CONTRAST RATIO (MINIMUM)

READING ANGLE

READING INDICATORS

RESOLUTION (MAXIMUM)

READING RANGES

TYPICAL DEPTH OF FIELD

SAFETY & REGULATORY

AGENCY APPROVALS

ENVIRONMENTAL COMPLIANCE LASER CLASSIFICATION

UTILITIES

DATALOGIC ALADDIN™

OPOS / JAVAPOS

REMOTE HOST DOWNLOAD

KEMOTE HOST DOWNLOA

WARRANTY

5-Year Factory Warranty

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear

codes.

Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code;

QR Code

 $Australian\ Post; British\ Post; China\ Post; IMB; Japanese\ Post; KIX\ Post;$

Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC) EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional;

MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

Operating (Typical): GD4410-B: < 170 mA @ 5 VDC GD4430-B: < 160 mA @ 5 VDC

65 mA @ 5 VDC

GD4410-B: 4.0 - 14.0 VDC; GD4430-B: 4.2 - 5.25 VDC

0 - 100,000 lux

Withstands repeated drops from 1.5 m / 5.0 ft onto a concrete surface

16 kV 5 - 95% IP52

Operating: 0 to 50 °C / 32 to 122 °F

Storage/Transport: -20 to 70 °C / -4 to 158 °F

GD4410-B: RS-232 / IBM 46XX / USB Multi-Interface

GD4430-B: RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

Black; White

19.2 x 8.9 x 11.9 cm / 7.5 x 3.5 x 4.7 in

368.5 g / 13.0 oz

Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2

Wide VGA: 752 x 480 pixels Aiming: 650 nm VLD

25 IPS 25%

Pitch: +/- 40°; Roll (Tilt): 180°; Skew (Yaw): +/- 40°

Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback;

Good Read LED

1D Linear: 0.102 mm / 4.0 mils; Data Matrix: 0.178 mm / 7.0 mils;

PDF417: 0.127 mm / 5.0 mils

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Standard Range (SR)

Code 39: 5 mils: 4.0 to 19.0 cm / 1.6 to 7.5 in Code 39: 10 mils: 1.0 to 30.0 cm / 0.4 to 11.8 in Data Matrix: 10 mils: 2.0 to 16.0 cm / 0.8 to 6.3 in Data Matrix: 15 mils: 0 to 23.6 cm / 0 to 9.3 in EAN-13: 13 mils: 1.5 to 40.0 cm / 0.6 to 15.7 in PDF417: 10 mils: 0.5 to 22.0 cm / 0.2 to 8.6 in QR Code: 10 mils: 3.0 to 12.5 cm / 1.2 to 4.9 in

The product meets necessary safety and regulatory approvals for its intended use

The Quick Reference Guide for this product can be referred to for a complete list of certifications.

Complies to China RoHS: Complies to EU RoHS

Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

Datalogic Aladdin configuration program is available for download at no charge.

charge. JavaPOS Utilities are available for download at no charge.

OPOS Utilities are available for download at no charge. Lowers service costs and improves operations.



© 2011 Datalogic Scanning Inc

All rights reserved. • Protected to the fullest extent under U.S. and international laws. • Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries including the U.S.A. and the E.U. Datalogic Aladdin is a trademark of Datalogic Scanning Group S.r.l.

Gryphon and Motionix are trademarks of Datalogic Scanning, Inc.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

DS-GRYPHONIGD4400-B-2D-EN 2011032

www.scanning.datalogic.com

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















