



### Bar Code Handy Terminal

/ /
* Work Flow Control ** Product No: 496430-5120 Product Name: Handy Terminal Handy Terminal
DENSO
-

## BHT-300 Series

The New Standard in BHT Scanners

# BHT-300 Series: robust, flexible and with numerous features.

Whether you use wireless LAN, Bluetooth<sup>™</sup>, infrared or radio frequency for data transfer, Denso's new BHT-300 series is ideal for fast and simple inventory and stocktaking. Nor does it matter if you work with one or two-dimensional barcodes – the BHT-300 series has the right device for all your requirements.

#### Communication

## Built-in wireless communication interface for connection to an existing LAN

- The BHT-300BW/BWB models are compatible with the global standard IEEE802.11b enabling wireless communication with up to 11 Mbps
- The BHT-300BB/BWB models are fitted with Bluetooth<sup>™</sup> – enabling wireless connection to portable printers

#### Performance and Quality

- Industry-leading impact resistance and superior operating environment features (the BHT-300 withstands being dropped onto concrete from a height of 1.20 m 30 times)
- Water and dust-resistance meet the IEC requirements of the International Standards Protection Class IP54 (equivalent to JIS splash proof)
- Power-saving design achieves longer
  operating time
- A lithium-ion battery and power-saving design extends continuous operating time and reduces costs by eliminating the need for replacement batteries as well as the inconvenience of managing battery recharging: 135 hours when reading two bar codes twice in 10 seconds and not using the wireless interface. 24 hours assuming a reading to wireless communication to display to standby mode ratio of 1:1:1:20 (BHT-300BW/BWB)
- CCD (Charged Coupled Device) technology: No moving parts, very robust

#### Extended scope of function

#### **User-friendly Design**

The angled scanner head and lightweight body improve user productivity – ideal for retail, logistics and warehousing applications.

#### Easy-to-use, highly durable key pad

Magic keys to which you can assign any

#### **Technical Data**

5 ME
1
1.50
App

(1): Maximum range and speed may vary according to operating condition (2): when reading two bar codes at 10-second intervals and not using the

#### Reading

#### High reading performance

- Scanning at ranges up to 450 mm (with narrow 1.2 mm bar width)
- Improved scanning of broader labels and badly printed or damaged bar codes

#### Viewing

#### Largest screen in its class

- Choose between a large, easy-to-read font size or a display of up to 9 lines with 22 characters each (12 point font)
- Alphanumerical characters, Kana and Kanji
- Compatibility mode with an 8-character, 4-line display for applications from earlier models (BHT-7000/-5000/-8000)
- The characters can be enlarged horizontally, vertically and simultaneously horizontally/

vertically





DENSO WAVE 04/01/31 1:Stock in 4:Shipping 2:Ordering 5:Returning 8:Inventory Select your task

DENSO





functions you wish. Cursor key enhances menu selection convenience. Resin-coated keys enhance durability.

#### Extension Pack

The BHT-300 series is compatible with BHT-BASIC 4.0, which is now equipped with easy to use functions – it is compatible with earlier models and enables uncomplicated transfer of applications.

#### Vibrator

The vibrator reliably informs the user when the reading process has been completed and if any errors have occurred – even in noisy working environments.

#### **Remote Wakeup Function**

Makes it possible for it to be controlled from a PC and enables remote maintenance of master files, applications and operating systems.

#### **BHT Extension Pack**

#### BHT pack for creating applications

High performance development software for the whole process, from development to implementation. Easy installation, can be implemented immediately.

BHT-302B	BHT-303B	BHT-303BB	BHT-303BW (303BWB)	BHT-304Q	BHT-304QW		
(User area approx.: 2.2 MB)	9 MB (User area approx.: 5.8 MB)	9 MB	9 MB (User area approx.: 5.25 MB)	18 MB (User area approx.: 12.5 MB)	18 MB (User area approx.: 12 MB		
		132 x 72 dots					
		Liquid crystal dot matrix display (Monochrome)					
		22 char x 9 lines					
		8 char x 4 lines					
		11 char x 6 lines					
		Advanced Scanning (CCD) 1D		Advanced Scanning (CCD) 2D	ced Scanning (CCD) 2D		
		420 mm max (with a distance of	400 mm from label)				
		EAN-13/-8 (JAN-13/-8), UPC-A/-E, Interleaved 2 of 5, CODABAR (NW CODE128 (EAN-128), Standard 2	V-7), CODE39, CODE93,	les, QR Code, Micro QR Code, PDF417, Maxi Code, DataMatrix, EAN, UCC Composite			
		0.125 mm					
		2-color LED (red & green), buzze	r, vibrator				
		26 keys (Incl. power switch) + 2 1	trigger keys				
		Infrared interface (IrDA-SIR Ver. 1.2[Low Power] compliant)					
		Approx. 115.2 Kbps max					
		Approx. 15 cm					
		Bluetooth™	IEEE802.11b (Bluetooth™)		IEEE802.11b		
			2.4 GHz		2.4 GHz		
			Indoors: approx. 75 m Outdoors: approx. 200 m		Indoors: approx. 75 m Outdoors: approx. 200 m		
			DSSS		DSSS		
			11/5.5/2.1 Mbps (with auto fallback)		11/5.5/2.1 Mbps (with auto fallback)		
		RS-232C (115.2 Kbps max)					
		Lithium-ion battery cartridge					
		Approx. 135 hours					
		Approx. 24 hours <sup>10</sup>					
		Clock, beeper, vibrator, low batte	ery indication, remote wakeup functions				
		−5 °C ~ 50 °C					
		IP54 (JIS splash Proof)					
(30 times onto concrete floor	)	1.20 m (30 times onto concrete floor) <sup>(4)</sup>					
. 230 g		Approx. 240 g	Approx. 250 g (260 g)	Approx. 260 g			

wireless interface.

(3): Reserve power calculation assuming a reading to wireless communication to display to standby mode ration of 1:1:1:20.(4): Test value, not guaranteed.

Bluetooth is the registered trademark of Bluetooth SIG Inc. and is used under licence by Denso Wave. Carefully read the user manual before using the device. Specifications are subject to change without notice. Information current as of June 2004.

#### Accessories

- Hand strap
- Lithium-ion battery BT-20L

Technical Data CU 300

• Operating manual




#### **Optional Accessories (not supplied)**


• Communication units: CU-301 (RS-232C) CU-321 (USB)

CU-311 (LAN) (available shortly)

- Battery charger for the main power supply battery (CH-351)
- Soft case and belt case (available shortly)

#### **Dimensions (in mm)**





CU-300 Series





			CU-301	CU-321 <sup>(1)</sup>	
Communication	BHT $\leftarrow \rightarrow$ CU (Communication unit)	Communication system	IrDA-SIR Ver. 1.2 (Low Power) compliant		
		Communication speed	115.2 Kbps max		
	CU ← → Host	Communication system	RS-232C	USB 1.1 Full Speed compliant	
Display	LEDs		Power, communication		
Battery charger	Charge time		4 hours	9 hours <sup>(2)</sup>	
Power source			AC/DC adapter	From connected device	

(1): Connection may not be possible depending on the type of PC or USB hub being used. First check if they are compatible. The AC/DC adapter (not included in the scope of delivery) is required for recharging or discharging the battery if no power supply is available via the connected device, such as when this is switched off or is in standby mode.

(2): Charge time may vary according to the power supplied by the connected device. Charge time with the AC/DC adapter is 4 hours.

#### www.denso-id.de

Company Stamp

Toyota Tsusho Europe S.A. · Denso ID Systems Department Carl-Schurz-Straße 2, 41460 Neuss, Germany Phone +49 2131-3691-0 · Fax +49 2131-3691-502 · info@denso-id.de

## Legacy Technology Services

## We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert 866-271-9891

#### About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

#### Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

#### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

#### **Discontinued product sourcing**

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

#### Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
  - Data destruction
  - · Hardware disposal
  - Auditing services

#### Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

#### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

#### www.LegacyGlobal.com

#### Some brands we carry







## Honeywell













