

17A2 17" All-in-One Touchcomputer

Expanded Versatility for POS Applications

Elo TouchSystems 17A2 17" All-in-one touchcomputer

provides an attractive ultra-compact 17" touch solution that can fit virtually anywhere in any point-of-service environment.

Expanded versatility, bigger screen, and improved serviceability all in a compact design

The 17A2 touchcomputer with dual video display support includes a choice of Elo TouchSystems newest breakthrough touch technology, Acoustic Pulse Recognition, AccuTouch five-wire resistive, IntelliTouch surface acoustic wave or CarrollTouch Infrared. Its 1280 X 1024 SXGA resolution with a 5 x 4 aspect ratio displays clear, precise graphics for improved readability. A variety of optional field-replaceable peripherals can easily be integrated into the 17A2's compact design including: magnetic stripe reader, vacuum fluorescent, rear-facing customer display, biometric fingerprint recognition device, and speaker bar with/without a built-in single or omni-directional barcode scanner.

Designed for public access

The silent, fanless, spill and tamper resistant design of the 17A2 and its compact integrated peripherals, make this touchcomputer a preferred choice for point-of-sale, kiosk and point-of-interest applications.

Features

- Space saving, integrated, all-in-one touchcomputer with the footprint of a standard 17" LCD display
- Silent, fanless Intel Celeron M design-ideal for POS, kiosk and POI applications
- Industry standard VESA mounting options configurable as a desktop or wall-mount
- Choice of Microsoft Windows Embedded for POS (WEPOS), XP Professional or Microsoft Windows XP Embedded operating systems
- Full range of "field" replaceable and serviceable POS options such as an integrated MSR, vacuum fluorescent, rear-facing customer display, biometric fingerprint recognition device, and speaker bar with/without a built in single or omni-directional barcode scanner
- Available with AccuTouch five-wire resistive, CarrollTouch Infrared, IntelliTouch surface acoustic wave or Acoustic Pulse Recognition (APR) touch technologies
- Integrated (optional) wireless LAN & DVD for expanded access and advanced media applications
- One Ethernet, two serial, and four high-speed USB 2.0 ports for maximum expansion
- Designed for public access with cables hidden from user's view; OSD and cable lockout function to minimize public tampering





17A2 17" All-in-One Touchcomputer Specifications

Case/Bezel color	Dark Gray
Processor	Intel Celeron M 1GHz CPU
Chipset	Intel 915GME/ICH6
Video	Up to 128MB shared
Memory (RAM)	1GB DDR2 standard on 1 of 2 slots; Expandable to 2GB maximum"
Supported Operating Systems	Microsoft Windows XP Professional Service Pack 2 Microsoft Windows Embedded for Point of Service (WEPOS) Microsoft Vista
Serial Ports	2 x RS232 serial (RJ45, 8 position); COM2 is RS232, RS422 and RS485 selectable
USB Port	4 x 2.0 high-speed USB self powered: 1 (of 4 port) is 12V USB Port (1.5A) for POS Peripherals
VGA Port	1 x VGA D-SUB
Ethernet 100/10Base-T Port	1 x LAN RJ45
Cash Drawer Port	1 x cash drawer (RJ11, 6 position)
PS/2 Port	1 x PS/2 Universal (default to Keyboard compatibility)
Audio Port	1 x 3.5mm audio-out; 1 x 3.5mm mic-in
Hard Drive	1 x 2.5" 160 GB SATA hard drive [™]
Compact Flash Slot	1 x Compact Flash type I (internal)
Display Size	17.0 in. diagonal; Type: Active matrix TFT LCD; Aspect Ratio: 5 x 4
Optional Touchscreens	AccuTouch Five-Wire Resistive; IntelliTouch Surface Wave; CarrollTouch Infrared; Acoustic Pulse Recognition (APR
Optional Peripherals	Magnetic Stripe Reader, Serial Customer Display; (20x2 VFD), Biometric Fingerprint Reader, Speaker Bar; Line or Omni Barcode Scanner, DVD Burner, drive (internal); Wireless Card
Useful Screen Area	337.92 mm (13.31 in.); 270.33 mm (10.65 in.)
Maximum Touchcomputer Dimensions with Stand™	Width: 391 mm (15.40 in.) Height: 380.6 mm (15.00 in.) Depth: 239 mm (9.42 in.)
Tilt Adjust	From -5° to 75°
Optimal Resolution	1280 x 1024 at 60Hz (native); scalar support for 1024 x 768 or 800 x 600 at 60Hz
Colors	16.7 million colors
Brightness (typical)	No Touchscreen: 300 cd/m ² with AccuTouch: 240 cd/m ² with IntelliTouch: 276 cd/m ² with CarrollTouch: 276 cd/m ² with APR: 276 cd/m ²
Viewing Angle (from center)	Horizontal (left/right): ±80° or 160° total; Vertical (up/down): ±80° or 160° total
Contrast Ratio	800:1 (typical)
Temperature	Operating: 0°C to 35°C; Storage: -20°C to 60°C
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 5% to 95%
Weight with All Options (approx.)	Actual: +20 lb. (+9.09 kg); Shipping: +25 lb. (11.36 kg)
Agency Approvals	UL/cUL (Recognized component), FCC, CE, VCCI, C-tick, EN60950
Warranty	3 years
Backlight Lamp Time to 1/2 Brightness	Minimum 50,000 hours
MTBF (mean time between failures)	50,000 hours demonstrated
Other Features	100mm VESA mounting; removable base; threaded holes on bottom of base for secure mounting; 2 watt/channel speakers located in display head; touchscreen sealed to bezel; touchscreen sealed to LCI
Power Supply	Type: External brick; Input (line) voltage: 100-240 VAC, 50-60 Hz; Output voltage/current: 12 V at 10.0 amps max

Memory supports both system and video. Accessible system memory may be up to 128 MB less than the amount stated, depending on the video mode.
Maximum memory using 2 slots.

iii GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less. May not be applicable for XP Embedded Systems. iv Dimensions vary with stand position and options selected.

Other restrictions and regional differences may apply. For a copy of the terms and conditions of the Elo TouchSystem's Limited Warranty, please contact your Elo representative or reseller.

To find out more about Elo's extensive range of touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo TouchSystems 301 Constitution Drive Menlo Park, CA 94025-1110 800-ELO-TOUCH Tel 1-650-361-4800 Fax 1-650-361-4722 eloinfo@elotouch.com

Europe Tel +32 (0)16 35 21 00 Fax +32 (0)16 35 21 01 elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161 Fax +81 (45) 478-2180 www.tps.co.jp Latin America

Tel 786-923-0251 Fax 305-931-0124 www.elotouch.com.ar



Tyco Electronics reserves the right to change or update, without notice, any information contained herein, to change, without notice, the design, construction, materials, processing or specifications of any products, and to discontinue or limit production or distribution of any products.



Our commitment. Your advantage.

AccuTouch, CarrollTouch, Elo logo, Elo TouchSystems, IntelliTouch, TE Logo, and Tyco Electronics are trademarks. Copyright 2009 Tyco Electronics Corporation 2/09

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













