

Vouge Pro

12" or 15" High-end Slim POS with Detachable LCD or VFD Customer Display



The Vouge Pro is a top of the line touch POS terminal designed to operate under the harshest retail and hospitality environments. With a sleek and lean aluminum exterior, small footprint and upright design, the Vouge Pro fits into space-constricted environments while conveying a clean and modern presentation.



Features

Space Saving, Small Footprint and Upright Design Upright elongated design delivers a sophisticated look for high-end environments such as fashion apparel and hotel



Downward Facing I/O Connector Panel for Countertop Management

Neatly conceals cabling under terminal for workspace





Dual HDD Supporting RAID Function


Provides secure data protection as well as a faster and safer data backup







I/O Interface



Dimensions 375 mm 255 mm 430 mm RP-3215B

Specifications

Processor	Model	RP-3212B	RP-3215B	
Power Supply Supports 2 x 2 S SATA HDD with TAVEAV Output Storage Device Supports 2 x 2 S SATA HDD with TAVEAV Output Storage Device Supports 2 x 2 S SATA HDD with TAVEAV Output Supports 2 x 2 S SATA HDD with TAVEAV Output Supports 2 x 2 S SATA HDD with TAVEAV Output Supports 2 x 2 S SATA HDD with TAVEAV Output Internal Speaker 2W x 2 Internal Speaker 2W x 2	Processor			
Supporte 2 x 2.5 SATA HDD with PAID Function (0.1), 2nd SATA HDD (Optional) Speaker Supporte 2 x 2.5 SATA HDD with PAID Function (0.1), 2nd SATA HDD (Optional) Internal Speaker 2W x 2 Construction	System Memory	1 GB Standard, Maximum 4 GB (2 x 240-pin DDR2)		
Internal Speaker 2W x 2	Power Supply	250W External Power Supply with 12V/24V Output		
Construction	Storage Device	Supports 2 x 2.5 SATA HDD with RAID Function (0,1), 2nd SATA HDD (Optional)		
Housing Color	Speaker	Internal Speaker 2W x 2		
Size / Resolution	Construction	Aluminum Die-casting, Plexi-Glass Acrylic (Front Bezel)		
Size / Resolution	Housing Color	Black		
Brightness (Backlight Type)	Touch LCD Display			
Touch Screen	Size / Resolution	12.1" TFT LCD / 800 x 600	15" TFT LCD / 1024 x 768	
Serial Port 3 x Internal : COM3 (Touch), COM4 (VFD / LCM or 2nd Touch), COM6 (Reserved)	Brightness (Backlight Type)	400 cd/m ² (CCFL)	250 / 350 cd/m² (CCFL)	
Serial Port	Touch Screen	5-Wire Resistive Touch		
Serial Port 3 x External : COM1 & COM2 (DB9), COM5 (RJ45)	I/O Ports			
3 x External : COMM & COMZ (DB9), COM6 (RJ46) USB Port 3 x Internal (1 WiFi, 1 MSR / 3-in-1, 1 Reserved), 5 x External (15 die, 4 Bottom) Printer Port 1 x B-Lift (12V) Cash Drawer Port 1 x RJ11 (12V) Keyboard 1 x RJ45 (siga LAN Video Port 1 x RJ45 (siga LAN Video Port 1 x Line-out OS Supported	Serial Port	3 x Internal : COM3 (Touch), COM4 (VFD / LCM or 2nd Touch), COM6 (Reserved)		
Printer Port 1 x Bi-directional Parallel Port Cash Drawer Port 1 x RJ11 (12V) Keyboard 1 x PS/2 LAN Port 1 x RJ45 Giga LAN Video Port 1 x VGA Audio Port 1 x Line-out OS Supported Windows Windows XP, POSReady 2009, Windows 7, POSReady 7 Linux Per Request Physical Dimensions Dimensions (WxHxD) 325 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A CP (22F - 104F) Corrage Temperature 0°C - 40°C (32F - 104F) CE (14F - 131F) Relative Humidity 10% - 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2:n-1 / 3-in-1 Module Integrated MCR + I-Button / MCR + RFIp / MCR + Fingerprint / MCR + Smartcard + I-Button 2nd Display Integrated VFD / LCM Customer Pole-Display		3 x External : COM1 & COM2 (DB9), COM5 (RJ45)		
Cash Drawer Port 1 x RJ11 (12V) Keyboard 1 x PS/2 LAN Port 1 x RJ45 Giga LAN Video Port 1 x VGA Audio Port 1 x Line-out OS Supported Windows Windows XP, POSReady 2009, Windows 7, POSReady 7 Linux Per Request Physical Dimensions Dimensions (WxHxD) 325 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature 0°C - 40°C (32°F - 104°F) Storage Temperature -10°C - 55°C (14°F - 131°F) Relative Humicity 10% - 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + HButton / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated VFD / LCM Customer Pole-Display	USB Port	3 x Internal (1 WiFi, 1 MSR / 3-in-1, 1 Reserved), 5 x External (1 Side, 4 Bottom)		
Tx PS/2	Printer Port	1 x Bi-directional Parallel Port		
LAN Port	Cash Drawer Port	1 x RJ11 (12V)		
Video Port 1 x VGA Audio Port 1 x Line-out OS Supported Windows XP, POSReady 2009, Windows 7, POSReady 7 Linux Per Request Physical Dimensions Dimensions (WxHxD) 325 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature 0°C ~ 40°C (32°F ~ 104°F) Storage Temperature -10°C ~ 55°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated VFD / LCM Customer Pole-Display	Keyboard	1 x PS/2		
Audio Port	LAN Port	1 x RJ45 Giga LAN		
Windows Windows XP, POSReady 2009, Windows 7, POSReady 7 Linux Per Request Physical Dimensions Dimensions (WxHxD) 325 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature 0°C ~ 40°C (32°F ~ 104°F) Storage Temperature 10°C ~ 56°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated VFD / LCM Customer Pole-Display	Video Port	1 x VGA		
Windows XP, POSReady 2009, Windows 7, POSReady 7 Linux Per Request Physical Dimensions Dimensions (WxHxD) 325 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature 0°C ~ 40°C (32°F ~ 104°F) Storage Temperature 10% ~ 55°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + Fringerprint / MCR + Smartcard + i-Button 2nd Display Integrated VFD / LCM Customer Pole-Display	Audio Port	1 x Line-out		
Linux Per Request Physical Dimensions Dimensions (WxHxD) 325 x 430 x 255 mm 375 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature 0°C ~ 40°C (32°F ~ 104°F) Storage Temperature -10°C ~ 55°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12:1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	OS Supported			
Physical Dimensions Dimensions (WXHXD) 325 x 430 x 255 mm 375 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature O"C ~ 40"C (32"F ~ 104"F) Storage Temperature -10"C ~ 55"C (14"F ~ 131"F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated VFD / LCM Customer Pole-Display	Windows	Windows XP, POSReady 2009, Windows 7, POSReady 7		
Dimensions (WxHxD) 325 x 430 x 255 mm 375 x 430 x 255 mm 375 x 430 x 255 mm Environment EMI / Safety CE, FCC Class A Operating Temperature 0°C ~ 40°C (32°F ~ 104°F) Storage Temperature -10°C ~ 55°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Linux	Per Request		
Environment EMI / Safety CE, FCC Class A Operating Temperature O'C ~ 40°C (32°F ~ 104°F) Storage Temperature -10°C ~ 55°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated VFD / LCM Customer Pole-Display	Physical Dimensions			
EMI / Safety CE, FCC Class A Operating Temperature 0°C ~ 40°C (32°F ~ 104°F) Storage Temperature -10°C ~ 55°C (14°F ~ 131°F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Dimensions (WxHxD)	325 x 430 x 255 mm	375 x 430 x 255 mm	
Operating Temperature O"C ~ 40"C (32"F ~ 104"F) Storage Temperature -10"C ~ 55"C (14"F ~ 131"F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Environment			
Operating Temperature O"C ~ 40"C (32"F ~ 104"F) Storage Temperature -10"C ~ 55"C (14"F ~ 131"F) Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	EMI / Safety	CE, FCC Class A		
Relative Humidity 10% ~ 90% (Non-condensing) Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)		
Optional Peripherals Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Storage Temperature	-10°C ~ 55°C (14°F ~ 131°F)		
Magnetic Stripe Card Reader Integrated MCR Module (Single / Dual / Triple Track Selectable) 2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Relative Humidity	10% ~ 90% (Non-condensing)		
2-in-1 / 3-in-1 Module Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button 2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Optional Peripherals			
2nd Display Integrated 12.1" / 15" TFT LCD (Touch Screen Optional) Customer Display Integrated VFD / LCM Customer Pole-Display	Magnetic Stripe Card Reader	Integrated MCR Module (Single / Dual / Triple Track Selectable)		
Customer Display Integrated VFD / LCM Customer Pole-Display	2-in-1 / 3-in-1 Module	Integrated MCR + i-Button / MCR + RFID / MCR + Fingerprint / MCR + Smartcard + i-Button		
	2nd Display	Integrated 12.1" / 15" TFT LCD (Touch Screen Optional)		
Wireless LAN Integrated 802.11 b/g/n Wireless Module	Customer Display	Integrated VFD / LCM Customer Pole-Display		
	Wireless LAN	Integrated 802.11 b/g/n Wireless Module		



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















