# Honeywell

# Orbit 7120/OrbitCG 7180

## **Omnidirectional Laser Scanners**

Honeywell's Orbit<sup>®</sup> series of scanners provide aggressive omnidirectional scanning in an award-winning design for retailers seeking an affordable, aesthetically-pleasing scanning solution.

Orbit, the all-time, best-selling hands-free omnidirectional scanner, presents an innovative, elegant and affordable solution for convenience retail applications where counter space is at a premium.

Compact, lightweight and rugged, Orbit maximizes customer satisfaction and employee efficiency with a patented 20-line scan pattern, an easy-to-find sweet spot and a scan speed of 1,120 scans per second.

Recipient of multiple design honors, Orbit's award-winning shape enables hand-held scanning of large, bulky items. For added flexibility, the scanning head can be tilted within a 30° range to accommodate objects of various sizes and shapes.

For applications that require menu scanning, OrbitCG 7180 combines the power of patented CodeGate<sup>®</sup> technology with many of the outstanding features already found in the Orbit<sup>®</sup> 7120. CodeGate technology allows the user to easily target the desired bar code and complete data transmission with the push of a single button.

The scanner's expanded ability to update its firmware via Honeywell's free patented MetroSet<sup>®</sup>2 configuration software safeguards long-term infrastructure commitments in the event of a change in the POS system or software.

Standard features include an integrated EAS antenna for tag deactivation (OrbitCG 7180 only), power save mode, user-replaceable cables, Honeywell's patented MetroSelect and MetroSet®2 for easy configuration, data editing and OPOS/JPOS compatibility for easy installation.



#### **Features**

- 20 Scan Line Omnidirectional Pattern: Provides aggressive scanning as an additional benefit to hand presentation applications
- Sweet Spot Scanning: Engineered "sweet spot" to optimize scan performance and first pass read rate
- Adjustable Scan Head: Ability to tilt scanner 30° for targeted scanning or larger products
- Flash ROM: Protects POS investment with free firmware updates via MetroSet®2 software and standard PC
- Automatic Scanning Operation: Simply present a bar code and the unit scans in a single pass
- Built-in RF EAS Antenna (Orbit 7180 only): Increases efficiency by simultaneously deactivating RF EAS tags and decoding bar codes

## Orbit 7120/OrbitCG 7180 Technical Specifications

Mechanical		
Dimensions (LxWxH)	105 mm x 102 mm x 150 mm (4.1" x 4.0" x 5.9")	
Weight	400 g (14.1 oz)	
Electrical		
Input Voltage	5 VDC ± 0.25 V	
Operating Power	900 mW (180 mA @ 5 V)	
Standby Power	850 mW (170mA @ 5 V)	
Host System Interfaces	USB, RS232, Keyboard Wedge, IBM 468xx (RS485), Light Pen Wand Emulation	
Environmental		
Operating Temperature	0°C to 40°C (32°F to 104°F)	
Storage Temperature	-40°C to 60°C (-40°F to 140°F)	
Humidity	5% to 95% relative humidity, non-condensing	
Drop	Designed to withstand 1.2 m (4') drops	
Environmental Sealing	Sealed to resist airborne particulate contaminants	
Light Levels	4842 Lux	
Scan Performance		
Scan Pattern	Omnidirectional: 5 fields of 4 parallel lines; button activated single line (7180)	
Scan Speed	Omnidirectional: 1120 scan lines per second; single line: 56 scan lines per second (7180)	
Print Contrast	35% minimum reflectance difference	
Pitch, Skew	60°, 60°	
Decode Capability	Reads standard 1D and GS1 DataBar symbologies	
Warranty	3 year factory warranty	

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies





For more information:

www.honeywellaidc.com

#### **Honeywell Scanning & Mobility**

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

Typical Performance*	Orbit 7120	Orbit 7180
Narrow Width	Depth of Field	Depth of Field
5.2 mil	0 mm - 50 mm (0″ - 2.0″)	0 mm - 50 mm (0″ - 2.0″)
7.5 mil	0 mm - 150 mm (0″ - 5.9″)	0 mm - 150 mm (0″ - 5.9″)
10 mil	0 mm - 175 mm (0″ - 6.9″)	0 mm - 220 mm (0″ - 8.7″)
13 mil	0 mm - 215 mm (0″ - 8.5″)	0 mm - 275 mm (0″ - 10.8″)
26 mil	0 mm - 250 mm (0″ - 9.8″)	0 mm - 300 mm (0″ - 11.8″)
*Resolution: 5 mil (0.125 mm	) )	

\*Performance may be impacted by bar code quality and environmental conditions



71X0-DS Rev A 07/10 © 2010 Honeywell International Inc.

# Legacy Technology Services

### We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert 866-271-9891

#### About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

#### Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

#### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

#### **Discontinued product sourcing**

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

#### Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
  - Data destruction
  - · Hardware disposal
  - Auditing services

#### Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

#### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

#### www.LegacyGlobal.com

#### Some brands we carry







# Honeywell













