


# TECTON™

THE BUILDING BLOCK OF YOUR SUPPLY CHAIN, THAT MOVES AS FAST AS YOU DO.



Light enough for scan-intensive picking, yet able to take a beating with a rugged IP-65 rating. And now, turbocharged with a PXA320 806 MHz processor, running available Windows® Mobile 6.5 or CE 6.0. LXE's Tecton handheld mobile computer, the successor to our MX7, moves your supply chain with the leading edge of warehouse computing technology.

The Tecton's enhanced performance comes without sacrificing any of the field-proven ruggedness you trust. Keypads protect against airborne and spilled chemical agents and are epoxy-topped to fight wear. Electrical components are soldered and glued to printed circuit boards to better withstand drops and shocks.

The options for deploying the Tecton are practically limitless, with LXE's proprietary ToughTalk technology for voice-driven applications, available vehicle mounts, and a host of other accessories, all backward compatible for existing installations.

It's the foundation of your supply chain – reinvented. Learn more at [lxe.com/tecton](http://lxe.com/tecton).



## PERFORMANCE

PXA320 processor for faster real-time data capture contributes to ROI

## FLEXIBILITY

Fits your needs as handheld, vehicle-mount, with 55 or 32 key backlit keypads and ToughTalk

## STRENGTH

IP 65-rated with up to 6' drop to concrete and available cold-storage configurations



IP 65



5ft  
6ft w/ boot



VOICE READY

# TECTON™

## TECHNICAL SPECIFICATIONS



### PLATFORM

#### Processing & Memory

- PXA320 806 MHz
- 256MB SDRAM
- 256MB Flash
- 1GB or 4GB SD card

#### System

- Windows® Mobile 6.5
- Windows® CE 6.0
- Non-volatile storage of resident drivers, applications & settings

#### Display & Touch Screen

- 3.5" (88 mm) 240x320 ¼ VGA TFT color LCD
- 280 NIT LED backlit brightness

- Resistive touchscreen w/ stylus

#### Power Supply & UPS

- Full shift battery life with typical usage 2200mAh@7.4V
- Fast recovery backup power for data retention: 2.5V super-capacitor
- Main battery low warning
- Active power management (configurable)

#### Enclosure

- Weight: 21oz (595g) w/ radio, battery, & SR laser scanner
- Dimensions: 8.8" x 3.4" x 2" (223mm x 86mm x 50mm)

### ENVIRONMENTAL

- Operating temperature: 14° to +122°F (-10° to +50°C)
- Storage temperature: -4° to +158°F (-20° to +70°C)
- Humidity: 5 to 90% RH non-condensing at 104°F (40°C)
- Drop: 5 ft. (1.5m) multiple drops to concrete (w/ handle); 6 ft. (1.8m) w/ rubber boot accessory (w/o handle)
- Ingress Protection: IEC 60529 compliant to IP65
- MIL STD 810F

#### Approvals

- Emissions: (EMI) FCC Part 15, Subpart B, Class A; EN 55022, Class A (CISPR 22)
- Immunity: (EMC) EN 55024:1998
- Safety: UL 60950, CSA C22.2 No. 60950, EN 60950, IEC 60950
- Laser Safety: CDRH:21 CFR 1040.10, EN 60825-1 & IEC 60825-1
- Battery Safety: UL 2054, IEEE 1725
- Radio: FCC Part 15C, IC RSS210, 102, EN 300 328
- RoHS compliant version available

### CONNECTIVITY

#### Optional Software

- WavelinkTE
- RFTerm® (TN5250, TN3270, VT220)
- AppLock utility controls user application access & unwanted configuration changes
- Multiple language OS support
- Voice recognition
- Wavelink Avalanche & LXE eXpress Config compatible
- Stay-Linked Ready

#### Interfaces

- USB client

- RS-232
- Power for in-terminal charging
- Audio for headset, voice recognition application certified
- Speaker w/ adjustable volume control
- Large scan status LED
- Power status LED

#### Radio Support

- WLAN: 802.11 a/b/g
- Internal antenna diversity
- Bluetooth® 2.0+EDR
- WPA or WPA2 security
- Cisco CCXv4 certified

### DATA CAPTURE

#### Barcode

- Base laser: SE955E
- Short range laser: SE955I
- Multi-range Lorax laser (4" -40'): SE1524ER
- 2D imager: HHP 5300

- Full symbology support
- Image capture, VGA
- Successful scan vibration signal
- Easy view scan LEDs

### CUSTOMIZATIONS

#### Accessories

- Handle w/2-finger trigger, molded rubber grip & wrist strap
- 4-slot battery charger
- Nylon hand strap
- Nylon holster w/ belt
- Nylon case w/ shoulder strap
- Nylon voice application case w/ belt

- Rubber protective boot
- Powered vehicle-mount cradle
- Passive cradle w/ RAM® Mount

Download full accessory brochure: [lxe.com/tecton](http://lxe.com/tecton)

#### Developers

Free SDK available: [lxe.com/developer](http://lxe.com/developer)



125 Technology Parkway  
Norcross, GA 30092

1-800-664-4593  
[info@lxe.com](mailto:info@lxe.com)



# Legacy Technology Services

**We Rent & Sell All Types Of Barcode Equipment**

Call now to talk to an expert

**866-271-9891**

[www.LegacyGlobal.com](http://www.LegacyGlobal.com)

Some brands we carry



MOTOROLA

**Intermec**

**DATALOGIC™**

**Honeywell**

**EQUINOX**  
PAYMENTS



## About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

## Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

## Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

## Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

## Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
  - Data destruction
  - Hardware disposal
  - Auditing services

## Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

## Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



[Legacy, Inc.](http://Legacy, Inc.)

160 West Road,  
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684