



# RFID Antenna Family

## RFID antennas for fixed readers



### Comprehensive RFID antenna portfolio for diverse application needs

Motorola's family of Radio Frequency Identification (RFID) Antennas offers the versatility and performance required to meet diverse environmental and application needs — including customer-facing areas, warehouses and outdoors. When used in conjunction with Motorola's Fixed RFID Readers, communication with Electronic Product Code (EPC™)-compliant RFID tags is accurate, fast and efficient. Vital components in reader-tag communications, our family of efficient, high-performance antennas can meet the needs of any RFID solution.

#### **AN700 Series: Compact antennas for customer facing environments**

The AN700 Series antennas offer all the features required for carpeted and customer-facing environments. A perfect complement to Motorola's FX7400 RFID Reader, the AN700 Series antennas are extremely compact, offering the aesthetics required for the most discreet installation in the most space constrained areas — for example, under the point of sale (POS) counter. The integrated mounting bracket enables easy installation in minutes. The AN710 is designed for inside the four walls. The rugged AN720 is designed to withstand exposure to rain, snow and extreme temperatures — ideal for the receiving dock doors or outdoor shopping areas.

#### **AN480: wide band antenna for worldwide use**

The AN480 single port antenna offers maximum performance and flexibility. The low axial ratio is nearly 50 percent lower than typical competitive devices, delivering a more uniform gain — and better performance. The wide frequency range

enables this antenna to be utilized in worldwide deployments, providing cost-efficiencies and a simplified RFID infrastructure. The AN480 can be installed throughout the enterprise in manufacturing and warehouse floor environments, or any dock door receiving application. As with all Motorola antennas, the AN480 uses Motorola's standard mounting bracket — mounting the antenna for the first time or upgrading an existing Motorola antenna with the AN480 is fast and easy.

#### **AN400: High-performance area antenna for high-capacity, high throughput environments**

Get the capacity and range you need to enable RFID tag reading in large areas with the AN400 high-performance area antenna. This general-purpose area antenna is optimized to perform in all environments. Easy to mount on ceilings and walls, the AN400 enables the easy creation of superior read zones around shelves, doorways and dock doors — anywhere boxes and pallets are moving into and out of a facility.

These packaged, rectangular antenna arrays offer a wide read field and high-speed RF signal conversion for fast and optimal communication of EPC-compliant passive tag data. High-performance area antennas are typically used in applications requiring the longest read ranges and highest levels of performance. They meet standard technical requirements for any RFID implementation and are deployment-ready with Motorola RFID fixed readers.

**AN200: general purpose antenna for indoor or outdoor application**

Get the convenience of a versatile antenna that can be utilized throughout your enterprise, from the warehouse floor and production line to outside the dock door. Able to withstand extreme heat and cold as well as moisture and vibration, the AN200 is ideal for nearly any application, including retail, manufacturing, wholesale distribution, healthcare, government and more.

This all-purpose antenna can be used in standard RFID applications with power levels up to one watt, as well as custom high-power applications requiring up to 20 watts. The antenna is traditionally used in pairs, with right and left hand polarization.

**Motorola RFID antennas – A vital RFID system component**

RFID Antennas complement the portfolio of Motorola enterprise mobility solutions that enable organizations to capture, move and manage critical information to and from every point of business activity. In combination with Motorola’s fixed readers, these efficient antennas deliver high-throughput, high capacity communication of EPC-compliant RFID tag data.

**Services complete the solution**

To help you seamlessly and successfully integrate your RFID Antennas into your environment, Motorola offers a complete suite of services that span the entire solution lifecycle — from initial planning and assessment through ongoing training and support.

For more information about Motorola RFID antennas for fixed readers and how Motorola’s enterprise mobility solutions can give your organization a competitive advantage, access our global contact directory at [www.motorola.com/enterprise/contactus](http://www.motorola.com/enterprise/contactus), or visit us on the web at [www.motorola.com/rfid](http://www.motorola.com/rfid)

**AN710**

**Compact General Purpose Indoor Antenna**



**Physical Characteristics**

Dimensions:	5.75 in. L x 5.75 in. W x 0.69 in. D 146.05 mm L x 146.05 mm W x 17.53 mm D
Weight:	1.1 lbs./0.5 kg

**User Environment**

Frequency Range:	900-928 MHz and 867-870 MHz
Gain:	3 dBiL
Bandwidth @ 2:1	SWR: 30 MHz
Beam Width:	80° elevation; 80° azimuth
Nominal Impedence:	50 Ohm
Maximum Power:	10 watts
Operating Temperature:	-22° to +176° F/-30° to +80° C
Connector:	Type 'N' female
Mounting:	Integrated articulating mount
Antenna Randomo:	White ABS plastic

## AN720

### Compact Rugged Indoor-Outdoor Antenna



#### Physical Characteristics

Dimensions: 5.2 in. L x 5.2 in. W x 0.7 in. D  
132.8 mm L x 132.8 mm W x 18.1 mm D

Weight: 0.8 lbs./0.37 kg

#### User Environment

Frequency Range: US and Canada: 900-928 MHz  
Europe: 865-868 MHz

Operating Temperature: -22° to +158° F/-30° to +70° C

Storage Temperature: -40° to +185° F/-40° to +85° C

Connector: Type "N" female

Gain: US/Canada: 3dBil  
Europe: 3.5 dBil

Return Loss (VSWR): 1.5:1

Front to Back Ratio: 8 db

Nominal Impedance: 50 Ohm

Beam Width: 100°

Polarization: Circular (L) left

Power: 10 watts

Axial Ratio: 2 dB

Mounting: 2 threaded studs (rack mount); includes articulating mount

Enclosure rating: IP67

Impact Resistance: 1.0 lbs./0.46 kg; Ball drop — 24 in./60.96 cm

Vibration: MILSTD-810

Shock: IEC-68-2-27

Humidity: IEC-68-2-30

Lightning Protection: DC grounded

## AN480

### High-Performance Worldwide Indoor Wide Band Antenna



#### Physical Characteristics

Dimensions: Without mounting screws:  
10.2 in. L x 10.2 in. W x 1.32 in. D  
25.91 cm L x 25.91 cm W x 3.35 cm D  
With mounting screws:  
10.2 in. L x 10.2 in. W x 1.98 in. D  
25.91 cm L x 25.91 cm W x 5.03 cm D

Weight: 2.5 lbs./1.13 kg

Polarization: LHCP and RHCP

#### User Environment

Frequency: 865-956 MHz

Operating Temperature: -13° to +158° F/-25° to +70° C

Environmental Sealing: IP54

Connectors: Type "N" female

Max. VSWR Free Space: 1.22:1

Max. VSW Ground at .15 Meter: 1.3:1

Nominal Impedance: 50 Ohm

Horizontal 3 dB Beam Width: 65°

Vertical 3 dB Beam Width: 65°

Gain: 6 dBil max.

Axial Ratio: 1.5 dB max.

DC Resistance: 10K Ohm

Front to Back Ratio: 18 dB

Power: 2 Watts

Transport Vibration: IEC-68 series

UV Rating: F2 per UL 746C

## AN400

### High-Performance Area Antenna



#### Physical Characteristics

Dimensions:	28.3 in. L x 12.5 in. W x 1.5 in. D 71.7 cm L x 31.7 cm W x 3.8 cm D
Weight:	8 lbs./3.6 Kg
Casing:	Aluminum with polycarbonate cover
Polarization:	Two circular polarized patch array

#### User Environment

Frequency Range:	900-928 MHz
Operating Temperature:	+32° to +122° F/0° to +50° C
Storage Temperature:	-4° to +158° F/-20° to +70° C
Connectors:	2 type "N" female connectors
Voltage Standing Wave Ratio (VSWR):	1.25
Isolation:	-37 db
3db Beam Width:	60°
Gain:	6.0 dBi linear

## AN200

### General Purpose Indoor-Outdoor Antenna



#### Physical Characteristics






Dimensions:	11.1 in. L x 11.1 in. W x 1.9 in. D 28.19 cm L x 28.19 cm W x 4.83 cm D
Weight:	3 lbs./1.26 kg

#### User Environment

Frequency Range:	900-928 MHz
Operating Temperature:	-40° to +149° F/-40° to +65° C
Connector:	Type "N" female
Connector Position:	Rear
Return Loss (VSWR):	20 dB (1.22)
Cold Test:	IEC-68-2-1 (-40° F/-40° C for 24 hours)
Heat Test:	IEC-68-2-2 (158° F/70° C for 24 hours)
Temperature Shock Test:	IEC-68-2-14 (-40° F rising to 158° F/-40° C rising to 70° C in 10 cycles of 60 minutes each)
Humidity Test:	IEC-68-2-30 (77° to 104° F/-25° to 40° C 24 hour cycles of 90% relative humidity)
Rain Test:	IEC-68-2-18 (8 hr min in rain chamber at 43 psi)
Salt Fog Test:	IEC-68-2-11 (96 hours, repetitive cycling)
Random Vibration Test:	IEC-68-2-6 (10 to 150 Hz, 05 g, 1 hour in each of 2 axes)
Nominal Impedance:	50 Ohm
Gain in dBi linear:	6.0
Impedance, DC:	10 kOhm +/- 5%
Polarization:	RHCP or LHCP
Axial Ratio at Boresight:	< 3 db AZ, EL BW: 60°
Front to Back Ratio:	<10 db
Max Input Power:	20 watts

# Choose the right antenna for your application

Motorola's complete family of RFID antennas meets the needs of virtually any RFID application. Choose the antenna that is designed for your environment — carpeted, industrial or outdoors, delivers the right level of performance, meets mounting requirements and fits in your budget.

Antenna		AN200	AN400	AN480	AN710	AN720
						
Environment	Business-class			●	●	●
	Industrial-class – Indoor	●	●	●		●
	Industrial-class – Outdoor	●				●
Value Solution				●	●	
Compact					●	●
High Performance/High Gain (dB)		●	●	●		
Polarization		R & L Circular	R & L Circular/ Dual	R & L Circular	L Circular	L Circular

**Notices:**

Repairs of Motorola RFID antennas for fixed readers may require the use of Motorola proprietary parts (and/or Motorola proprietary information). Motorola will sell these parts (and provide this proprietary information) only to end-user customers for self-service. Applicable in the U.S. For all other countries, please contact your Motorola account manager or the local Motorola Customer Service representative in your area for further details.

The antenna frequency specification and label is a characteristic trait of the antenna's peak frequency response. The RFID reader, when professionally installed and selected for a country of operation, dictates the actual frequency of transmission/reception to ensure regulatory compliance for operation in a designated country. The actual frequency specification of the antenna is not material to regulatory compliance.

The AN400 and AN200 will perform reasonably well in EU frequency in most applications.

## SPECIFICATION SHEET

RFID ANTENNA FAMILY  
RFID antennas for fixed readers



**MOTOROLA**

[motorola.com](http://motorola.com)

Part number SS-RFIDANTENNA. Printed in USA 07/11. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2011 Motorola Solutions, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.

# Legacy Technology Services

**We Rent & Sell All Types Of Barcode Equipment**

Call now to talk to an expert

**866-271-9891**

[www.LegacyGlobal.com](http://www.LegacyGlobal.com)

Some brands we carry



MOTOROLA

**Intermec**

**DATALOGIC**™

**Honeywell**

**EQUINOX**  
PAYMENTS



## About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

## Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

## Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

## Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

## Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
  - Data destruction
  - Hardware disposal
  - Auditing services

## Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

## Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



[Legacy, Inc.](http://Legacy, Inc.)

160 West Road,  
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684