



THE WIRED ETHERNET SWITCH FOR UNIFIED WIRED-WIRELESS NETWORKS

EX 3500 ETHERNET SWITCH

GET ALL THE WIRED NETWORKING FEATURES YOU NEED, PLUS THE SIMPLICITY OF A SINGLE POINT OF MANAGEMENT FOR ALL YOUR WIRELESS AND WIRED NETWORK INFRASTRUCTURE

The perfect complement for your Motorola Solutions WLAN, the EX 3500 addresses all the access layer needs in your branch and remote office deployments. This economical, standalone solution offers all the features you need in a wired access switch, with the advantages of centralized management through your Motorola WiNG-based NX Integrated Services Platforms. Now, not only can you easily support your wired networking requirements, you can also monitor and manage all your wired and wireless equipment with the simplicity of a single pane of glass, reducing management time and complexity.

FEATURES AND BENEFITS HIGHLIGHTS

High performance GbE wired switch for your converged network

- Fixed configuration 24 GbE and 48 GbE ports for all the branch/low-density converged wired networking requirements.
- 4 front panel SFP GbE ports for upstream connectivity.

Comprehensive security features keep your network and data safe

- User access and authentication features include access control, standardsbased 802.1x port-level access control, MAC authentication, MAC limiting.
- Threat detection features include DHCP snooping, Dynamic ARP inspection, Proxy ARP, IP source guard, Broadcast/multicast storm control, MAC based port security.

Easy and cost-effective deployment with Power-over-Ethernet (PoE)

- Eliminates the cost of running power to wired devices, such as access points, IP phones and video cameras.
- PoE available on all ports, both 24 and 48 port models, simultaneously.
- Comprehensive protocol support for 802.3af/802.3at (PoE/PoE+) at 15.4W or 30W provides future proofing, ensuring that the EX 3500 you buy today can provide power to the PoE-enabled devices of the future.

Quality of Service (QoS) ensures network performance

- Supports multi-layer QoS including 802.1p CoS and DiffServ standards for data/voice and video traffic and maintaining end-to-end traffic prioritizations.
- Scheduling policy options include Strict, WRR and Strict-WRR.

Auto-discovery and centralized remote management — through your NX Integrated Services Platforms

- Industry standard LLDP (Link Layer Discovery Protocol) and LLDP-MED (Link Layer Discovery Protocol-Media Endpoint Discovery) enable auto discovery of devices, VLAN configuration and identification of power requirements for efficient power management.
- Remotely stage, configure, monitor and manage the wired EX 3500 through your NX Integrated Services Platforms, just like all of your wireless infrastructure, providing the simplicity of a single management windowpane for your entire wired and wireless network.

TECHNICAL SPECIFICATIONS

PART NUMBERS

EX-3524-0000-00-WR: 24GE + 4SFP Wired PoE/PoE+ Switch EX-3548-0000-00-WR: 48GE + 4SFP Wired PoE/PoE+ Switch

	EX 3524	EX 3548
PHYSICAL CHARACTER	STICS	<u>'</u>
Form factor	1U Rack Mount	
Dimensions (WxDxH)	44.0 x 28.0 x 4.4 cm 17.32 x 11.0 x 1.73 in.	44.0 x 40.9 x 4.4 cm 17.32 x 16.10 x 1.73 in.
Weight	3.6 kg (7.83 lb.)	6.6 kg (14.55 lb.)
AC input	100-240 V, 50-60Hz, 6A	100-240 V, 50-60Hz, 12A
Power Budget (PoE)	Up to 370W	Up to 740W
Ethernet Ports	24xGbE + 4x1G SFP	48xGbE + 4x1G SFP
ENVIRONMENTAL RANG	GES	
Operating temperature	32° F to 122° F/0° C to 50° C	
Storage temperature	-40° F to 158° F/-40° C to 70° C	
Operating altitude	4,004 m (13,136 ft.)	2,000 m (6,561 ft.)
Non-operating altitude	4572 m (15,000 ft.)	
Operating humidity	10% to 90% (non-condensing)	
Storage humidity	10% to 90% (non-condensing)	
SWITCHING/LAYER-2 TI	HROUGHPUT	
Packet switching in Gbps	56	104
Throughput in Mpps	41.664	77.376
COMMON FEATURES		
Optics and connectors		
100BASE-FX: 100 Mbps at fu	ıll duplex (SFP)	
1000BASE-T: 10/100 Mbps a	t half/full duplex, 1000 Mbp	s at full duplex
1000BASE-SX/LX/LH: 1000	Mbps at full duplex (SFP)	
Layer-2 switching		
Max MAC addresses: 16K		
Jumbo frames (bytes): 10K		
Number of VLANs: 4K (256 a	ctive)	
Port-based-VLAN		

Layer-2 switching (continued)
MAC-based-VLAN
Voice VLAN
Private VLAN: Traffic Segmentation
Multicast VLAN registration
IEEE 802.1a/b Link Layer Discovery Protocol (LLDP)
LLDP-MED with VoIP integration
IEEE 802.1d: Spanning Tree Protocol
IEEE 802.1p: CoS prioritization
IEEE 802.1v: Protocol-based VLAN
IEEE 802.10: VLAN tagging
IEEE 802.10-in-0: VLAN stacking
IEEE 802.1s: Multiple Spanning Tree protocol (MSTP)
Number of MST instances: 32
IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1x: Port Authentication
IEEE 802.3: 10BASE-T
IEEE 802.3u: 100BASE-T
IEEE 802.3ab: 1000BASE-T
IEEE 802.3z: 1000BASE-X
IEEE 802.3af: PoE
IEEE 802.3at: PoE+
IEEE 802.3ad: Link Aggregation Control Protocol (LACP)
Layer-3 features
Static Routing
Max IPv4 unicast routes: 32
Max ARP entries: 104
Security and access control
DHCP snooping
Dynamic ARP inspection
Proxy ARP
IP Source guard
IP Filter (Management IP Filter for Telnet/HTTP/SNMP access)

Security and access control (continued)
Port security (MAC based)
Access Control Lists (512 entries)
Port-based ACL
802.1x port authentication
MAC authentication
MAC limiting
Storm control: Broadcast, multicast traffic threshold
Quality of service (QoS) and rate-limiting
Scheduling: Strict, Strict-WRR, WRR
802.1p, DSCP/IP precedence trust and marking
Queues per port: 4
Input/output rate limits (per port)
Port trunking/mirroring
Mirroring: 6 sessions (multi-source-to-one-destination)
Static trunks (EtherChannel compliant)
802.3ad: Dynamic trunks (LACP)
Number of LAGs supported: 12
Max number of ports/LAG: 8
Multicast
IGMP snooping: 255 groups
IGMP: v1, v2, v3
Management/services
CLI
Web interface
Out-of-band management : Console port
SSH v1, v2
BOOTP client
DCHP client
DNS client, proxy
Remote Monitoring (RMON) Groups 1,2,3,9
Simple Network Time Protocol (SNTP)

Management/services (continued)	
Simple Network Management Protocol (SNMP): v1, v2, v3	
RADIUS (client)	
TACACS+ (client)	
HTTP/HTTPS	
Logging: Syslog	
FTP/TFTP	
Telnet	
Troubleshooting	
Diagnostics: show and debug commands	
Traffic mirroring (port-mirroring)	

Simplify the deployment and management of your wired and wireless network with the EX 3500 Ethernet Switch.

For more information on the EX 3500, please visit www.motorolasolutions.comwlan or access our global contact directory at www.motorolasolutions.com/contactus

Part number: SS-EX3500. Printed in USA 02/14. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2014 Motorola Solutions, Inc. All rights reserved.

MOTOROLA WLAN UNLEASH OPTIMAL



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

 Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com

Some brands we carry





















