

Symbol LS3408-ER

Extended range rugged scanner



FEATURES

Flexible working range: 0.25" / 0.64 cm to 45 ft. / 13.7 m
Improves user productivity

Ergonomic, rugged industrial design withstands up to 50 drops to concrete from 6.5 ft. (2m) and 2,500 3 ft. (1m) tumbles (5,000 hits)

Ensures maximum reliability with less down time due to accidental drops

IP65 sealing rating (electronic enclosure)

Protects against water and dust to ensure reliable performance in rough conditions

Bright 650nm laser aiming dotDelivers clearly visible line for more accurate scanning

Dual-scan angle switches from standard to wide under software control

Offers fast, accurate bar code reading on menus and pick lists

Redefining performance for maximum industrial mobility

The rugged Symbol LS3408-ER handheld scanner from Motorola delivers superior performance and versatility for your scan-intensive industrial applications. In the yard, warehouse, distribution center, manufacturing plant or retail store, the Symbol LS3408-ER handheld scanner offers best-in-class performance, excellent reliability and user-friendly ergonomics to create a more productive mobile environment. Multiple on-board interfaces ensure flexible plug and play host connectivity.

Advanced data capture features for industrial-grade applications

The Symbol LS3408-ER offers an outstanding reading range, providing the flexibility to enable a wide range of industrial applications. Industry-leading impact tests ensure reliable performance in spite of the inevitable accidental drops. The device is impervious to dust and water, and its exit window is scratch-resistant and recessed for the highest level of durability. As a result, you avoid unnecessary equipment downtime or expensive equipment replacement costs.

For applications requiring quick access and convenient storage, the Symbol LS3408-ER features a built-in metal hook for attachment to a pulley. Two large LED-enhancing windows and an extra loud 80 decibel (db) beeper are strategically placed on the scanner for clear and audible feedback to users.

The smartest way to capture missioncritical information

The extended range Symbol LS3408-ER is designed specifically for industrial applications. When you choose the Symbol LS3408-ER, you receive the added assurance of purchasing from Motorola — a company with proven advanced data capture capabilities and millions of scanner installations worldwide

For more information on the Symbol LS3408-ER and its full line of accessories, access our global contact directory at www.motorola.com/enterprisemobility/contactus or visit us on the web at www.motorola.com/ls3408er

SYMBOL LS3408-ER Extended range rugged scanner

Multiple on-board interfaces

Ensures flexible connectivity, allowing for host "future proofing"

Advanced data formatting (ADF)

Eliminates costly modifications to the host software

Flash memory

Facilitates updates and customization of product in the field

Universal cable set

Allows for easy replacement and/or upgrades

Supports GS1DataBar Symbologies (formerly RSS)

Compatible with emerging symbology to leverage your hardware investment

Symbol LS3408-ER Specifications

Physical Characteris	rtics			
Dimensions:	7.34 in. H x 4.82 in. W x 2.93 in. D 18.65 cm H x 12.25 cm W x 7.43 cm D			
Weight (w/o cable):	12.56 oz./356 g			
Power Requirements:	4.5 - 14 VDC			
Stand-by Current:	50 mA			
Power Sources:	Depending on host: • Host power • External power supply			
Color:	Twilight Black/Yellow			
Performance Charac	eteristics			
Scanner Type:	Retrocollective			
Light Source:	650 nm visible laser diode			
Scan Repetition:	36 scans per second typical			
Min. Element Width:	7.5 mil/0.191 mm			
Working Distance:	See Decode Zone			
Print Contrast:	25% minimum reflective difference			
Roll (Tilt):1	± 10° from normal			
Pitch: ²	± 65° from normal			
Skew (Yaw):3	± 60° from normal			
Decode Capability:	UPC/EAN, UPC/EAN with Supplementals, GS1-128 (formerly UCC/EAN 128), JAN 8 & 13, Code 39, Code 39 Full ASCII, Code 39 Trioptic, Code 128, Code 128 Full ASCII, Codabar (NW7), Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, Code 32, Bookland EAN, IATA, GS1DataBar (formerly RSS)			
Interfaces Supported:	RS232, Keyboard Wedge, Wand Emulation, Scanner Emulation, IBM 468X/469X, USB and Synapse			
User Environment				
Operating Temp.:	-22° to 122° F/-30° to 50° C			
Storage Temp.:	-40° to 158° F/-40° to 70° C			
Humidity:	5% to 95% relative humidity, non-condensing			
Sealing:	Sealed to IP65 specifications			
Drop Specifications:	Unit functions normally after 50 drops to concrete from 6.5 ft. (2m)			
Ambient Light Immunity:	Immune to direct exposure of normal office and factory lighting conditions, as well as direct exposure to sunlight; Indoor: 450 ft. candles/4,84 LUX; Outdoor: 4,000 ft. candles/43,040 LUX			

Electrostatic Discharge (ESD):	Conforms to 20 kV air discharge and 8 kV of contact discharge	
Regulatory		
Input Transient	IEC 1000-4-(2,3,4,5,6,11) Protection:	
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Japan VCCI/MITI/Dentori	
Laser Safety:	IEC825-1 Class 2	
Warranty		

Warranty

The Symbol LS3408-ER is warranted against defects in workmanship and materials for a period of 3 years (36 months) from date of shipment, provided that the product remains unmodified and is operated under normal and proper conditions. See full warranty for details.

- 1 Roll (Tilt): Controlled by rotating the wrist clockwise or counterclockwise
- Pitch: Controlled by dropping or raising the wrist
- 3 Skew (Yaw): Controlled by rotating the wrist from left to right or vice versa

	Depth of Field		
Label Density	LS3408-ER		
Paper Label	English	Metric	
Code 39 - 7.5 mil	0.25" - 20.00"	0.64 - 50.80 cm	
Code 39 - 10 mil	2.00" - 32.00"	5.08 - 81.28 cm	
Code 39 - 15 mil	3.00" - 69.00"	7.62 - 175.26 cm	
Code 39 - 20 mil	3.00" - 94.00"	7.62 - 238.76 cm	
Code 39 - 55 mil	15.00" - 180.00"	38.10 - 457.20 cm	
Reflective Label			
Code 39 - 70 mil	Up to 30 ft.	Up to 9.27 m	
Code 39 - 100 mil	Up to 45 ft.	Up to 13.72 m	

For more detailed information, please see the Product Reference Guide in the Resource tab at www.motorola.com/ls3408er.







motorola.com

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















