ROBUST PERFORMANCE THAT LEADS AND EXCEEDS

The VX 520 leads the way with unprecedented performance, mission-critical features and more of everything you want in a countertop payment device. More revenue opportunities. Flexible connectivity. Uncompromising security and dependability. All on the proven VX platform.



Proven, Popular Platform — Evolved For Today

- Runs on the advanced VX Evolution platform powered by the time-tested Verix operating system, with over 7 million Verix-based devices sold
- Backward compatibility eliminates retraining for sales, support and deployment
- Consistency and high usability ensure lower cost of ownership and ease of use

Unparalleled Features Deliver Next Level Performance

- Generates new recurring revenues from value-added applications, thanks to an extraordinary increase in memory of 160 MB standard, increasing to over 500 MB
- Takes advantage of the industry's fastest processor to handle encryption, decryption and processing at lightning speeds — moving more transactions in the same time for greater profits
- Offers a full range of connectivity options with choice of dial, dial and Ethernet, or dial, Ethernet and GPRS - optional battery enables mobility because there are no distance constraints
- Uniquely designed communication port area neatly connects cables under the device for clean countertops
- Incorporates an integrated contactless reader (optional) into the sleek device
- Combines an ergonomic design, small footprint and unique cable management system to optimize handover usage

Reassuring Confidence From Full Spectrum Security

- PCI PED 2.0 approval is standard, with the option of PCI PTS 3.0
- Provides end-to-end encryption with VeriShield Protect, to maximize protection against fraud and misuse

Superior Value From Extended Life Design

- · Leverages VeriFone's unmatched reputation for quality with longer-life components to extend the field life of devices and minimize repair frequency
- Metal dome keypad design delivers one of the most reliable keypads in the POS industry
- Landed smart card reader is built for 5x the life expectancy of friction readers

Processor

400 MHz ARM11 32-bit processor

Memory 160 MB (128 MB of Flash, 32 MB of SDRAM) standard, can exceed up to 500 MB

128 x 64 pixel graphical (white backlit) LCD with backlighting; supports up to 8 lines x 21 characters

Magnetic Card Reader

Triple track (tracks 1, 2, 3), high coercivity, bi-directional

Primary Smart Card (optional)

ISO 7816, 1.8V, 3V, 5V; synchronous and asynchronous cards; EMV Level 1 and 2 Type approved

SAM Card Reader (optional)

3 Security Access Modules (SAMs)

Kevpad

3 x 4 numeric backlit keypad, plus 8 soft-function keys and 4 screenaddressable kevs

Peripheral Ports

One Ethernet (10/100BaseT), one telco, one RS-232 port, one USB 2.0 Host port and one USB Client port supporting peripherals including PIN pads and contactless devices

Printer

Integrated thermal with graphics capabilities, 18 lines per second, 24 or 32 columns; standard roll paper 58 mm (2.25 in.) x 25 M (82 ft.), single ply

Standard 56 kbps modem Bell 103/212a, CCITT V.21/V.22/V.22bis/V.32/V.32bis (300/1200/2400/9600/14400/ 33.6/56 and HC FastConnect for 1200bps)

Radio (optional)

GPRS Quad band radio On 850/900/1800/1900 MHz

Contactless Support (optional)

MasterCard PayPass M/Chip MasterCard PayPass MagStripe Visa payWave MSD Visa payWave qVSDC Discover Zip American Express ExpressPay Pass-through access to ISO 14443-4 and MiFare card, for direct host terminal Base access Secure SoftSAM protects Hardware SAM optional

Protocols

Application selects between asynchronous protocols (Visa 1, Visa 2, and others) and synchronous protocols (including ISO 8583/SDLC); Communication protocol is V.92/V.34/ V.32 BIS/V.32



PCI SECURITY OPTIONS





Standard

Premium

Security

SSL v3.0, 3DES encryption, Master/ Session and DUKPT key management; PCI PED 2.0 standard; PCI PTS 3.0 optional; VeriShield file authentication


Physical

Length: 203 mm (8.0 in.); Width: 87 mm (3.4 in.); Height: 76 mm (3.0 in.); Weight: 500g

Environmental

0° to 40° C (32° to 104° F) operating temperature; 5% to 90% relative humidity, non-condensing; -20° to 60° C (-4° to 140° F) storage temperature

AC input 100 - 240 VAC, 50/60 Hz; DC Output 8V 2.25A





Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















