CPL11046 1704-English outside final 41x29.3cm

SPECIFICATIONS

11

1704 2D scanner

| | T. |
|--|----|
|--|----|


| | | | | | 1704 | 17 | 04DC | (can capture A4 d | locument) |
|---|---------------|--|---|----------|----------------------------------|-----------|--------------------|-------------------|-------------------|
| | Performance | Category | Category 2D barcode scanner | | | | | | |
| | | Optical sensor | 1280 (H) × 1024 (V) | | | | | | |
| | | Light source | Red LED 630 nm±20 nm | | | | | | |
| | | Resolution | 5 mil 1D 6.67 mil 2D | | | | | | |
| | | | Code 39 | 5 mil | 6.4 to 17.8 cm / 2.5 to 7 in. | Code 39 | 5 mil | 10.7 to 25.4 cm | / 4.2 to 10 in. |
| | | | Code 39 | 7.5 mil | 6.4 to 22.9 cm / 2.5 to 9 in. | Code 39 | 7.5 mil | 6.4 to 36.3 cm / | 2.5 to 14.3 in. |
| | | | UPCA | 13 mil | 6.4 to 25.4 cm / 2.5 to 10 in. | UPCA | 13 mil | 6.4 to 41.4 cm / | 2.5 to 16.3 in. |
| | | Depth of field at 80% MRD | Code 39 | 20 mil | 6.4 to 36.8 cm / 2.5 to 14.5 in. | Code 39 | 20 mil | 7.1 to 58.4 cm / | 2.8 to 23 in. |
| | | | PDF 417 | 6.67 mil | 7.6 to 17.3 cm / 3 to 6.8 in. | PDF 417 | 6.67 mil | 12.2 to 24.9 cm | |
| | | | PDF 417 | 10 mil | 7.6 to 19.8 cm / 3 to 7.8 in. | PDF 417 | 10 mil | 10.2 to 32.3 cm | |
| | | | PDF 417 | 15 mil | 11.9 to 23.6 cm / 4.7 to 9.3 in. | PDF 417 | 15 mil | 11.9 to 38.9 cm | / 4.7 to 15.3 in. |
| | | Scanning angle | | | Pitch ±65° | Skew ± | ±60° | | |
| | | PCS | | | Minimu | m 25% | | | |
| | | Frame rate | | | 30 frame: | s/second | ł | | |
| | | Interfaces supported | | RS2 | 32 / Keyboard wedge / I | JSB HID | / USB | Virtual COM | |
| | | Barcodes supported | <i>1D symbology:</i> Codabar, Code 11, Code 39, Code 93, Code 128, Discret 2 of 5, Interleaved 2 of 5, MSI, RSS, UPC/EAN, UPC/EAN128 | | | | | | |
| | | | 2D symbology: Aztec and composites, DataMatrix, Maxicode, PDF417, QRCode Postal codes: Australia, Japan, U.S. Postnet, U.S. Planet, UK | | | | | | |
| | | Programmable features | | | | | | | |
| | | Language support | US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Japanese | | | | | | |
| | Physical | Weight including battery | | | | | | | |
| | , | Color | | | | low | | | |
| | | Switch | | | | | | | |
| _ | Electrical | | Voltage 4.5 to 24V er consumption 45mA / 378mA @5V | | | | | | |
| | | Power consumption Standby / Operating | | | | | | | |
| | User | Operating temperature | | | -10° to 55°C | / 14° to | 131°F ¹ | | |
| | environment | Storage temperature | | | | | | | |
| | | Humidity Non-condensing | | | | | | | |
| | | Impact resistance | 1.8 m / 5.9 ft., five drops per side | | | | | | |
| | | Electrostatic discharge | ±15 kV air discharge, ±8 kV contact discharge | | | | | | |
| | | Ingress protection | ו IP54 | | | | | | |
| | | EMC regulation | | | BSMI, CE, C | -Tick, FC | C, IC | | |
| | Configuration | | Setup options include Windows [®] based ScanMaster software by direct connection or printing out barcode settings | | | | | | |
| | Accessories | | Power Hood | | | | | | T |
| | Warranty | | 3 years / engine 1 year | | | | | | Power Hood |
| | | | | | | | | | |

 $^1adapter's$ operating temperature is 0° to $40^\circ C$ (32° to $104^\circ F$)

© 2011 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.







1704 2D scanner

CipherLab's handheld 2D scanner enables you to capture more symbologies in nearly any application. For manufacturing, warehouse, logistics, and more, you can depend on the CipherLab 1704 scanner to help save money and increase productivity.

1704 rugged 2D scanner

Rugged Value, **High Performance**

LONG-LASTING VALUE

We designed the 1704 to give you long-lasting value by making it rugged with a low-cost investment. Built to IP54 specifications and repeatedly drop-tested from 1.8 meters, the 1704 withstands sudden shock, dusty environments, and splashing water. Even in the harsh environments of manufacturing, warehousing, and logistics it keeps delivering high performance for years to come.

1.3 MEGAPIXEL IMAGE CAPTURE

With the 1704, you can easily enable higher levels of authentication. The 1704's 1.3 megapixel, high-resolution imager lets you capture signatures for processes requiring a greater degree of authorization or documentation, such as confirmation of a damaged shipment. An option allows capture of documents as large as A4.

ROBUST DECODING CAPABILITIES

The 1704 scanner captures both 2D and 1D barcodes in the same rugged unit. Its high-resolution imager is ideal for damaged or poorly printed barcodes, allowing accurate data capture even when barcodes are scratched and damaged.

TRIPLE ALERTS FOR EVERY ENVIRONMENT

With three modes of "good scan" confirmation, the 1704 allows work to proceed, even in dark, noisy or distracting environments. Choose confirmation signals from a bright LED alert, adjustable volume alert, or vibration in the handle. Few other 2D scanners offer such a complete choice of alerts, tailored to the rigors of your workplace.

Custom-configure vour scanner

software provides a comprehensive tool set to configure the 1704 scanner, edit

Bright LED capture indicator Tactile trigger Ergonomic form for easy use and comfort Adjustable volume and vibration capture confirmation Rugged design: IP54 ingress protection,

1704 FEATURES

Built for harsh work conditions, drop tested to 1.8 meters, sealed to IP54

High-resolution scanning engine captures documents and signature

Multi-mode 'good scan' signals

Adjustable volume, bright LED and exclusive vibrator notify user-even in dark or noisy environment.

04 scanner

SCANMASTER CipherLab's complimentary ScanMaster

format and symbol types, plus more.







1D/2D 1.3 megapixel imager

survives multiple 1.8 meter drops to concrete

USER BENEFITS

Productivity in extreme temperature, humidity situations. Maximized service life for highest return on investment, lowest cost of ownership.

Rich data capture adds functionality and performance.









CIPHERLAB PRODUCTS ARE VALUED WORLDWIDE FOR ENGINEERING EXCELLENCE. **OUR RUGGED SCANNERS** ARE ANOTHER EXAMPLE OF **TECHNICAL INNOVATION AND** QUALITY VALUE FOR TODAY'S AIDC SOLUTIONS.

1704 rugged 2D scanner

Rugged Value, **High Performance**

LONG-LASTING VALUE

We designed the 1704 to give you long-lasting value by making it rugged with a low-cost investment. Built to IP54 specifications and repeatedly drop-tested from 1.8 meters, the 1704 withstands sudden shock, dusty environments, and splashing water. Even in the harsh environments of manufacturing, warehousing, and logistics it keeps delivering high performance for years to come.

1.3 MEGAPIXEL IMAGE CAPTURE

With the 1704, you can easily enable higher levels of authentication. The 1704's 1.3 megapixel, high-resolution imager lets you capture signatures for processes requiring a greater degree of authorization or documentation, such as confirmation of a damaged shipment. An option allows capture of documents as large as A4.

ROBUST DECODING CAPABILITIES

The 1704 scanner captures both 2D and 1D barcodes in the same rugged unit. Its high-resolution imager is ideal for damaged or poorly printed barcodes, allowing accurate data capture even when barcodes are scratched and damaged.

TRIPLE ALERTS FOR EVERY ENVIRONMENT

With three modes of "good scan" confirmation, the 1704 allows work to proceed, even in dark, noisy or distracting environments. Choose confirmation signals from a bright LED alert, adjustable volume alert, or vibration in the handle. Few other 2D scanners offer such a complete choice of alerts, tailored to the rigors of your workplace.

Custom-configure vour scanner

software provides a comprehensive tool set to configure the 1704 scanner, edit

Bright LED capture indicator Tactile trigger Ergonomic form for easy use and comfort Adjustable volume and vibration capture confirmation Rugged design: IP54 ingress protection,

1704 FEATURES

Built for harsh work conditions, drop tested to 1.8 meters, sealed to IP54

High-resolution scanning engine captures documents and signature

Multi-mode 'good scan' signals

Adjustable volume, bright LED and exclusive vibrator notify user-even in dark or noisy environment.

04 scanner

SCANMASTER CipherLab's complimentary ScanMaster

format and symbol types, plus more.







1D/2D 1.3 megapixel imager

survives multiple 1.8 meter drops to concrete

USER BENEFITS

Productivity in extreme temperature, humidity situations. Maximized service life for highest return on investment, lowest cost of ownership.

Rich data capture adds functionality and performance.









CIPHERLAB PRODUCTS ARE VALUED WORLDWIDE FOR ENGINEERING EXCELLENCE. **OUR RUGGED SCANNERS** ARE ANOTHER EXAMPLE OF **TECHNICAL INNOVATION AND** QUALITY VALUE FOR TODAY'S AIDC SOLUTIONS.

CPL11046 1704-English outside final 41x29.3cm

SPECIFICATIONS

11

1704 2D scanner

| | T. |
|--|----|
|--|----|


| | | | | | 1704 | 17 | 04DC | (can capture A4 d | locument) |
|---|---------------|--|---|----------|----------------------------------|-----------|--------------------|-------------------|-------------------|
| | Performance | Category | Category 2D barcode scanner | | | | | | |
| | | Optical sensor | 1280 (H) × 1024 (V) | | | | | | |
| | | Light source | Red LED 630 nm±20 nm | | | | | | |
| | | Resolution | 5 mil 1D 6.67 mil 2D | | | | | | |
| | | | Code 39 | 5 mil | 6.4 to 17.8 cm / 2.5 to 7 in. | Code 39 | 5 mil | 10.7 to 25.4 cm | / 4.2 to 10 in. |
| | | | Code 39 | 7.5 mil | 6.4 to 22.9 cm / 2.5 to 9 in. | Code 39 | 7.5 mil | 6.4 to 36.3 cm / | 2.5 to 14.3 in. |
| | | | UPCA | 13 mil | 6.4 to 25.4 cm / 2.5 to 10 in. | UPCA | 13 mil | 6.4 to 41.4 cm / | 2.5 to 16.3 in. |
| | | Depth of field at 80% MRD | Code 39 | 20 mil | 6.4 to 36.8 cm / 2.5 to 14.5 in. | Code 39 | 20 mil | 7.1 to 58.4 cm / | 2.8 to 23 in. |
| | | | PDF 417 | 6.67 mil | 7.6 to 17.3 cm / 3 to 6.8 in. | PDF 417 | 6.67 mil | 12.2 to 24.9 cm | |
| | | | PDF 417 | 10 mil | 7.6 to 19.8 cm / 3 to 7.8 in. | PDF 417 | 10 mil | 10.2 to 32.3 cm | |
| | | | PDF 417 | 15 mil | 11.9 to 23.6 cm / 4.7 to 9.3 in. | PDF 417 | 15 mil | 11.9 to 38.9 cm | / 4.7 to 15.3 in. |
| | | Scanning angle | | | Pitch ±65° | Skew ± | ±60° | | |
| | | PCS | | | Minimu | m 25% | | | |
| | | Frame rate | | | 30 frame: | s/second | ł | | |
| | | Interfaces supported | | RS2 | 32 / Keyboard wedge / I | JSB HID | / USB | Virtual COM | |
| | | Barcodes supported | <i>1D symbology:</i> Codabar, Code 11, Code 39, Code 93, Code 128, Discret 2 of 5, Interleaved 2 of 5, MSI, RSS, UPC/EAN, UPC/EAN128 | | | | | | |
| | | | 2D symbology: Aztec and composites, DataMatrix, Maxicode, PDF417, QRCode Postal codes: Australia, Japan, U.S. Postnet, U.S. Planet, UK | | | | | | |
| | | Programmable features | | | | | | | |
| | | Language support | US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Japanese | | | | | | |
| | Physical | Weight including battery | | | | | | | |
| | , | Color | | | | low | | | |
| | | Switch | | | | | | | |
| _ | Electrical | | Voltage 4.5 to 24V er consumption 45mA / 378mA @5V | | | | | | |
| | | Power consumption Standby / Operating | | | | | | | |
| | User | Operating temperature | | | -10° to 55°C | / 14° to | 131°F ¹ | | |
| | environment | Storage temperature | | | | | | | |
| | | Humidity Non-condensing | | | | | | | |
| | | Impact resistance | 1.8 m / 5.9 ft., five drops per side | | | | | | |
| | | Electrostatic discharge | ±15 kV air discharge, ±8 kV contact discharge | | | | | | |
| | | Ingress protection | ו IP54 | | | | | | |
| | | EMC regulation | | | BSMI, CE, C | -Tick, FC | C, IC | | |
| | Configuration | | Setup options include Windows [®] based ScanMaster software by direct connection or printing out barcode settings | | | | | | |
| | Accessories | | Power Hood | | | | | | T |
| | Warranty | | 3 years / engine 1 year | | | | | | Power Hood |
| | | | | | | | | | |

 $^1adapter's$ operating temperature is 0° to $40^\circ C$ (32° to $104^\circ F$)

© 2011 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.







1704 2D scanner

CipherLab's handheld 2D scanner enables you to capture more symbologies in nearly any application. For manufacturing, warehouse, logistics, and more, you can depend on the CipherLab 1704 scanner to help save money and increase productivity.

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













