# ēlo

## 1598L 15-inch LCD

**Open-Frame Touchscreen** 





**Integrated Touch** 



**Commercial Grade** 



**3-Year Warranty** 

### **Product Overview**

The Elo 1598L 15-inch open-frame LCD touch display features a slim design and narrow outside dimensions due to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. The 1598L includes a 500 nit high bright display and extended temperature range to 50° C (122° F) making it ideal for factory automation and other instrumentation control applications. With an optional 24 VDC converter kit included with the unit, manufacturers can leverage a common 24V power supply in their design with a single AC connection. This compact touch display is designed for touch with proven Elo expertise and provides stable, drift-free operation with outstanding image clarity and light transmission—for accurate touch responses and vivid images. Instantly grabbing and holding users' attention, the 15-inch open frame is perfect for kiosks, casino and amusement, retail self-service, and industrial automation environments.

The 1598L is available with Elo's industry-leading AccuTouch' five-wire resistive with single-touch technology

The touchscreen is sealed against dirt, dust and liquids, to simplify integration into the final enclosure

Video Interfaces: HDMI, VGA & Display Port

#### 1598L 15-inch Open-Frame Touchscreen

Specifications	
Model	1598L
Color	Black
Active Display Area	11.97" x 8.98" / 304.1mm x 228.1mm
Diagonal	15"
Aspect Ratio	4:3
Dimensions	13.24" x 10.41" x 1.65" / 336.4mm x 264.4mm x 41.9mm
Native Resolution	1024 x 768 at 60, 75 Hz
Other Supported Resolutions	640 x 480 at 60 Hz; 720 x 400 at 70 Hz; 800 x 500 at 60 Hz; 800 x 600 at 56, 60Hz
Number of Colors	16.2 million
Number of Touches	Single-touch
Brightness (typical)	LCD Panel: 500 nits; AccuTouch: 400 nits
Response (typical)	35 msec
Viewing Angle	Horizontal: ±85° / 170°; Vertical: ±85° / 170°
Contrast Ratio	1500:1
Contrast Natio	Accessible through switches on the unit's tethered OSD Control box.
	Controls: Menu, Up, Down, Select, Power
0.0	Settings: Brightness, Contrast, Clock, Phase, H-Position, V-Position, Auto-Adjust, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD
On-Screen Display	H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode
	Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese
	Lockouts: OSD, Power
	HDMI V1.3 Type A receptacle for HDMI input
VC 1	Analog VGA on Female DB-15 connector
Video	DisplayPort V1.1a - Supports later versions of Display Port video input
	Input Video Horizontal Sync frequency range: 30 - 60KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
	External DC - Optional power brick (sold separately), Adapter input connector: IEC 60320 C14, Adapter input voltage range: 100-240VAC, 50/60Hz
	Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm
Power	(+/- 0.3mm) barrel depth)
	Monitor input power signal specifications: 12VDC +/- 5%
	ON (monitor + power brick): 14.1W
Power Consumption	SLEEP (monitor + power brick): 1.5W
	OFF (monitor + power brick): 0.5W
Temperature	Operating: 0° C to 50° C / 32° F to 122° F; Storage: -20° C to 70° C / -4° F to 158° F
Humidity	Operating: 20% to 80%; Storage: 10% to 95%
Weight	Unpackaged: 6.4 lbs / 2.9 kg; Packaged: 10.36 lbs / 4.7 kg
Shipping Dimensions	17.09" x 14.76" x 6.89" / 434mm x 375mm x 175mm
	75 mm and 100 mm VESA mount
M	2-hole mounting interface on all 4 sides
Mounting Options	Front mount with optional bezel kit  Rack mount with optional bezel kit
	See dimensional drawings for details
Warranty	3 years standard
MTBF	50,000 hours demonstrated
Agency Approvals	UL, FCC; RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; RoHS, China RoHS, WEEE, IMERC
Agency Approvais	HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, User Manual CD and Quick Install Guide; "L" (Side Mount) Brackets w/Screws, EEI Label, Japan
What's in the Box	Class-B TM info sheet

### **Ordering Information**

Model	Part Number	Technology	Interface	Surface Treatment	Video Interface	Availability
1598L	E126407	AccuTouch	Dual serial/USB	Antiglare	HDMI, VGA & Display Port	Worldwide

### **Extended Warranty Options**

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo advance unit replacement for touchmonitors

### **Optional Peripherals / Accessories**

Part Number	Description
E483757	OSD Remote
E546861	Replacement Cable Kit for 90 Series
E203787	15-inch "L" (Side Mount) Brackets
E323425	15-inch Front Mount Bezel Kit
E295006	15-inch Rack Mount Bracket Kit
E538507	DVI-D to HDMI Cable Kit
E582895	DP to DP Cable Kit
E239980	Power Converter Kit - 24V DC to 12V DC



### **Legacy Technology Services**

### We Rent & Sell All Types Of Barcode Equipment

### Call now to talk to an expert

866-271-9891

### About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

### Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

### Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

#### **Trade-in and Disposal services**

- That old equipment laying around your facility may still have some value.
   Legacy routinely purchases equipment from our clients around the globe.
  - · Data destruction
  - · Hardware disposal
  - Auditing services

#### Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















