

- Designed for medical and healthcare requirements
- Desktop with removable base with mounting options
- 3 year standard warranty



1929LM 19" LCD Desktop Touchmonitor for Medical and Healthcare Settings

The Elo 1929LM 19" LCD Medical Desktop Touchmonitor delivers cost-effective solutions for healthcare professionals and patients. This fully featured touchmonitor offers IntelliTouch surface acoustic wave touchscreen technology which provides stable "drift-free" touch response, outstanding image clarity and resolution, and AccuTouch five-wire resistive technology, the preferred solution for applications that demand reliability, input flexibility, and contamination resistance. Additionally, the 1929LM is equipped with a USB and RS232 combination touch controller, VGA, HDMI, DisplayPort connectors and an included adapter for DVI, built-in audio amp and speakers.

The 1929LM is compliant with multiple safety and electrical certification standards, including EN 60950-1 and EN 60601-1-2 for safety and EN 60950-1, EN55022, EN55024, and EN 60601-1 (3rd Edition) for EMC.

Its new plastic housing with a more densely packed material structure can withstand long term disinfecting with chemicals. Equipped with an LED backlit state-of-the-art LCD panel, the monitor is environmentally friendly with reduced power consumption.

The Elo 1929LM touch monitor is an effective solution for nurse stations, computer-aided therapy, electronic medical record keeping, paperless charting, patient self-check-in, as well as non-medical applications.

Having been "designed for touch" from the drawing board up, the 1929LM features a stable stand with tilting functionality and removable for VESA mount, cable management and cable fastening features to prevent accidental disconnection, OSD controls with lockout capability and a IPx1 drip-resistant housing.



Benefits:

- Densely packed plastic structure to withstand long term chemical disinfection
- Compliant with multiple safety and electrical certifications
- Elo controlled design with long product life cycle and availability
- Additional video connectivity with HDMI and DisplayPort

Applications:

- Nurse stations
- Computer-aided therapy
- Electronic medical records
- Paperless charting
- Patient self-check-in

About Elo

Elo founders pioneered the touch screen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

1929LM 19" LCD Desktop Touchmonitor

Specifications	
Model	1929LM
Color	Black or white
Useful Screen Area	376.3 x 301 mm / 14.8 x 11.8 inches
Monitor Dimensions	432 mm x 390.5 mm x 50.8 mm (188.4 mm w/stand)/17 x 15.37 x 2 inches (7.41 inches w/stand)
Display type	TFT active matrix LCD, LED backlight
Diagonal Size	19.0" diagonal
Aspect Ratio	5:4
Native (Optimal) Resolution	1280 x 1024
Other Supported Resolutions	1280 x 1024 60Hz, 70Hz (Native), 640x350 70Hz, 720x400 70Hz, 640x480 60Hz, 66Hz, 72Hz, 75Hz, 800x600 56Hz, 60Hz, 72Hz, 75Hz, MAC 832x624 75Hz, 1024x768 60Hz, 65Hz, 70Hz, 75Hz, 1152x864 75Hz, 1280x960 60Hz
Colors	16.7 million
Brightness (typical)	LCD Panel: 300 nits; with IntelliTouch: 250 nits; with AccuTouch: 205 nits
Response Time – Total (typical)	15msec
Viewing Angle (typical)	Horizontal 178°; Vertical: 178°
Contrast Ratio (typical)	2000:1
Video	Analog VGA on Female DE-15 connector (cable included) DVI-D (via included adapter) HDMI (cable optional) DisplayPort 1.1 (cable optional)
Audio	Audio input connector: 3.5mm TRS input jack for Line In audio (PC-99 compliant) 3.5mm TRS input jack for Line Out audio (PC-99 compliant) Built-in audio amp Internal Speakers output: 2 x 2W Stereo Speakers
Power	Monitor input power connector: Coaxial Power jack (2.5mm pin diameter, 6.4mm barrel diameter) Monitor input power signal specifications: 12VDC +/- 5% Power Consumption (Typical): ON (monitor only + AC/DC adapter): 28W SLEEP (monitor + AC/DC adapter): 2W OFF (monitor + AC/DC adapter): 1.2W
Weight	Unpackaged: 7.5 kg /16.5 lb; Packaged: 10 kg/22 lb
Shipping Dimensions	530 x 480 x 265 mm/20.8 x 18.8 x 10.4 inches
On-Screen Display (OSD)	Controls: Menu, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD Rotation, Volume, Mute, Recall Defaults, Video Source Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Korean, Polish Lockouts: OSD, Power, Mute Lock Accessible through switches along the bottom
Mounting Options	Detachable stand with VESA 4-hole 100mm mounting interface on rear of unit
Temperature	Operating: 0°C to 40°C /32°F to 104°F; Storage: -20°C to 60°C /-4°F to 140°F
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-90%
Regulatory approvals and declarations	UL - ANSI/AAMI ES 60601-1, Ed. 1, cUL - CAN/CSA C22.2 No. 60601-1-08, EN 60601-1:2006 3rd Edition, IEC 60601-1 3rd Edition, UL - UL 60950-1, 2nd edition, cUL - CSA 22.2 No. 60950-1-07, 2nd edition, CE Mark, RoHS, WEEE, EN 60950-1:2006+A11:2009+A1:2010+A12:2011, IEC 60950-1:2005(2nd edition) + Am 1:2009, FCC Part 15, Class B, ICES-003: 2004, Class B, EN 55011, Class B, EN 55022, Class B, EN 60600-6-1:2007, EN 60601-1-2, EN 61000-3-2, EN 61000-3-3, V-3/2011.04, Class B, V-4/2010.04, CCC, China RoHS, NRCAN (Power Supply), • S-Mark (Power Supply), C-Tick, PSE, VCC, KC Mark, BSMI, EAC
Touch Interface	Serial and USB
Warranty	3 years standard
Mean time between failures (MTBF)	50,000 hours demonstrated

Ordering Information

Model	Part Number	Technology	Color	Surface Treatment	Availability
1929LM	E000166	IntelliTouch	Black	Anti-glare	Worldwide
	E000167	IntelliTouch	White	Anti-glare	Worldwide
	E000168	AccuTouch	Black	Anti-glare	Worldwide
	E000169	AccuTouch	White	Anti-glare	Worldwide

Optional Peripherals

Part Number	Description
E001450	DisplayPort cable kit
E001449	HDMI cable kit
D82064-000	IntelliTouch stylus pen
E448370	Replacement DC Power Supply

Medical and Healthcare Application Disclaimer: It is the sole responsibility of any person intending to commercialize, market or use any of Elo Touch Solutions, Inc. or its family of companies ("Elo") products for medical or healthcare applications to ensure that such product is adequate and appropriate for the person's intended use and complies with all applicable laws, regulations, codes and standards including but not limited to the European Union Medical Device Directive, United States Federal Food, Drug, and Cosmetic Act, regulations of the United States Food and Drug Administration (FDA), and other similar legislation in jurisdictions around the world, and for obtaining and maintaining any required regulatory approvals including but not limited to any required market clearances. Elo has not sought nor received any rulings from the FDA or any other federal, state, or local government agency or notified body as to the safety, effectiveness or appropriateness of its product for such applications. Persons intending to evaluate or use Elo's product for medical or healthcare purposes must rely on their own medical and legal judgment without any representation on the part of Elo.

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8001
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2014 Elo Touch Solutions, Inc. All rights reserved. DS000100, rev A 09/14



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684