



- Deliver interactive brand experiences
- Multi-touch performance with "Built for Touch" reliability
- Optional plug-in computer modules: Microsoft® Windows® with Intel® Core™ or Android with Qualcomm® Snapdragon™ (supports EloView®)
- Thin, commercial-grade touchscreen ideal for kiosks, wayfinding and other office applications
- Touch OSD (no remote needed)

## 4202L 42" Interactive Digital Signage (IDS)

Elo's 4202L 42-inch interactive digital signage touchscreen delivers a professional-grade large format display in a slim, integrated package. Designed from the bottom up for retail, hospitality, healthcare and other commercial markets, the Elo IDS is a high-quality, interactive canvas for attracting and engaging consumers. The 4202L offers system integrators and value-added resellers (VARs) a high performance solution that is easy to deploy and maintain in public environments. At 2 inches (50.5 mm) thin, the 4202L is over 40% thinner than the 4201L and is compliant with the ADA and IBC requirements of less than 4-inch protrusion when mounted with an Elo Low-profile wall-mounting kit.

With a 500 nit LED panel, the 4202L is a bright, high quality display suitable for public environments. Available with a choice of two multi-touch touchscreen technologies, zero-bezel Projected Capacitive (PCAP) or Infrared (IR), both enable up to ten simultaneous touches for multi-user interaction. This touch technology offers a fast and extremely sensitive response similar to the experience on mobile devices and is compatible with Windows 7 and Windows 8 operating systems. The IR touchscreen is 4mm thick with fully tempered glass and the PCAP touchscreen is 2.8mm thick

with chemically strengthened glass.

Low-profile wall mounting kit available with features to allow cable access. State of the art HD display technology is utilized including a high contrast/brightness LED-backlit LCD panel, extended color gamut with movie/ gaming/ photo modes, black level adjustment, and on-screen menu enhancements.

Optional, high performance computer modules are available which turn the 4202L into a completely integrated all-in-one computer—without the need for any cables or additional mounting hardware. Computer modules are available in a choice of four models: ECMG2C-i3 based on a 3.4GHz, Intel Core 4th Gen i3 processor and HD4400 graphics; ECMG2C-i5 based on a 3.7GHz, Intel Core 4th Gen i5 processor and HD4600 graphics; ECMG2C-i7 based on a 4.0GHz, Intel Core 4th Gen i7 processor and HD4600 graphics; ECMG2C-AND based on a Qualcomm® Snapdragon™ processor. The high performance, commercial-grade computer modules make the 4202L a reliable platform that is interoperable with most content management servers and supports optimal partitioning of locally cached and network streamed content.



## PRODUCT OVERVIEW

### Benefits

- Over 40% thinner than the 4201L
- Professional-grade hardware with strengthened touchscreen glass to withstand the rigors of public use
- Thin (<4" mounted) design is attractive and compliant with ADA and IBC protrusion requirements
- Reliable, integrated IDS solution with optional NFC / RFID scanners and webcam kits
- 3 year standard warranty with optional 2 year extended warranty. On-site advance replacement exchange option available in USA
- EloView content and device management enabled
- Intel OPS compliant with available adapter kit
- Flexible mounting in portrait, landscape and table-top orientation

### About Elo

Elo founders pioneered the touch screen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.



## 4202L 42" Interactive Digital Signage (IDS)

Specifications	
Model	4202L
Form Factor	Digital Signage
Bezel Color	Black
Active Display Area (W x H)	36.6" x 20.1" (930.2mm x 523.3mm)
Dimensions (W x D x H)	IR: 39.2" x 2.4" x 23.2" (995.1mm x 61.6mm x 588.1mm) PCAP: 39.2" x 2.0" x 23.2" (995.1mm x 50.5mm x 588.1mm)
Display Technology	Full HD 1920 x 1080 @ 60hz (native) Active matrix TFT LCD with LED backlight (Other resolutions supported)
Mounting Options	VESA 4-hole mount per MIS-F, 400, 400, 6MM
Diagonal Size	42.0" (106.7 cm)
Aspect Ratio	16:9
Number of Colors	16.7 million
Brightness (typical)	LCD Panel 500 nits; with IR 450 nits; with Projected Capacitive 430 nits
Response Time (Tr + Tf) (typical)	8 ms
Viewing Angle (typical)	Horizontal: ±89°/178°; Vertical: ±89°/178°
Contrast Ratio (typical)	4000:1
On-Screen Display (OSD)	<b>Video Settings:</b> Video Port Discovery, Video Source Select, Black Level, Brightness, Contrast, Sharpness & Auto Adjustment <b>Color Settings:</b> Color Temperature, User Preset (for color), Dynamic Color Modes are available in this menu <b>Audio Settings:</b> Audio Source selection is available here. The monitor can be muted & volume adjustments <b>OSD Settings:</b> The OSD Timer and language can be changed in this menu <b>Power Settings:</b> The Power Behavior can be changed in this menu <b>RTC Settings:</b> Time setting & the monitor ON/OFF schedule can be changed within this menu. Daylight Saving time will change the current time by one hour to accommodate daylight savings time. <b>See user manual for full details.</b>
Available I/O Ports	<b>Input:</b> AC power input, USB type B (for Touch), VGA, 2x HDMI, GPIO, DisplayPort, Audio Line in <b>Output:</b> Audio Headphones out, RJ45 (for optional OSD remote)
Video Inputs	Analog VGA on Female DE-15 connector; 2x HDCP-capable HDMI 1.3 on Type A connector; DisplayPort 1.1a connector; Input Video Horizontal Sync frequency range: 31.5-73 KHz; Input Video Vertical Sync (frame rate) frequency range: 47-63Hz
Power	Input power connector: IEC 60320 C14; Input power signal specifications: 100-240VAC 50/60Hz Monitor Only (typical at 120V at 60Hz): ON: 81W; SLEEP: 8.6W; OFF: 2W / (typical at 230V at 50Hz): ON: 80W; SLEEP: 7W; OFF: 2.1W
Audio	Internal Speakers: 4 x 5W stereo speakers; Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out); Headphone output connector: 3.5mm TRS jack
Weight	IR Model: Unpackaged —with ECMG2B: 54.9 lbs (24.9kg); w/o ECMG2B: 48.3 lbs (21.9kg); Packaged: w/o ECMG2B: 61.7 lbs (28.0kg); Projected Capacitive Model: Unpackaged —with ECMG2B: 52.4 lbs (23.8kg); w/o ECMG2B: 45.8 lbs (20.8kg) Packaged: w/o ECMG2B: 59.6 lbs (27.0kg)
Shipping Dimensions	<b>IR:</b> Length: 43.7" (1110 mm) x Width: 8.46" (215 mm) x Height: 28.35" (720 mm) <b>PCAP:</b> Length: 45.28" (1150 mm) x Width: 8.46" (215 mm) x Height: 28.35" (720 mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals and Declarations	UL, FCC; cUL, IC; CB; CE / RFID Supported Protocols: ISO - 14443-A; ISO - 14443-B; ISO - 15693
Accessories	NFC Adapter (E001004), Barcode Reader (E093433), MSR (E001002), ECMG2 Power Module (E275433), OPS Kit (E337104), OSD Control Box (E483757), Replacement Cable Kit (E000263), Stand (E275623), Side-mount brackets (E329508), Wall Mount Kit (E275050), Webcam (E275233)
Warranty	3 years standard. On-site exchange (U.S. only) and extended warranty available
MTBF	50,000 hours demonstrated
What's in the box	HDMI cable, USB cable, North America power cable, EU/KR power cable, UK power cable, 3.5mm audio cable, energy label according to EU Regulation 1062/2010, Quick Installation Guide (QIG)

## Ordering Information

Model	Part Number	Number	Technology	Color
4202L	E222369	ET4202L-9UWA-0-MT-GY-G	Infrared	Black
	E222372	ET4202L-2UWA-0-MT-ZB-GY-G	Projected Capacitive	Black
	E440897	ET4202L-0UWA-0-GY-G	No Touch	Black

## Optional Computer Modules

Model	Part Number	Processor	RAM	Storage	OS
ELO-KIT-ECMG2C-i3-NO	E333775	Intel Core 4th Gen i3 3.4 GHz HD4400	2GB	320GB	No OS
ELO-KIT-ECMG2C-i3-W7	E333965	Intel Core 4th Gen i3 3.4 GHz HD4400	2GB	320GB	Windows 7
ELO-KIT-ECMG2C-i3-W8	E334168	Intel Core 4th Gen i3 3.4 GHz HD4400	2GB	320GB	Windows 8.1
ELO-KIT-ECMG2C-i5-NO	E334358	Intel Core 4th Gen i5 3.7 GHz HD4600	4GB	320GB	No OS
ELO-KIT-ECMG2C-i5-W7	E334542	Intel Core 4th Gen i5 3.7 GHz HD4600	4GB	320GB	Windows 7
ELO-KIT-ECMG2C-i5-W8	E334744	Intel Core 4th Gen i5 3.7 GHz HD4600	4GB	320GB	Windows 8.1
ELO-KIT-ECMG2C-i7-NO	E334949	Intel Core 4th Gen i7 4.0 GHz HD4600	8GB	320GB	No OS
ELO-KIT-ECMG2C-i7-W7	E335147	Intel Core 4th Gen i7 4.0 GHz HD4600	8GB	320GB	Windows 7
ELO-KIT-ECMG2C-i7-W8	E335345	Intel Core 4th Gen i7 4.0 GHz HD4600	8GB	320GB	Windows 8.1
ELO-KIT-ECMG2C-AND	E336899	Qualcomm Snapdragon APQ8064 CPU	2GB	16 GB eMMC	Android

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Elo Touch Solutions  
1033 McCarthy Boulevard  
Milpitas, CA 95035

### 800-ELO-TOUCH

Tel +1 408 597 8000  
Fax +1 408 597 8001  
customerservice@elotouch.com

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
elosales@elotouch.com

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
www.elotouch.com.cn

### Latin America

Tel 786-923-0251  
Fax 305-931-0124  
www.elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2016 Elo Touch Solutions, Inc. All rights reserved. 16041AES00040



# Legacy Technology Services

**We Rent & Sell All Types Of Barcode Equipment**

Call now to talk to an expert

**866-271-9891**

[www.LegacyGlobal.com](http://www.LegacyGlobal.com)

Some brands we carry



MOTOROLA

**Intermec**

**DATALOGIC**™

**Honeywell**

**EQUINOX**  
PAYMENTS



## About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

## Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

## Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

## Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

## Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
  - Data destruction
  - Hardware disposal
  - Auditing services

## Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

## Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



[Legacy, Inc.](http://Legacy, Inc.)

160 West Road,  
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684