

- Best-in-class optical performance
- Designed for medical and healthcare requirements
- 35% energy savings using LED technology
- 3 year standard warranty



# 2401LM 24-inch Desktop Touch Monitor for Medical and Healthcare Settings

#### Overview

The fully featured 2401LM touch monitor offers IntelliTouch® surface acoustic wave (SAW) touchscreen technology which provides stable "drift-free" touch response, outstanding image clarity and full HD resolution, resulting in an accurate touch experience and vivid images. Additionally, the touch monitor is equipped with industry standard connectivity in the form of a combination USB and RS232 touch controller, DVI-D, VGA connectors and built-in audio amp with stereo speakers. The 2401LM is available in medical white or black color.

The 2401LM is compliant with multiple safety and electrical certification standards, including EN 60950-1 and EN 60601-1 for safety and EN 60950-1, EN55022, EN55024, and EN 60601-1 (3rd Edition) for EMC. Equipped with an LED

backlit state-of-the-art LCD panel, the monitor is environmentally friendly with reduced power consumption.

The Elo 2401LM touch monitor is an effective solution for nurse stations, computer-aided therapy, electronic medical record keeping, paperless charting, patient self-check-in, as well as non-medical applications that benefit from DVI-D input, speakers and a pristine full HD image display.

Having been "designed for touch", the 2401LM features a stable stand with tilting functionality which can be removed for VESA mounting; cable management and cable fastening features to prevent accidental disconnection; OSD controls with lockout capability; and an IPx1 drip-resistant housing



#### Reliable

- Pure-glass touchscreen for superior image quality and driftfree performance
- Compliant with multiple safety and electrical certifications recognized by public health authorities
- Elo controlled design with long product life cycle and availability cycle

# **Applications:**

- Nurse stations
- Patient self-check in
- Paperless charting
- · Electronic record keeping

### **About Elo**

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touch monitors, and all-in-one touch computers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.



### 2401LM 24-inch Desktop Touchmonitor

Specifications			
Model	2401LM		
Color	Black and white		
Active Display Area	531.4 x 298.9 mm / 20.9 x 11.7 inches		
Monitor Dimensions (without stand)	606 x 373 x 61 mm / 23.9 x 14.6 x 2.4 inches		
LCD Technology	Active matrix TFT LCD		
Diagonal Size	24.0"		
Aspect Ratio	16:9		
Native Resolution	1920 x 1080 at 60 Hz		
Preset Video Modes	1920 x 1080 60Hz ( Native ), 640 x 350 70Hz, 720 x 400 70Hz, 640 x 480 60, 72 & 75Hz, 800 x 600 56, 60, 72 & 75Hz, 832 x 624 75Hz1024 x 768 60, 70 & 75Hz, 1280 x 800 60Hz, 1280 x 960 60Hz, 1280 x 1024 60Hz & 75Hz, 1360 x 768 60Hz, 1366 x 768 60Hz, 1440 x 900 60Hz, 1600 x 1200 60Hz, 1680 x 1050 60Hz		
Number of Colors	16,7 million		
Brightness (typical)	LCD Panel: 300 nits; IntelliTouch: 270 nits		
Response Time (Tr+tf) (typical)	25ms		
Viewing Angle (typical)	Horizontal: 178°; Vertical: 178°		
Contrast Ratio (typical)	3000:1		
Video	Input connector: 3.5mm TRS jack Input signal range: 0.5Vrms maximum stereo signal Internal Speakers output: Two 1W speakers		
Audio	Input connector: 3.5mm TRS jack Input signal range: 0.5Vrms maximum stereo signal Internal Speakers output: Two 1W speakers		
	Input voltage AC Adaptor: 100-240 VAC, 50/60Hz Input voltage Monitor DC: 12 VDC +/- 0.5V		
Power	Input connector AC Adaptor: IEC 60320 C14 Input connector Monitor DC: 4 pin Mini DIN		
	Power Consumption (Typical): ON: 32W		
Weight	Unpackaged: 8,8 kg (19,4 lb); Packaged: 13,2 kg (29 lb)		
Shipping Dimensions	711 x 508 x 267 mm / 28 x 20 x 10.5 inches		
Mounting Options	100 mm VESA rear-mount		
	Controls (bottom): menu, up, down, select, power		
On-Screen Display (OSD) Controls	<b>Settings:</b> contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, volume, sharpness, OSD H/V POS, OSDTime		
	Languages: English, German, Spanish, Japanese, French, Italian, Chinese, Polish, Swedish		
	Lockouts: power, user controls		
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)		
Humidity (non-condensing)	Operating: 20% to 80%; Storage: 10% to 90%		
Regulatory Approvals and Declarations	UL/cUL, CE EN/IEC 60601-1 3rd ed., FCC Class B, VCCI, C-Tick, KC, GOST, BSMI, CCC, China RoHS, IPX1 Elo Declarations: RoHS, WEEE, CE		
Touch Interface	Serial (RS232) and USB		
Warranty	3 years standard		
MTBF	50.000 hours demonstrated		

### **Ordering Information**

Model	Part Number	Technology	Surface Treatment	Color	Availability
2401LM	E263686	IntelliTouch	Anti-glare	White	Worldwide
	E000140	IntelliTouch	Anti-glare	Black	Worldwide

### **Optional Peripherals**

Model	Part
Repl. medical grade power adapter	E000648
IntelliTouch Stylus Pen	D82064-000

Medical and Healthcare Application Disclaimer: It is the sole responsibility of any person intending to commercialize, market or use any of Elo Touch Solutions, Inc., or its family of companies ("Elo") products for medical or healthcare applications to ensure that such product is adequate and appropriate for the person's intended use and complies with all applicable laws, regulations, codes and standards including but not limited to the European Union Medical Device Directive, United States Federal Food, Drug, and Cosmetic Act, regulations of the United States Food and Drug Administration (FDA), and other similar legislation in jurisdictions around the world, and for obtaining and maintaining any required regulatory approvals including but not limited to any required market clearances. Elo has not sought nor received any rulings from the FDA or any other federal, state, or local government agency or notified body as to the safety, effectiveness or appropriateness of its product for such applications. Persons intending to evaluate or use Elo's product for medical or healthcare purposes must rely on their own medical and legal judgment

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America Elo Touch Solutions 1033 McCarthy Boulevard Milpitas, CA 95035

800-ELO-TOUCH Tel +1 408 597 8000 Fax +1 408 597 8050 customerservice@elotouch.com elosales@elotouch.com

Europe Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49

Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 www.elotouch.com.cn

Asia-Pacific

Latin America Tel 786-923-0251 Fax 305-931-0124

www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2013 Elo Touch Solutions, Inc. All rights reserved. DS000082, rev A 10/13



# **Legacy Technology Services**

# We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert

866-271-9891

## About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

### Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

### Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

### Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
   Legacy routinely purchases equipment from our clients around the globe.
  - · Data destruction
  - · Hardware disposal
  - Auditing services

#### Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















