



1517L 15" LCD Desktop Touchmonitor

Rugged, flexible, space-saving

The Elo Touch Solutions 1517L is well-suited to meet the durability and aesthetic requirements for a variety of high traffic retail and hospitality interactive solutions including:

- Point-of-sale (POS)
- Point-of-service
- Loyalty systems
- Countertop kiosk point-of-information
- Back office solutions integrating labor management and inventory analysis
- Shelf-level/countertop interactive digital signage displays

Available with a choice of two zero-bezel touchscreen technologies, iTouch surface acoustic wave or AccuTouch resistive, the 1517L provides stable, "drift-free" operation with excellent image clarity, resolution, and light transmission—for an accurate touch response and vivid images!

Features and Benefits

- Choice of two leading Elo zero-bezel touchscreen technologies for a seamless, easy to-clean glass-to-edge design:
 - iTouch surface acoustic wave
 - Zero-bezel AccuTouch resistive
- 4:3 aspect ratio panel
- USB touch controller, VGA port
- LED backlighting allows for state-of-the-art slim design with lower power consumption than CCFL
- Removable base and mounting features including VESA, wall- and arm-mounting options for installation flexibility and mounting holes on base for table-top security
- Optional peripherals include field-installable 3-stripe Magnetic Stripe Reader (MSR), Rear Facing Customer Display (RFCD) and various display stands
- Digital on-screen display (OSD) and controls on the side with lock-out function for public use



1517L 15" LCD Desktop Touchmonitor

Specifications

| | |
|--|--|
| Model | 1517L |
| Color | Black or white |
| Active Display Area | 11.97" x 8.98" (304.13mm x 228.096mm) |
| Dimensions* (without stand and packaging) | 14.09" x 6.81" x 12.52" (358.1mm x 173mm x 318mm) max |
| LCD Technology | Active matrix TFT LCD |
| Diagonal Size | 15" |
| On-Screen Display (OSD) | Accessible through switches along the bottom. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults, Video Source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power |
| Mounting Options* | VESA 4-hole 75mm mounting interface on rear of unit; 3-hole threaded mounting on bottom of stand |
| Aspect Ratio | 4:3 |
| Native Resolution | 1024 x 768 |
| Preset Video Timings | 640 x 480 60Hz, 75Hz; 720 x 400 70Hz; 800 x 600 56, 60Hz, 75Hz; 1024 x 768 60Hz, 75Hz |
| Number of Colors | 16.2 million |
| Brightness (typical) | LCD Panel: 250 nits; with iTouch: 225 nits; with AccuTouch: 200 nits |
| Response Time (Tr + Tf) (typical) | 25ms |
| Viewing Angle (typical) | Horizontal: 160°; Vertical: 140° |
| Contrast Ratio (typical) | 700:1 |
| Video | Analog VGA on Female DE-15 connector; Input Video Horizontal Sync frequency range: 31.5-80KHz Input Video Vertical Sync (frame rate) frequency range: 56-75Hz |
| Power | Monitor input power connector: Coaxial power jack (2.1mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC \pm 5%. Note: This monitor is sold with an AC-DC power adapter. Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz; Power Consumption (Typical): ON (monitor + AC/DC adapter): 10W; SLEEP (monitor + AC/DC adapter): 1.1W; OFF (monitor + AC/DC adapter): 1.0W |
| Weight (with stand) | Unpackaged: 9.0 lbs (4.1kg); Packaged: 14.9 lbs (6.8kg) |
| Shipping Dimensions | 17.16" x 14.56" x 7.67" (436mm x 370mm x 195mm) |
| Temperature | Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 140°F (-20°C to 60°C) |
| Humidity (non-condensing) | Operating: 20%-80%; Storage: 10%-90% |
| Regulatory approvals and declarations | C-Tick; cUL, IC; CCC; CE; VCCI; KCC, e-Standby; Coc; BSMI Mark; UL, FCC; CB; RoHS, China RoHS, WEEE, IMERC |
| Warranty | 3 years |
| MTBF | 50,000 hours demonstrated |

*See dimensional drawings for details

For updated specifications and more information, please visit www.elotouch.com.

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
301 Constitution Drive
Menlo Park, CA 94025-1110

800-ELO-TOUCH

Tel 1-650-361-4800
Fax 1-650-361-4722
customerservice@elotouch.com

Europe

Tel +32 (0)16 35 21 00
Fax +32 (0)16 35 21 01
elosales@elotouch.com

Asia-Pacific

Tel +81 (45) 478-2161
Fax +81 (45) 478-2180
www.tps.co.jp

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com.ar

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. AccuTouch, Elo (logo), Elo Touch Solutions and iTouch are trademarks of Elo Touch Solutions, Inc.
Copyright 2012 Elo Touch Solutions, Inc. All rights reserved. DS000066, rev 11/2012

www.elotouch.com



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684