

Epson

TM-T88 ReStick Label Printer



- Cost-effective liner-free label printing for food service, retail and grocery
- Automatic paper advance reduces effects of heat and humidity
- Compatible with most TM-T88 printer applications
- High-speed label printing up to 5.91"/sec at 203 dpi
- Produces 60% more labels per roll than die-cut labels
- Uses MAXStick™ silicone-free, liner-free adhesive labels
- Supports a wide range of standard/wireless interfaces
- Modified paper well, printhead and support rollers reduce paper jams
- Compact, durable design with the highest reliability in its class

Epson's TM-T88 ReStick™ liner-free label printer provides trouble-free printing of repositionable labels with the most reliability available today.

TM-T88 ReStick offers high-speed, liner-free label printing for a wide range of food service, retail and grocery applications at a much lower cost than standard label printers using coated paper liners.

The liner-free, hassle-free label printer that really works

Fast and reliable, the TM-T88 ReStick label printer prints repositionable labels at a crisp 203 x 203 dpi. It supports variable length label output, a variety of paper widths, autocutter and more. Based on new technology, the TM-T88 ReStick printer delivers label printing without the problems associated with traditional linerless label printers. It features a modified paper well to ensure paper movement through the paper path, a modified printhead, additional paper guides and dual support rollers to avoid paper jams.

Ideal for QSR, food service and retail applications

Designed expressly for high-volume food service and retail environments, TM-T88 ReStick prints crisp text and graphics at a fast 5.91"/sec speed. From food bag, coffee and deli labels to price labels, shelf tags and return labels, it is a cost-effective solution for a wide range of labeling applications.

Liner-free, silicone-free labels

Epson's TM-T88 ReStick printer uses cost-effective silicone-free, liner-free MAXStick™ labels that produce 60% more labels per roll than die-cut labels. Adhesive is applied only to the center strip of the label to minimize the negative effects of adhesive material in the printer and enable repositioning of the label multiple times without tearing.

Integration made easy

ReStick supports multiple interfaces including parallel, high-speed USB, Ethernet and 802.11g, and is compatible with best-of-breed and component-based systems. In addition, it is compatible with most TM-T88 series thermal printers and can be used for receipt printing when needed using standard POS paper rolls.

Quality you can rely on

To ensure optimum performance, TM-T88 ReStick has been extensively tested in demanding food service and retail environments and is backed by Epson's two-year limited warranty.

Epson TM-T88 ReStick Label Printer

Printer Specifications

General	Print method	Thermal line printing	
	Print resolution	203 dpi x 203 dpi	
	Print fonts		
	Font size (Font A/B/C)	3.125" (80mm) : Normal mode (203 dpi) 12 x 24/9 x 17/10 x 24; Emulation mode (180 dpi) 13 x 24/10 x 17/10 x 24. 2.25" (58mm) : Normal mode (203 dpi) 12 x 24/9 x 17/10 x 24; Emulation mode (180 dpi) 10 x 24/9 x 17/12 x 24	
	Column capacity (Font A/B/C)	3.125" (80mm) : Normal mode (203 dpi) 48/64/57 columns; Emulation mode (180 dpi) 44/57/57 columns. 2.25" (58mm) : Normal mode (203 dpi) 35/46/42 columns; Emulation mode (180 dpi) 42/46/35 columns	
	Character sizes (Font A/B/C) (W x Hmm)	3.125" (80mm) : Normal mode (203 dpi) 1.25 x 3.0/0.88 x 2.13/1.125 x 3.0; Emulation mode (180 dpi) 1.25 x 3.0/0.88 x 2.13/1.125 x 3.0. 2.25" (58mm) : Normal mode (203 dpi) 1.25 x 3.0/0.88 x 2.13/1.125 x 3.0; Emulation mode (180 dpi) 1.125 x 3.0/0.88 x 2.13/1.25 x 3.0	
	Character sets	95 Alphanumeric, 48 International, 128 x 11 Graphic (including user-defined page) Traditional/Simple Chinese, Thai, Japanese, Korean	
	Barcodes	UPC-A/E, CODE 39/93/128, EAN8/13, ITF, CODABAR, 2D symbols: PDF417, QR-CODE	
Printer	Interface*	RS-232C, IEEE 1284 parallel; RS-485; high-speed USB; 10/100Base-T/TX; wireless	
	Data buffer	Receive: 45 bytes or 4KB, selectable; user-defined: 12KB; macro: 2KB; NV graphics: 256KB; NV user: 1KB	
		Receipt Paper	TM-T88 ReStick Label Paper
	Print speed (max.)	6.97"/second (177mm) graphics and text	5.91"/second (150mm) graphics and text
	Paper dimensions	3.125" (80mm): 3.13" ± 0.02"(W) x 3.27" dia. (79.5 ± 0.5(W) x 83mm) 2.25" (58mm): 2.26" ± 0.02"(W) x 3.27" dia. (57.5 ± 0.5(W) x 83mm)	3.125" (80mm): 3.12" ± 0.016"(W) x 3" +0.15/-0.06" dia. (79.4 ± 0.4(W) x 76.2 +3.8/-1.6 mm) 2.25" (58mm): 2.25" +0.016/-0.008" x 3" +0.15/-0.06" dia. (57.2 + 0.4/-0.2(W) x 76.2 +3.8/-1.6 mm)
	Paper thickness	55 – 80 µm	82.5 ± 3.8 µm
	Reliability		
	MTBF	360,000 hours	360,000 hours
	MCBF	52,000,000 lines	48,000,000 lines
	Autocutter	1.5 million cuts	600,000 cuts
	Power	24 VDC ± 7%	
	Power consumption	Approx. 1.8 A (mean)	
	D.K.D. function	2 drivers	
	Overall dimensions	5.71 x 7.68 x 5.83" (W x D x H) (145 x 195 x 148mm)	
	Mass	3.96 lb (1.8 kg)	
	Color	Epson Dark Gray, Epson Cool White	
	Factory options	Power supply cover, PS-180 AC adapter, wall-hanging bracket, paper roll spacer, affixing tape and Connect-It interfaces*	
Control Board	EMI standards	FCC/ICES-003 Class A	
	Safety standards	UL1950/CSA C22.2 No. 950	
	Font emulation	TM-T88 Series (180 dpi) font emulation available	


Inch values are approximate.

dpi: dots per 25.4mm (dots per inch)

cpi: characters per 25.4mm (characters per inch)

lps: lines per second

*To find out more about our line of Connect-It™ interfaces, talk to your Epson Sales Representative.



Optional power supply case
secures cords under printer.



JAVAPOS™



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684