CARD PRINTING AND ENCODING







TECHNOLOGY HIGHLIGHTS

- Simple one-color, single-side, edge-toedge printing
- Eco-friendly refillable ribbon cartridge reduces cost and waste
- Print to standard CR-80 and CR-79 cards, from 9 mil to 40 mil thick
- Optional resin-erase and rewrite capability for visitor badges and temporary workers
- Optional magnetic stripe encoding

APPLICATIONS

- Bank and financial services payment cards
- Casino employee and member ID
- Employee and temporary badges for small- to medium-sized businesses
- Retail loyalty program member ID and payment cards

DIRECT-TO-CARD MONOCHROME PRINTER

- Affordable economical and reliable ID issuance
- Convenient operation plug-and-play; minimal maintenance required
- Efficient simple all-in-one card personalization with optional magnetic stripe encoding

The FARGO® DTC1000M Monochrome printer delivers the ultimate simplicity in card personalization. The affordable printer is easy to use, virtually maintenancefree and economical to operate.

The DTC1000M is the cost-effective, low- to moderate-volume card issuance solution for organizations such as casinos, financial services firms, small businesses and retailers. An eco-friendly erase-and-rewrite option also makes the printer ideal for visitor badges and temporary worker ID applications.

The DTC1000M prints a single color, edge-to-edge image on one side of a standard CR-80 or CR-79 identification card. The resin thermal transfer process assures clear reproduction of photo images, bar codes and alphanumeric data.

Connect quickly via USB or optional Ethernet port and begin creating ID badges within seconds. With the builtin Swift ID[™] application, you can start printing without having to install any additional software. Receive instant system status cues through color-coded buttons during your printing operation. Ribbon options include standard or premium black, or your choice of green, blue, red, white, silver or gold.

Print ribbon and card-cleaning roller installation is a snap with the cartridgebased design. A standard refillable cartridge for black resin ribbons decreases waste and reduces cost in the most common resin printing applications.

For magnetic stripe cards, an optional module enables inline, onestep encoding and card printing.

The FARGO DTC1000M Monochrome printer is built to the quality and reliability standards of every Genuine HID[™] product. It is fully interoperable with other HID Global products and solutions, as well as most third party systems, enabling organizations to leverage their existing technology investments.

hidglobal.com



SPECIFICATIONS

Model Name	DTC1000 Monochrome
Print Method	Resin thermal transfer
Resolution	300 dpi (11.8 dots/mm)
Colors	Monochrome: black, green, blue, red, white, silver or gold
	Provided as Refill Ribbon for Cartridge in Printer: • Resin black (standard and premium): 1,000 prints
Print Ribbon Options	Provided in Disposable Ribbon Cartridge: • Resin black and overlay panel, KO*: 500 prints • Resin green, blue, red, white, silver or gold: 1000 prints • Rewrite technology - No ribbon is required • Standard resin black refillable ribbon cartridge (included)
Print Speed**	7 seconds per card (K*); 12 seconds per card (KO*)
Accepted Standard Card Sizes	CR-80, 3.375 in. L x 2.125 in W (85.6 mm L x 54 mm W); CR-79 adhesive back, 3.313 in L x 2.063 in W (84.1 mm L x 52.4 mm W)
Print Area	CR-80 edge-to-edge, 3.36 in L x 2.11 in W (85.3 mm L x 53.7 mm W); CR-79, 3.3 in L x 2.04 in W (83.8 mm L x 51.8 mm W)
Accepted Card Thickness	0.009 in to 0.040 in (0.229 mm to 1.016 mm)
Accepted Card Types	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish
Input Hopper Card Capacity	100 cards at 0.030 in (0.762 mm)
Input Hopper Card Capacity Output Hopper Card Capacity	100 cards at 0.030 in (0.762 mm) Up to 30 cards at 0.030 in (0.762 mm)
	Up to 30 cards at 0.030 in (0.762 mm)
Output Hopper Card Capacity	Up to 30 cards at 0.030 in (0.762 mm)
Output Hopper Card Capacity Card Cleaning	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM
Output Hopper Card Capacity Card Cleaning Memory	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows® XP and Vista® (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.4
Output Hopper Card Capacity Card Cleaning Memory Software Drivers	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows® XP and Vista® (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10. Linux***
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows® XP and Vista® (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10. Linux*** USB 2.0, optional Ethernet with internal print server
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows® XP and Vista® (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10. Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows® XP and Vista® (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.4 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows® XP and Vista® (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.4 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg)
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.0 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.0 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024 CCC, BSMI, KCC
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.0 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024 CCC, BSMI, KCC ENERGY STAR qualified printer and refillable supply cartridges
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.0 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024 CCC, BSMI, KCC ENERGY STAR qualified printer and refillable supply cartridges 100-240 VAC, 3.3 A
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage Supply Frequency	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.4 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024 CCC, BSMI, KCC ENERGY STAR qualified printer and refillable supply cartridges 100-240 VAC, 3.3 A 50 Hz / 60 Hz
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage Supply Frequency Warranty	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon char 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.0 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024 CCC, BSMI, KCC ENERGY STAR qualified printer and refillable supply cartridges 100-240 VAC, 3.3 A 50 Hz / 60 Hz Printer - 2 years; Printhead - 2 years, unlimited pass with UltraCard*
Output Hopper Card Capacity Card Cleaning Memory Software Drivers Interface Operating Temperature Humidity Dimensions Weight Agency Listings ENERGY STAR* / Green Supply Voltage Supply Frequency Warranty Encoding Options	Up to 30 cards at 0.030 in (0.762 mm) Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon chan 32 MB RAM Windows* XP and Vista* (32 bit & 64 bit); Server 2003 & 2008; Windows 7 (32 bit & 64 bit). MAC: OS X 10.5 & 10.6 Linux*** USB 2.0, optional Ethernet with internal print server 65° to 80° F / 18° to 27° C 20% to 80% non-condensing 8.8 in H x 13.7 in W x 7.9 in D (224 mm H x 348 mm W x 201 mm D) 7.5 lbs (3.4 Kg) Safety: UL 60950-1, CSA C22.2 (60950-1), and CE; EMC: FCC Class A, CRC c1374, CE (EN 55022 Class A, EN 55024 CCC, BSMI, KCC ENERGY STAR qualified printer and refillable supply cartridges 100-240 VAC, 3.3 A 50 Hz / 60 Hz Printer - 2 years; Printhead - 2 years, unlimited pass with UltraCard* ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3

* Indicates the ribbon type and the number of ribbon panels printed where K=Resin Black and O=Overlay.
** Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to

process. ***Linux versions: Ubuntu 8.04/9.04, Red Hat 5, Fedora 7/8/9/10/11, Open Suse 10.3, Debian 5.03/5.04, Mandiva one 2009

North America: +1 949 732 2000 Toll Free: 1 800 237 7769 Europe, Middle East, Africa: +49 6123 791 0 Asia Pacific: +852 3160 9800 Latin America: +52 55 5081 1650



© 2012 HID Global Corporation. All rights reserved. FARGO, HID and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. 20120215-hid-fargo-dtc1000m-ds-en

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













