ThinLine[®] II Reader

Low Profile Proximity Card Reader • 5395 (Wiegand) 5398 (Clock-and-Data)



ACCESS reliability.

Application

Providing performance and reliability, HID's attractive, unobtrusive ThinLine[®] II proximity card reader is housed in a two-piece, weatherproof secure potted enclosure.


Features

- Easily installed and maintained with the use of replaceable covers.
- Available with a Wiegand or Clock-and-Data interface.
- Provides high reliability, consistent read range and low power consumption.
- Features include multicolor LED and internal control or host control of the LED and beeper.
- Mounts directly on metal with minimal impact on the read range performance.
- Aesthetic design available in two cover designs and four colors to match any décor.
- Includes multilingual installation manual.

2CIT	IC at	ions
	Cau	

Mounting	Mounts on a single-gang electrical box for easy installation. Mounts directly on metal with minimal impact on read range performance.	
Audiovisual Indication	A red LED flashes green and the beeper sounds when reader is presented with a proximity card. The multicolor LED and beeper can also be controlled individually by the host system.	
Diagnostics	On reader power-up, an internal self-test routine checks and ver ifies the setup configuration, determines the internal or external control of the LED and beeper and initializes reader operation. An additional external loop-back test allows for the reader outputs and inputs to be verified without the use of additional test equipment.	
Indoor/outdoor Design	Sealed in a rugged, weatherized polycarbonate enclosure designed to withstand harsh environments, providing reliable performance and a high degree of vandal resistance.	
Easily Interfaced	Wiegand output model interfaces with all existing Wiegand protocol access control systems. Clock-and-Data (magnetic stripe) model interfaces with most systems that accept magnetic stripe readers.	
Security	Recognizes card formats up to 85 bits, with over 137 billion unique codes.	
Warranty	Lifetime warranty against defects in materials and workmanship (see complete sales policy for details).	
Part Numbers	Base Part No.: 5395 Wiegand interface Base Part No.: 5398 Clock-and-Data interface Description: Tri-State LED, internal beeper on	
Options	 CLASSIC series cover in white, beige, charcoal gray or black (or) Designer series cover in white, wave blue, charcoal gray or black LED and beeper operation 	

(Please see "How to Order Guide" for a description of the options and associated part numbers.)



Typical Maximum* Read Range

ProxCard® II card - up to 5.5" (14 cm) ISOProx® II card - up to 5" (12.7 cm) DuoProx® II card - up to 5" (12.7 cm) DuoProx[®] II card - up to 5 (12.7 cm) Smart ISO[®]/DuoProx[®] cards - up to 5" (12.7 cm) ProxCard[®] Plus card - up to 1.5" (3.8 cm) ProxKey[®] II keyfob - up to 2" (5.1 cm) MicroProx[®] Tag - up to 3" (7.6 cm) *Depending on local installation conditions.

Dimensions:

4.70" × 3.00" × 0.68" (11.9 × 7.6 × 1.7 cm)

Material: Polycarbonate UL 94

Power supply:

-16 VDC Linear power supplies are recommended.

Current requirements:

Average: 30 mA (5 VDC); 20 mA (12 VDC) Peak: 110 mA (5 VDC); 115 mA (12 VDC)

Operating temperature: -22° to 150° F (-30° to 65° C)

Operating humidity:

0-95% relative humidity non-condensing

Weight: 3.3 oz. (94 gm)

Transmit frequency: 125 kHz

Excite frequency: 125 kHz

Cable distance:


Wiegand interface: 500 feet (150 m) Clock-and-data interface: 50 feet (15 m) Recommended cable is ALPHA 1295 (22 AWG) 5 conductor minimum stranded with overall shield or equivalent. Additional conductors may be required for LED or beeper control.

Environmental: IP55

Certifications:

UL294/cUL (US), FCC Certification (US), IC (Canada), CE (EU), C-tick (Australia, New Zealand), SRRC (China), MIC (Korea), NCC (Taiwan), MIC (Japan), iDA (Singapore), RoHS

© 2009 HID Global. All rights reserved. HID, and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 05/2009



MKT-PTHINLINEii_DS_EN

hidglobal.com

ACCESS experience.

th Ame **North America** 15370 Barranca Pl rvine, CA 92618

a Pacific 852 3160-9800 +852 <u>3160-</u>4809

Latin America Circunvalacion Ote. #201 B Despacho 2 Col. Jardines del Moral Leon 37160, Gto. Mexico Tel: +52 477 779 1492 Fax: +52 477 779 1493

Europe, Middle East & Africa Haverhill Business Park Phoenix Road Haverhill, Suffolk CB9 7AE England Tel: +44 (0) 1440 714 850 Fax: +44 (0) 1440 714 840



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













