

Granit 1981i

Wireless Industrial-Grade Full-Range Area-Imaging Scanner

The Granit™ 1981i wireless industrial-grade scanner features full-range area-imaging technology capable of reading both 1D and 2D barcodes across a wide range of distances. From poor quality 2 mil codes scanned at close range to 100 mil codes hanging from warehouse rafters scanned at ranges of 52 feet (16m), the 1981i is built to perform. With an unmatched range and wireless freedom providing incredible versatility, Granit enables maximum operator productivity in the harshest environments.

The 1981i is packed with technologies that make it simple to use. An integrated laser pointer aiming system with auto-illumination, omni-directional reading capability, and support for centering take the guesswork out of scanning at extended ranges. Operators of fork trucks equipped with vehicle-mounted mobile computers, such as the Honeywell Thor™ series, will appreciate how the full-range scanning capability of 1981i allows them to remain seated—and hence more productive—while scanning pallets at extended ranges. And with Bluetooth™ technology, complete freedom of movement up to 330 feet (100 meters) provides additional operator convenience.

As a member of the Granit family of scanners, the 1981i is built to withstand the varied demands of harsh working environments. Incorporating the Granit housing that has long set the standard for scanner reliability, the 1981i is rated IP65 and is built to survive 5,000 tumbles from 3.2 feet (1m) and 50 drops to concrete from 6.5 feet (2m)—even in temperatures as low as -4°F (-20°C). As a result, operations that deploy Granit scanners can expect to experience minimal device downtime and a lower overall cost of ownership.



Features

- Full-Range Area-Imaging Performance: Scans low density (100 mil) codes out to 52 ft (16 m) and high density (2 mil) codes at close range—and everything in between.
- Built Granit Tough: Tested to withstand the toughest environments, Granit is rated IP65 and can withstand 5,000 tumbles from 3.2 ft (1 m) and 50 drops to concrete from 6.5 ft (2 m).
- Easy to Use: A laser-spot aimer, omni-directional scanning, and features such as centering take the guesswork out of scanning at extended ranges.
- Efficient Wireless Performance: Bluetooth[™] wireless technology provides freedom of movement up to 330 ft (100 m) from base and reduces interference with other wireless systems.
- Single Scanning Solution: Can replace and consolidate multiple purpose-built scanners in typical distribution center and warehouse environments.

Granit 1981i Technical Specifications

Wireless		
Wireless		
Radio/Range	2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1: Class 1: 100m (330') line of sight	
Data Rate (Transmission Rate)	Up to 1 Mbps	
Number of Scans	At least 7200 (1 scan every 4 seconds for 8 hours)	
Expected Hours of Operation	8 hours	
Expected Charge Time	4.5 hours (With external power supply on charger)	
Battery	2000 mAh Li-ion minimum	
Mechanical / Electrical	Scanner (1981iFR-3)	Charger/Communication Base (CCB05-100BT-07N)
Dimensions (LxWxH)	133 mm x 75 mm x 195 mm (5.2" x 2.9" x 7.6")	250 mm x 103 mm x 65mm (9.9" x 4.1" x 2.6")
Weight	420 g (14.8 oz)	290 g (10.2 oz)
Operating Power (Charging)	N/A	5 W (1A @ 5V)
Non-Charging Power	N/A	0.6 W (0.12A @ 5 V)
Host System Interfaces	N/A	USB, Keyboard Wedge, RS232 TTL
Environmental	Scanner (1981iFR-3)	Charger/Communication Base (CCB05-100BT-07N)
Operating Temperature	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Operating Temperature	20 0 10 00 0 (+ 1 10 122 1)	-20 0 10 30 0 (-4 1 10 122 1)
Storage Temperature with battery	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)
	,	,
Storage Temperature with battery	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)
Storage Temperature with battery Humidity	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5')	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4')
Storage Temperature with battery Humidity Drop	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C
Storage Temperature with battery Humidity Drop Tumble	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles
Storage Temperature with battery Humidity Drop Tumble Environmental Sealing	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles IP65	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles IP51
Storage Temperature with battery Humidity Drop Tumble Environmental Sealing Light Levels	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles IP65 0 to 100,000 lux (9,290 foot-candles)	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles IP51 N/A
Storage Temperature with battery Humidity Drop Tumble Environmental Sealing Light Levels ESD	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles IP65 0 to 100,000 lux (9,290 foot-candles)	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles IP51 N/A
Storage Temperature with battery Humidity Drop Tumble Environmental Sealing Light Levels ESD Scan Performance	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles IP65 0 to 100,000 lux (9,290 foot-candles) ±20Kv air discharge, ±8kV contact discharge	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles IP51 N/A
Storage Temperature with battery Humidity Drop Tumble Environmental Sealing Light Levels ESD Scan Performance Scan Pattern	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles IP65 0 to 100,000 lux (9,290 foot-candles) ±20Kv air discharge, ±8kV contact discharge Area Image Horizontal: 12.9°	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles IP51 N/A
Storage Temperature with battery Humidity Drop Tumble Environmental Sealing Light Levels ESD Scan Performance Scan Pattern Scan Angle	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 2 m (6.5') drops to concrete at -20°C 5,000 1m (40') tumbles IP65 0 to 100,000 lux (9,290 foot-candles) ±20Kv air discharge, ±8kV contact discharge Area Image Horizontal: 12.9° Vertical: 8° 1D Codes: 30% minimum reflectance difference	-40°C to 70°C (-40°F to 158°F) 0 to 95% relative humidity, non-condensing Designed to withstand 50 1.2 m (4') drops to concrete at -20°C 5,000 1m (40') tumbles IP51 N/A

Refer to the Honeywell Scanning & Mobility Compliance Center (www.honeywellaidc.com/compliance) to review and download any publicly available documentation pertaining to the certification of this product in a given country.

Refer to the Honeywell Scanning & Mobility Supported Symbologies Datasheet (www.honeywellaidc.com/symbologies) for a complete listing of all supported bar code symbologies.

Specifications are subject to change without notice.

LASER LIGHT- DO NOT STARE INTO BEAM CLASS 2 LASER PRODUCT. a射光,請勿直視鐳射光束,等級2鐳射產品. RAYONNEMENT LASER NE PAS REGARDER DANS LE FAISCEAU. APPAREIL À LASER DE CLASSE 2. MAX. 1mW: 630-680 nm IEC 60825-1:2007. Complies with 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser Notice No. 50, dated June 24, 2007.

For more information:

www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

Typical Performance*	Full Range (FR)	
Narrow Width	Depth of Field	
7.5 mil Code 39	10.0 cm - 166.8 cm (3.9" - 65.7")	
13 mil UPC	12.2 cm - 233.4 cm (4.8" - 91.9")	
20 mil Code 39	15.2 cm – 439.0 cm (6.0" – 172.8")	
55 mil Code 39	50.9 cm - 1342.3 cm (20.0" - 528.5")	
100 mil Code 39	92.5 cm - 1600.0 cm (36.4" - 629.9")	
7.5 mil DataMatrix	10.0 cm - 77.2 cm (3.9" - 30.4")	
55 mil DataMatrix	40.8 cm - 599.1 cm (16.1" - 235.9")	
100 mil DataMatrix	81.4 cm - 1056.1 cm (32.0" - 415.8")	
Resolution 1D Code 39	2 mil (.051mm)	
Resolution 2D DataMatrix	2 mil (.051mm)	
*Performance may be impacted by bar code quality and		

environmental condition



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















