## Honeywell

# Voyager 1202g-bf

#### **Battery-Free Wireless Laser Scanner**

Honeywell's Voyager<sup>™</sup> 1202g-bf single-line laser scanner incorporates breakthrough battery-free technology, offering the freedom of Bluetooth<sup>®</sup> wireless technology without the maintenance hassle or long recharge time associated with traditional batteries. Like all other Voyager scanners, the 1202g-bf delivers aggressive linear bar code scanning performance—even on poor quality or damaged bar codes.

An integrated Bluetooth Class 2 radio grants users complete freedom of movement up to 10 meters (33 feet) from the base in a typical work environment. For added convenience, a paging system on the base activates auditory signals that help to locate a misplaced scanner. By eliminating the trip-hazard of tethered cables, the 1202g-bf can make for a safer and more productive work environment.

Battery-free wireless technology completely eliminates the battery, replacing it with a super-capacitor capable of achieving full-charge in less than 35 seconds, and providing enough wireless power to last at least 100 scans.<sup>1</sup> This makes the 1202g-bf ideal for applications where occasional wireless scanning is needed; for example, as a complement to bioptic (in-counter) scanners in retail environments where bulky items are sometimes left in shopping carts and must be scanned by hand. With no battery, a common maintenance hassle is removed and the scanner is lighter and more ecologically friendly.

Voyager is a plug-and-play scanner, and features a multi-interface design with automatic interface detection. By automatically configuring itself to the appropriate interface upon connection, the installation process is shortened, and the cumbersome task of scanning programming bar codes is eliminated.

Built on the proven Voyager platform, the 1202g-bf offers high performance linear bar code scanning and the convenience of wireless—all without the battery.



#### Features

- Battery-Free Wireless Technology: Fully charges in less than 35 seconds with a wall power adapter, and provides short-term power for at least 100 wireless scans.<sup>1</sup> By eliminating the battery, a common maintenance headache is removed, and the scanner is lighter and more environmentally friendly.
- Bluetooth<sup>®</sup> Wireless Technology: Grants wireless freedom of movement up to 10 meters (33 feet) from the base, depending on user environment.
- Reliable Bar Code Reading: Increase throughput and reduce the potential for hand-keyed errors by quickly scanning a variety of 1D bar codes, including those that are damaged or poor quality.
- Automatic Interface Configuration: Supports all popular interfaces in one device, replacing the time-consuming process of scanning programming bar codes with automatic interface detection and configuration.
- **Paging Functionality:** Simply press the button on the base to locate your lost scanner; Voyager responds with a series of beeps and blinking lights on its indicator panel.

<sup>1</sup> Honeywell's battery-free wireless technology powers the scanner for at least 100 scans, with one scan performed every second. For applications requiring more than 100 continuous wireless scans, a traditional battery-powered scanner such as the Voyager 1202g is recommended.

### Voyager 1202g-bf Technical Specifications

Radio/Range	2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1; Class 2: 10m (33') line of sight	
Data Rate (Transmission Rate)	Up to 3 Mbps	
Number of Scans	At least 100 scans, with one scan every second At least 35 scans, with one scan every 6 seconds	
Expected Full Charge Time	Less than 35 seconds via wall power adapter Less than 90 seconds via USB power	
Use Time per Full Charge	2-6 minutes (depending on use)	
Mechanical/Electrical	Scanner (Voyager 1202g-bf)	Charge & Communication Base
Dimensions	180 mm x 66 mm x 92 mm (7.1″ x 2.6″ x 3.6″)	200 mm x 67 mm x 97 mm (7.9″ x 2.6″ x 3.8″)
Weight	160 g (5.6 oz)	216 g (7.6 oz)
Operating Power	Scanning: 180mA @ 4.0V	Charging: 5W: (1A @ 5V peak) with AC wall supply 2.5W: (0.5A @ 5V peak) with USB
Non-Charging Power	Standby: 40mA at 4.0V	Base with Scanner: 1W (0.2A @ 5V) Base without Scanner : 0.5W (0.1A @ 5V) Suspend Mode: 0.0125W (0.0025A @ 5V)
Host System Interfaces	N/A	USB, RS232, RS485, KBW
Environmental	Scanner (Voyager 1202g-bf)	Charge/Communication Base (CCB00-010BT-01N-BF)
Operating Temperature	0°C to 50°C (32°F to 122°F)	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	-20°C to 60°C (-4°F to 140°F)
Humidity	5 to 95% relative humidity, non-condensing	5 to 95% relative humidity, non-condensing
Drop	Designed to withstand 30 1.5 m (5) drops to concrete	Designed to withstand 30 1.0 m (3.3) drops to concrete
Environmental Sealing	IP42	IP42
Light Levels	0 to 70,000 lux (6,500 foot-candles)	N/A
Scan Performance		
Scan Pattern	Single scan line	
Scan Speed (laser only)	100 scan lines per second	
Scan Angle	Horizontal: 30°	
Print Contrast	10% minimum reflectance difference	
Pitch, Skew	60°, 60°	
Then, okew		
Decode Capabilities	Reads standard 1D and GS1 DataBar symbologies.	

Refer to the Honeywell Scanning & Mobility Compliance Center (<u>www.honeywellaidc.com/compliance</u>) to review and download any publicly available documentation pertaining to the certification of this product in a given country.

Refer to the Honeywell Scanning & Mobility Supported Symbologies Datasheet (<u>www.honeywellaidc.com/symbologies</u>) for a complete listing of all supported bar code symbologies.

Specifications are subject to change without notice.

#### For more information:

www.honeywellaidc.com

#### **Honeywell Scanning & Mobility**

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

## Honeywell

CLASS 2 LASER PRODUCT 1.0 mW MAX OUTPUT: 650nM

Typical Performance\*

\*Performance may be impacted by bar code quality

Depth of Field

Narrow Width

5 mil

7.5 mil

10 mil 13 mil

20 mil

\*Resolution: 3.5 mil

and environmental conditions

C 60825-1 Ed 2 (2007). pulse duration f 15.5mSec. Complies with 21 CFR 1040. d 1040.11 except for deviations pursuan Laser Notice No. 50, dated June 24, 200

27 mm - 151 mm (1.1" - 5.9") 16 mm - 216 mm (0.6" - 8.5")

0 mm - 277 mm (0" - 10.9")

0 mm - 311 mm (0" - 12.2")

0 mm - 367 mm (0" - 14.4")

1

s pu-

1202g-bf-DS Rev C 05/15 © 2015 Honeywell International Inc.

# Legacy Technology Services

## We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert 866-271-9891

#### About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

#### Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

#### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

#### **Discontinued product sourcing**

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

#### Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
  - Data destruction
  - · Hardware disposal
  - Auditing services

#### Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

#### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

#### www.LegacyGlobal.com

#### Some brands we carry







# Honeywell













