

Xenon 1902

Wireless Area-Imaging Scanner

Xenon 1902, Honeywell's sixth-generation of area-imaging technology, is redefining the standard for hand-held scanners. Featuring a custom sensor that is optimized for bar code scanning, Xenon 1902 offers industry-leading performance and reliability for a wide variety of applications that require the versatility of area-imaging technology plus the freedom of Bluetooth® wireless connectivity.

Powered by Adaptus® Imaging Technology 6.0, Xenon 1902 delivers superior bar code scanning and digital image capture. Xenon 1902 incorporates a revolutionary decoding architecture that combines Adaptus Imaging Technology 5.5 and Omniplanar's SwiftDecoder™ software along with a custom sensor, enabling extended depth of field, faster reading, and improved scanning performance on poor quality bar codes. From high density linear to 2D bar codes found directly on the screen of a mobile device, Xenon 1902 decodes virtually all bar codes with ease.

Xenon 1902 incorporates a Bluetooth Class 2, v2.1 radio, enabling unrestricted movement up to 33 feet (10m) from the base. Honeywell's Shift-PLUS™ power management system provides up to 14 hours of battery life, maximizing productivity. For added convenience, a paging system helps locate misplaced scanners.

A new space-saving design that mounts critical components on a single board eliminates the need for connectors. A more reliable design with fewer components minimizes downtime and improves serviceability, resulting in increased productivity. Its small form factor ensures that the Xenon 1902 fits well in nearly any sized hand, reducing fatigue.

Built with durability in mind, Xenon 1902 can withstand up to 50 drops to concrete from 6 feet. An IP41-rating provides added protection. With a solid-state design backed by a three-year warranty, Xenon 1902 is constructed to deliver years of uninterrupted performance.



Features

- Wireless Connectivity: Bluetooth Class 2, v2.1 radio enables movement up to 33 feet (10m) from base, reduces interference with other wireless systems, and lowers total cost of ownership by allowing up to seven imagers to communicate to a single base
- Long-Lasting Lithium-lon Battery: Powers up to 50,000 scans per full charge, ensuring maximum uptime
- Flexible Power Management: Allows user to limit radio power output of scanner, minimizing the likelihood of interference with other devices
- Optional Disinfectant-Ready Housing: Protects investment with durable construction that is better able to resist the harmful effects of harsh chemicals
- Image Processing Software: Offers advanced editing functionality—cropping, brightening, rotating, sharpening and more—to produce high-quality digital images
- TotalFreedom™ 2.0: Second-generation development platform enables the loading and linking of multiple applications on the scanner to enhance image processing, decoding or data formatting functionality, eliminating the need for host system modifications
- Remote MasterMind™ Scanner Management Software:
 Provides a quick and convenient solution for IT administrators seeking to manage all scanners within their network from a single remote location

Xenon 1902 Technical Specifications

	•			
Wireless				
Radio/Range	2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1; Class 2: 10 m (33') line of sight			
Data Rate (Transmission Rate)	Up to 1 Mbit/s			
Battery	1800 mAh Li-ion minimum			
Number of Scans	Up to 50,000 scans per charge			
Expected Hours of Operation	14 hours			
Expected Charge Time	4.5 hours			
Mechanical/Electrical				
	Scanner	Charger/Communication Base		
Dimensions (LxWxH)	104 mm x 71 mm x 160 mm (4.1" x 2.8" x 6.3")	132 mm x 102 mm x 81 mm (5.2" x 4" x 3.2")		
Weight	214 g (7.5 oz)	179 g (6.3 oz)		
Operating Power (Charging)	N/A	5 W (1A @ 5 V)		
Non-Charging Power	N/A	0.5 W (0.1A @ 5 V)		
Host System Interfaces	N/A	USB, Keyboard Wedge, RS232, IBM 46xx (RS485)		
Environmental				
Operating Temperature	0°C to 50°C (32°F to 122°F)	Charging: 5°C to 40°C (41°F to 104°F) Non-Charging: 0°C to 50°C (32°F to 122°F)		
Storage Temperature	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)		
Humidity	0 to 95% relative humidity, non-condensing	0 to 95% relative humidity, non-condensing		
Drop	Designed to withstand 50 1.8 m (6´) drops to concrete	d 50 1.8 m (6') drops to concrete Designed to withstand 50 1 m (3.3') drops to concrete		
Environmental Sealing	IP41	41 IP41		
Light Levels	0 to 100,000 lux (9,290 foot-candles)	N/A		
Scan Performance				
Scan Pattern	Area Image (838 x 640 pixel array)	Area Image (838 x 640 pixel array)		
Motion Tolerance	Up to 610 cm/s (240 in/s) for 13 mil UPC at optimal for	Up to 610 cm/s (240 in/s) for 13 mil UPC at optimal focus		
Scan Angle	(HD): Horizontal: 41.4°; Vertical: 32.2° (SR): Horizontal: 42.4°; Vertical: 33° (ER): Horizontal: 31.6°; Vertical: 24.4°			
Print Contrast	20% minimum reflectance difference	20% minimum reflectance difference		
Pitch, Skew	45°, 65°			
Decode Capabilities Reads standard 1D, PDF, 2D, Postal and OCR symbologies *Note: Decode capabilities dependent on kit configuration				
Warranty	3 year factory warranty (Note: battery warranty is 1 year)			

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies

**Data Matrix (DM)

	Typical Performance*	High Density (HD)	Standard Range (SR)	Extended Range (ER)	
	Narrow Width				
	5 mil Code 39	0 mm - 91 mm (0" - 3.6")	36 mm - 127 mm (1.4" - 5")	114 mm - 198 mm (4.5" - 7.8")	
	13 mil UPC	15 mm - 150 mm (0.6" - 5.9")	13 mm - 401 mm (0.5" - 15.8")	36 mm - 500 mm (1.4" - 19.7")	
	20 mil Code 39	20 mm - 208 mm (0.8" - 8.2")	18 mm - 480 mm (0.7" - 18.9")	38 mm - 643 mm (1.5" - 25.3")	
	6.7 mil PDF417	0 mm - 94 mm (0" - 3.7")	15 mm - 137 mm (0.6" - 5.4")	84 mm - 221 mm (3.3" - 8.7")	
	10 mil DM**	0 mm - 104 mm (0" - 4.1")	15 mm - 178 mm (0.6" - 7")	104 mm - 256 mm (4.1" - 10.1")	
3	20 mil QR	18 mm - 173 mm (0.7" - 6.8")	15 mm - 371 mm (0.6" - 14.6")	18 mm - 467 mm (0.7" - 18.4")	
	Resolution 1D Code 39	3 mil (0.076 mm)	5 mil (0.127 mm)	5 mil (0.127 mm)	
	Resolution 2D DM**	5 mil (0.127 mm)	6.7 mil (0.170 mm)	7.5 mil (0.191 mm)	
	*Performance may be impacted by har code quality and environmental conditions				



For more information:

www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















