



IF2

Network Reader

- **Advanced performance in a compact and cost-effective design**
- **Easily deployed and managed on common networks**
- **Low cost per read point for superior ROI**
- **Choice of Power over Ethernet lowers cost of installation**
- **Directly monitors and controls peripherals without extra equipment**
- **Factory configurable to operate in world regions supporting FCC or ETSI frequency bands**

The Intermec IF2 is a compact, cost-effective network reader designed to support diverse RFID applications in both enterprise and industrial environments that require a scalable RFID system with a low cost per read point.

The IF2 is based on an Intermec-designed radio frequency (RF) platform that offers best-in-class read performance and includes support for Intermec's exclusive Advanced RFID Extensions (ARX), helping customers achieve a new level of visibility to the identification of RFID tags for greater accuracy of reading tags of interest over readers utilizing less-versatile commodity chipsets.

Packaged in a small and lightweight, yet durable enclosure, the IF2 is suited for nearly any environment, including industrial warehouse and manufacturing operations and enterprise environments for asset and inventory management applications.

Reduces System and Deployment Costs for Large and Small Installations

With a focus on keeping the cost of ancillary equipment and installation low, the IF2 Network Reader includes features that reduce the costs and complexity of the overall solution.

Not only does the low-profile enclosure with integrated mounting slots allow the IF2 to be easily installed in virtually any environment, the IF2 also supports Power over Ethernet (PoE) for scalable deployments without the cost of adding electrical drops where AC line power is not available or practical. An optional DC converter is available to support conventional wall power. Either power method supports the full RF output power capability of the IF2 (up to 30 dBm).

Because the general purpose input/output (GPIO) circuitry can be powered directly through either PoE or the DC power converter, the IF2 allows for direct monitoring and controlling of peripherals such as presence detectors and signal lights without requiring extra devices and power supplies to facilitate the connection.

Further reducing installation and equipment costs, the IF2's four antenna ports can be configured to transmit in either mono- or bi-static mode, increasing the flexibility of the system to achieve the best results for the application and environment. A variety of antennas from Intermec's extensive product line supports diverse applications, versus integrated antenna readers that include one type of antenna and limit the flexibility of applications and deployment.

Easy to Use and Manage

The IF2 supports standard network device protocols, including auto-discovery and network service protocols, enabling seamless integration with common network infrastructures.

Supporting the standards-based LLRP application interface, the IF2 can quickly integrate with business solutions such as IBM® WebSphere® RFID and Microsoft® BizTalk® RFID, providing a scalable standardized platform for the development, deployment, and management of RFID solutions. The IF2 also supports Intermec's easy to use Basic Reader Interface (BRI), enabling Intermec customers and partners to quickly and seamlessly include the IF2 in their solutions.

The IF2 comes factory-loaded with the Intermec SmartSystems™ client at no extra charge. Intermec SmartSystems Foundation allows administrators to change device settings, send firmware upgrades, update software applications, and execute other changes on multiple devices directly from a centralized console to save time and cost for deploying, configuring, and maintaining the Intermec hardware.

Intermec's Advanced Services can provide process analysis, site analysis, installation and an 18-month guarantee of system performance.

In support of global operations, the IF2 is certified in regions across the globe and is factory configured to operate in the corresponding RFID frequency band.

General Description

The IF2 is a compact, cost-effective network reader designed to support diverse passive UHF RFID applications in both enterprise and industrial environments. The IF2 supports Power over Ethernet, four mono- or bi-static RF ports, built-in powered general purpose input output (GPIO) control, and both standards-based LLRP and Intermec's easy to use Basic Radio Interface (BRI) application interfaces, enabling scalable low-cost deployments for improved return on investment (ROI). The IF2 is packaged in a durable enclosure for nearly any environment and is factory configured to operate in regions across the globe.

Physical Characteristics

Length: 18.85 cm (7.42 in)
Length w/splashguard: 19.9 cm (7.87 in)
Width: 16.31 cm (6.42 in)
Height: 4.32 cm (1.70 in)
Weight: 1.0 kg (2.2 lbs)
LED Status Indicators: RFID service, power, PoE, Ethernet, tag detection, and antenna port connection status

Environmental

Operating Temperature: -20 to 50°C (-4 to 122°F)
Storage Temperature: -30 to 70°C (-22 to 158°F)
Relative Humidity: 5% to 95% (non-condensing)
Enclosure: IP53 sealing
Die cast magnesium base, Lexan plastic cover

Connectivity

Communications: 10/100 BaseT Ethernet
RS-232, USB for configuration
Input Power: PoE (802.3at compliant)
DC power input (12 VDC +/-5%, 30W), sealed/
locking connection. Requires optional
Intermec 100/240 VAC converter.

General Purpose

Input/Output (GPIO): Four input (0-40 VDC)
and four output (0-48 VDC, 0.25 amp) circuits,
powered via PoE or DC input (500 mA, 12 VDC)

RF Characteristics

Antenna Connections: Four reverse-polarity (RP) TNC
ports configurable for mono- or bi- static operation.
Antenna fault detection and auto tuning for best
performance
Output Power: 1 to 30 dBm, configurable in 1 dB steps
(calibrated above 9 dBm)
Frequency Ranges: FCC (902-928 MHz) and
ETSI (865-868 MHz), factory configured

Software Platform

Passive UHF Tag Protocols:

ISO 18000-6B
ISO 18000-6C
EPCglobal UHF Class 1 Gen 2

Tag Features:

NXP G2X, Impinj Monza 4QT extensions
High memory tags (Fujitsu, Tego, ATA)

Host Application Protocols:

EPCglobal LLRP
Intermec Advanced RFID Extensions (ARX)
Intermec Basic Reader Interface (BRI)
Intermec Developer Library (IDL) resource
kit for BRI (Java, C# .NET)

Management and Configuration:

Bonjour
Universal Plug and Play (UPnP)
Intermec SmartSystems client
Intermec Web Services and Web Configuration Interface

Network Protocols:

HTTP/HTTPS Web Server
IPv4, IPv6
DHCP, DNS, NTP, Syslog

Security

FIPS 140-2 compliance for HTTPS, LLRP-secure,
and Web Services (DCWS)-secure
RADIUS client support
SSL Certificate support

Accessories

Intermec approved antennas, antenna cables

Regulatory Approvals and Compliance

Model: 1009FF01

Safety: IEC/UL 60950-1

EMC: Class B - FCC/ICES/EN

Intermec Global Services Support

www.intermec.com --> Support --> Knowledge Central
Telephone support available in the USA & Canada
(+1-800-755-5505). Outside of this area,
contact your local representative.

Restrictions on Use

Some approvals and features may vary by country and
may change without notice. Please check with your
local Intermec sales office for further information.

North America

Corporate Headquarters

6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

North Latin America

Headquarters Office

Mexico
Phone: +52 55 52-41-48-00
Fax: +52 55 52-11-81-21

South Latin America

Headquarters Office

Brazil
Phone: +55 11 3711-6776
Fax: +55 11 5502-6780

Europe/Middle East & Africa Headquarters Office

Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office

Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW:
00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2011 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 612043-01C 05/11

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684