

- Perfect complement for Intermec CN3, CN3e and CK61 mobile computers
- Convenient, integrated solution simplifies use in both portable and vehicle mount applications
- Optimized for DSD, Home Delivery and Field Service applications
- Integrated DEX communications allows easy connectivity to in-store computer system
- Optional magnetic stripe and smart card readers
- Patented power management maximizes battery life
- High-speed electronics and highvoltage battery deliver fast print speeds
- Standard communications includes Bluetooth[®] and serial



Designed specifically for use with Intermec CN3, CN3e, and CK61 mobile computers, the PW50 four-inch mobile workboard printer provides a convenient, integrated solution for DSD and field service applications. With its integrated DEX communications, fast print speed, Bluetooth connectivity, and optional integrated smart card and magnetic stripe readers, the PW50 provides everything the mobile worker needs to process transactions quickly and easily.

This integrated solution provides a single convenient bundle that can easily be transported or installed in a vehicle. Custom holders safely secure the handheld computer in the mobile printer, yet allow easy removal for scanning or data entry. Hand straps and shoulder straps are available to simplify moving the equipment between the truck and the point of delivery. Drivers can easily keep batteries charged on both the printer and handheld computer: a single electrical connection through the vehicle mount or 12 volt adapter will charge both devices simultaneously.

The PW50 interfaces seamlessly with Bluetooth-enabled Intermec mobile computers including the CN3, CN3e, and CK61. Bluetooth connectivity allows the print job to be initiated whenever the handheld and printer are within wireless range of each other. A unique design combines a high-voltage battery, patented techniques for power management, and high speed "desktop" electronics. This enables the PW50 to print the full-width of all pixels simultaneously and achieve best-in-class print speeds.

Patented power management of the robust 4-cell Li-lon battery enables the PW50 to maintain consistent voltage to the print head for high quality printing, independent of the charge remaining in the battery. Battery capacity is designed to print 2 full rolls of receipts with 10% density text without the need to charge or change the batteries.

With 64MB of on-board Flash memory and the ability to store a full Unicode font, the PW50 gives users the flexibility to easily use multiple languages. In addition, users can improve throughput by storing frequently-used formats and graphics on the printer, eliminating the need to download large files from the mobile computer.

The PW50 combines rubberized bumpers, extra-durable gears, and a fully-integrated radio and antenna, enabling the printer to withstand the bumps and drops common to fast-paced mobile usage.

The PW50 is designed for ease of use. Paper loading, charging, and printing are fast and simple, enabling users to perform their job efficiently. Physical Characteristics Height: 180 mm (7.0 in) Width: 310 mm (12.2 in) Depth: 80 mm (3.2 in) Weight: 1688 g (59.5 oz) with battery

Environmental

Operating temperature: -20°C to 50°C (-4°F to 122°F) Storage temperature: -30°C to 70°C (-22°F to 158°F) Charging temperature: 0°C to 40°C (32°F to 104°F) Humidity: 10 to 90% (non-condensing) Electrostatic Discharge: Contact Discharge: +/-8kV Air Discharge: +/-15kV Sealing: IP20 Drop spec: Survives 1.2 m (4 ft) drops to concrete

Power

Battery: Rechargeable 14.8V Li-Ion, 2200mAh (4 cells); 32.56 watt hours; Battery must be ordered separately. Recharging: 6 hours maximum AC Adapter: 50 watts Voltage Range: 12V +/- 5%

Memory

RAM: 16MB Flash: 64MB

Standard Communications

RS-232 Serial (115k) Bluetooth® (Class 1) DEX / UCS

Optional Features

Magnetic Stripe Reader and Smart Card Reader (EMV level 1 certified)

Print Speed and Resolution

4 IPS (100 mm/s) 203 DPI (8 dots/mm) Maximum Print Width 108 mm (4.25 in)

Media

Supports receipt media in both top coated and uncoated paper in continuous roll stock only. **Type:** Direct thermal fanfold and receipt. **Media width:** 111.5 mm (4.4 in) **Media length for fanfold:** 25.4 mm (1.0 in) min;

609.6 mm (24 in) max **Media length for receipt:** Continuous

Media thickness for receipts: 2 mil (0.05 mm) to 4.4 mil (0.112 mm) Core ID: 19 mm (0.75 in) standard, 10mm (0.40 in) optional

Capacity: 67.3 mm (2.65 in) max. roll diameter (approximately 200", depending on media thickness)

Note: Print Speed and Environmental performance are specified for typical receipt printing applications with 10% density text.

Software Programming Language

ESC-P command sets (Line Print and EZ Print)

Character Sets

West European Latin No.1 and 9: Danish, Dutch, English Faeroese, Finnish, French, German, Icelandic, Irish, Italian, Norwegian, Portuguese, Spanish, Swedish East European Latin No.2: Albanian, Czech, English, German, Hungarian, Polish, Rumanian, Serbo-Croatian, Slovak, Slovene Cyrillic: Bulgarian, Byelorussian, English, Macedonian, Russian, Serbo-Croatian, Ukrainian Arabic Greek Hebrew U.S. Standard Europe multilingual Code Page requirements for Asian characters

Font types

40 column, normal, bold, 80 column, normal, bold, 132 column, normal, bold

Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos

Barcode Symbologies

1D: Codabar, Code 39, Code 128, Code 128 Subset A-C, EAN-8, EAN-13, EAN-128 Subset C, Interleaved 2 of 5, UPC-A **2D:** PDF 417

User Interface

LEDs and two external buttons: Standby (Power), Paper Feed

Four audio status indicators: Error alert, hardware change alert, button press alert and startup alert

Accessories

Hand strap, shoulder strap, vehicle mount, cleaning card, battery, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable.

Approvals

North America UL and cUL Listed, UL 60950-1 Europe - GS Licensed, EN 60950-1 Mexico NYCE Certified, NOM 19 Other Countries IEC 60950-1 EMC Approvals USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN55022 Class B + EN55024) ; CISPR22

Warranty

One year; additional Medallion service packages available

North America

Corporate Headquarters 6001 36th Avenue West Everett, Washington 98203 Phone: (425) 348-2600 Fax: (425) 355-9551

South America & Mexico Headquarters Office Newport Beach, California Phone: (949) 955-0785 Fax: (949) 756-8782

Europe/Middle East & Africa Headquarters Office Reading, United Kingdom Phone: +44 118 923 0800

Fax: +44 118 923 0801

Headquarters Office Singapore Phone: +65 6303 2100 Fax: +65 6303 2199

Internet

www.intermec.com Worldwide Locations: www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163 Toll in NA: (425) 348-2726 Freephone ROW: 00 800 4488 8844 Toll ROW: +44 134 435 0296

OEM Sales Phone: (425) 348-2762

Media Sales Phone: (513) 874-5882

Customer Service and Support Toll Free NA: (800) 755-5505 Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611880-01A 04/08

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













