Technology at Work.®





XP Series

Put your Palm OS applications to work.

Janam's XP Series rugged mobile computers combine the benefits of Palm OS^{\otimes} GarnetTM with the advanced features today's mobile applications demand. Purpose built for maximum performance, the XP Series is designed to:

- Support barcode scanning applications written for earlier versions of Palm OS
- Extend solutions with new functionality
- · Improve productivity and performance

Reclaim your technology roadmap.

Janam's XP Series delivers state-of-the-art processor and memory technology in a remarkably small and light package. As a drop-in replacement for existing rugged Palm OS mobile computers, the XP Series provides an easy migration path that protects users' investments in legacy Palm applications and work processes. Now customers can continue to deploy their proven and cost-effective Palm OS applications as needed and upgrade their technology on their own timetable, not someone else's.

The right tool for the job.

Janam designed the **XP20** to execute mission-critical, data collection tasks in the enterprise. Every element of the product's form and function has a purpose. For example, the XP20 Series' custom, "bright-white" monochrome display was created because it offers the same 160x160 screen resolution as legacy Palm OS products, thereby facilitating application migration across hardware platforms. At the same time, the XP20 Series also delivers significant improvements over legacy Palm OS products, each one aimed at extending the product's reach into the enterprise. Customers no longer need to compromise on features like numeric keypad, 2D barcode scanning, permanent memory backup of applications and data, keypad backlighting, WLAN security, battery capacity and many more.

The **XP30** is the world's first fully-featured mobile computer that scans barcodes and runs the latest version of the Palm OS. A brilliant, color, quarter-VGA display and blazing Freescale $^{\text{TM}}$ architecture make the XP30 a best-of-breed, rugged, barcode scanning, mobile computer, while its list price makes it impossible to ignore. For customers who want to extend the reach and capability of their mobile Palm applications, the XP30 has the horsepower to execute mission-critical data collection tasks at the point of business activity. And for customers who are ready to switch to the Palm OS for its simplicity and its durability, the XP30 is a platform that pays for itself twice as fast as comparable devices.



XP30 with Numeric Keypad

Purpose. Performance. Productivity.





1D and 2D Barcode Scanning

Expanded data collection capability with Adaptus $^{\circledR}$ Imaging Technology

32MB SDRAM/64MB NAND and Total Recall

Power and performance plus complete application and user data backup

- Color screen option

Supports graphics-intensive applications

Less than 10 ounces

Smaller and lighter than comparable mobile computers

Built tough for today's mobile workers


Sealed to IP54 standards and withstands drops from four feet to concrete

- Keypad options - Numeric or PDA-style

Designed for application flexibility, both versions are backlit and easy to program

Enterprise class WLAN

Advanced WEP and WPA security protocols to protect mission-critical data transmission



With **Adaptus® Imaging Technology**, the XP Series easily reads all types of barcode symbologies including linear, stacked and two-dimensional. Regardless of the type of barcode used today, the XP Series offers the flexibility to adapt as business needs change, without the need to invest in new hardware.



XP20 Series Specifications



TE	СН	N 1	N۱

TECHNICAL				
Operating System	Palm OS 5.4.9 Garnet			
Processor	Freescale™ i.MX21 @266MHz			
Memory	32MB SDRAM, 64MB NAND, NAND flash backup of OS, applications and user data			
Expansion	User accessible miniSD card slot			
Power	Swappable 3.7V 2000mAh rechargeable Li-ion main battery; rechargeable 20mAh Ni-MH backup battery			
PHYSICAL				
Dimensions	1.28" H x 3.11" W x 5.75"L/ 32.5n	nm H x 79mm W x 146mm L		
Weight	9.88oz / 280g with battery			
Keypad	PDA keypad (with 4-way navigatio	n) or numeric keypad		
Display	Bright white monochrome FSTN 16	50x160 LCD display		
Touch Panel	Analog resistance type; stylus inpu	ıt		
ENVIRONMENTAL				
Operating Temperature	14° to 122°F/ -10° to 50°C			
Storage Temperature	-13° to 158° F / -25° to 70° C			
Humidity	5% to 90% RH (no condensation)			
Drop	Multiple 4ft / 1.2m drops to concrete on all sides across a wide temperature range			
Water & Dust	IP54 Category II			
Vibration	0.03 G ² /Hz from 20Hz to 2kHz; 1 hour random wave per axis			
Electro Static Discharge (ESD)	+/- 15kVDC air; +/- 8kVDC contact			
Sterilization	76.9% to 81.4% concentration alcohol rub			
Ambient Light	450ft-candelas (artificial light); 8,000ft-candelas (sunlight)			
INTERFACE FEATURES				
Audio	Buzzer			
Alerts	Vibration, LED indicators, audio be	ep		
LED Indicators	Tri-color			
Scan Triggers	Left, right, center buttons			
DATA CAPTURE	-			
Imager	1D/2D Adaptus [®] Imaging Technol	ogy; 752 x 480 pixel CMOS area imager		
1D Symbologies	93i, Code 128, EAN-8, EAN-13, GS 128, Matrix 2 of 5, Korea Post, MSI	Code 11, Code 16K, Code 32 Pharmaceutica 1-128, GS1 Databar (RSS-144, RSS Limited I, Plessey Code, PosiCode, , Straight 2 of 5 elepen, Trioptic Code, UPC-A, UPC-A with Ex	IATA (two-bar start/stop), Straight 2 of 5	
2D Symbologies (with firmware upgrade)	PDF417 (EAN-UCC Composite, MicroPDF417, PDF417, TCIF Linked Code 39, TLC39), 4-CB (4-State Customer Barcode), Australian Post, Aztec Code, Aztec Mesas, British Post, Canadian Post, GS1 Data Matrix, Han Xin, ID-tag (UPU 4-State), Japanese Post, KIX (Netherlands) Post, MaxiCode, OCR, Planet Code, Postnet, QR Code			
DATA COMMUNICATION				
IrDA	Standard v1.2			
USB	v1.1 client (up to 12Mbps)			
WLAN	IEEE 802.11b/g, 2.4GHz, WPA support			
ACCESSORIES				
	Single-Slot Cradle Kit	RFID Reader	Stylus 5-Pack	
	Four-Slot Cradle Kit	Cable Cup	Stylus Tether	
	Modem Cradle Kit	Vehicle Charger	Nylon Holster	
	Extended Capacity Battery	Syncing/Charging Cables	Adjustable Handstrap	
	Magnetic Stripe Reader	Battery Charger	Operating Case	
SAFETY/REGULATORY				
Safety	UL60950-1, CSA C22.2 No. 60950-	-1-03, EN60950-1:2001+A11, GS, NOM		
EMI	FCC Part 15 Subpart B, EN55022:1998+A1: 2000+A2:2003, EN55024:1998+A1:2000+A2:2003, ICES-003 Issue 4, AS/NZS CISPR 22:2004			
RF	FCC Part 15 Subpart C and Supart B, EN300 328 v1.6.1 (2004-11), EN301 489-1 v1.6.1 (2005-09), EN301 489-17 v1.2.1 (2002-08), RSS 210 Issue 6, COFETEL			
	UL Listing (US and Canada) Class I Div 2, Groups A, B, C, D			

XP30 Series Specifications



-			100		
- 11	EC	нг	MT.	LA	ш

TECHNICAL			
Operating System	Palm OS 5.4.9 Garnet		
Processor	Freescale™ i.MX21 @266MHz		
Memory	32MB SDRAM, 64MB NAND, NAM	ND flash backup of OS, applications and us	ser data
Expansion	User accessible miniSD card slot		
Power	Swappable 3.7V 2000mAh rechargeable Li-ion main battery; rechargeable 20mAh Ni-MH backup battery		
PHYSICAL			
Dimensions	1.20" H x 3.11" W x 5.75" L / 30	.5mm H x 79mm W x 146mm L	
Weight	9.88oz / 280g with battery		
Keypad	Backlit PDA keypad (with 4-way	navigation) or backlit numeric keypad	
Display	2.17"W x 2.95"L / 55.0mm W x	75.0mm L; 262K colors TFT QVGA (240x)	320)
Touch Panel	Analog resistance type; stylus ir	nput	
ENVIRONMENTAL			
Operating Temperature	14º to 122ºF/ -10º to 50ºC		
Storage Temperature	-13° to 158°F/ -25° to 70°C		
Humidity	5% to 90% RH (no condensatio	n)	
Drop	·	·	ire range
Water & Dust	Multiple 4ft / 1.2m drops to concrete on all sides across a wide temperature range IP54 Category II		
Vibration		1 hour random wave per axis	
Electro Static Discharge (ESD)	0.03 G ² /Hz from 20Hz to 2kHz; 1 hour random wave per axis +/- 15kVDC air; +/- 8kVDC contact		
Sterilization	76.9% to 81.4% concentration alcohol rub		
Ambient Light	450ft-candelas (artificial light); 8,000ft-candelas (sunlight)		
INTERFACE FEATURES	+3010 Canacias (artificial light),	o,ooore canacias (samighe)	
Audio	Speaker and Microphone		
Alerts	Speaker and Microphone		
LED Indicators	Vibration, LED indicators, audio beep		
Scan Triggers	Tri-color Left, right, center buttons		
DATA CAPTURE	Leit, right, center buttons		
Imager	1D/2D Adaptus [®] Imaging Tochr	pology, 752 v 490 pivol CMOS area image	
1D Symbologies	1D/2D Adaptus [®] Imaging Technology; 752 x 480 pixel CMOS area imager China Post, Codabar, Codablock F, Code 11, Code 16K, Code 32 Pharmaceutical (PARAF), Code 39, Code 49, Code 93 and 93i, Code 128, EAN-8, EAN-13, GS1-128, GS1 Databar (RSS-144, RSS Limited, RSS Expanded), Interleaved 2 of 5, ISBT 128, Matrix 2 of 5, Korea Post, MSI, Plessey Code, PosiCode, , Straight 2 of 5 IATA (two-bar start/stop), Straight 2 of 5		
2D Symbologies	, 17,	Telepen, Trioptic Code, UPC-A, UPC-A with icroPDF417, PDF417, TCIF Linked Code 39	· · · ·
(with firmware upgrade)	PDF417 (EAN-UCC Composite, MicroPDF417, PDF417, TCIF Linked Code 39, TLC39), 4-CB (4-State Customer Barcode), Australian Post, Aztec Code, Aztec Mesas, British Post, Canadian Post, GS1 Data Matrix, Han Xin, ID-tag (UPU 4-State), Japanese Post, KIX (Netherlands) Post, MaxiCode, OCR, Planet Code, Postnet, QR Code		
DATA COMMUNICATION			
IrDA	Standard v1.2		
USB	v1.1 client (up to 12Mbps)		
WLAN	IEEE 802.11b/g, 2.4GHz, WPA support		
ACCESSORIES			
	Single-Slot Cradle Kit	RFID Reader	Stylus 5-Pack
	Four-Slot Cradle Kit	Cable Cup	Stylus Tether
	Modem Cradle Kit	Vehicle Charger	Nylon Holster
	Extended Capacity Battery	Syncing/Charging Cables	Adjustable Handstrap
	Magnetic Stripe Reader	Battery Charger	Operating Case
SAFETY/REGULATORY			
Safety	UL60950-1, CSA C22.2 No. 60950-1-03, EN60950-1:2001+A11, GS, NOM		
EMI	FCC Part 15 Subpart B, EN55022:1998+A1: 2000+A2:2003, EN55024:1998+A1:2000+A2:2003, ICES-003 Issue 4, AS/NZS CISPR 22:2004		
Litt			
RF	CISPR 22:2004		89-1 v1.6.1 (2005-09), EN301 489-17 v1.2.1

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

 Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com

Some brands we carry





















