MP-4200 Series

Thermal Printers



- Fast printing up to of 9.8" per second (250 mm/s)
- Large drop-in paper roll with 410' capacity (125 m)
- Variable paper width from 2.29 to 3.25" (58.0 to 82.5 mm)
- Proven reliability and performance over 50,000 units sold
- OPOS drivers
- Windows Spooler drivers
- Proprietary features: Quick system error recovery and modular interface electronics
- User Software: allows for the user to try the printer capabilities



Efficient and Flexible

MP-4200 TH is the evolution of Logic Controls thermal printers for retail and hospitality industries. Its improved performance optimizes the checkout process. While its standard USB interface is aligned with the current interface trend in POS systems, the second, optional and customer installed interface allows it either to comply with traditional standards, such as RS232, or with Ethernet and Wi-Fi for special applications. This felxibility allows retailers to keep their printers in pace with the communication technology throughout the product life cycle, by simply changing the interface.

Reliable and Sturdy

MP-4200 TH is built with Logic Controls' Easy Recovery System (ERS) that enhances the reliability and Modular Cartridge System (MCS) that makes it easier for repairing and minimizes any down-time. If a paper jam occurs, ERS restores the printer's capability simply by lifting the printer cover, then lifting and putting back the paper roll. MCS holds all the electronic parts of the printer, allowing for the change of either the mechanism or the cartridge to be completed in store in a few minutes. These features optimize the ease of service and reduce the costs of printer down-time and maintenance. The MP-4200 TH housing is designed with an easy to clean, non-fading material which makes it ideal for demanding environments.

Compatibility

The wide range of MP-4200 TH software tools makes it one of the easiest printers to integrate to commercial applications. To allow a quick and easy installation in any environment, the MP-4200 TH offers a wide range of point-of-sale protocols, such as OPOS, spooler drivers for either Windows or Linux (CUPS). Furthermore the USB interface presents itself to the host system as a virtual COMM port, allowing legacy software to use it with almost zero effort. Local area network users may also take advantage of Ethernet interface by using the embedded LPD printer server.

MP-4200 THERMAL PRINTER SPECIFICATIONS

MECHANICAL

Weight 2.6 lbs / 1.2 kgs

Dimension (WxDxH) 5.90" x 8.58" x 5.75"

150 mm x 218 mm x 146 mm

PRINTING

Method Direct thermal line printing Printing Speed Up to 9.84"/s (250 mm/s),

configurable

Paper Feed Speed 59 lps

Dot Density 0.32 dots/in (203 dpi x 203dpi)

Printing Width

Paper Width (inch) Printing Width (inch)

2.28" (58 mm) 1.89" (48 mm or 384 dots) 2.99" (76 mm) 2.83" (72 mm or 576 dots) 3.15" (80 mm) 2.99" (76 mm or 608 dots) 3.25" (82,5 mm) 3.15" (80 mm or 640 dots)

Characters per Line 24, 32, 48, 64 or 21, 28, 42, 56 Character Set Code pages 437 (USA/ Standard

Europe), 850 (Multilingual "Latin-1" - Western European Languages), 858 (Multilingual with Euro symbol), 860 (Portuguese), 862 (Hebrew), 864 (Arabic) and 866

(Cyrillic).

FEATURES

Paper cutter Total or partial cut configurable,

panel or software application

control

EAN-8, EAN-13, CODE 39, CODE Bar Codes

> 93, CODE 128 (A, B and C), ITF. CODABAR, UPC-A, UPC-E, ISBN, MSI, Plessey and PDF-417

Selectable font styles Normal, Double High, Double Wide,

> Double High & Wide, Emphasized, Bold, Underscore, Italic, Inverted,

superscript, underscript

End of Paper Sensor, Near End Sensors

Paper Sensor, Top Cover Sensor,

Print Head Sensor

Buttons Paper feed & Paper cut Power & Information LEDs Indicators

Cash Drawer Driver 01 driver (RJ-12 connector) Easy paper loading Drop in and easy paper loading

Firmware Downloadable Logos and character font table Downloadable

Under software application control Buzzer Bitmap Image Buffer 16KB for volatile memory and

256KB for non-volatile memory

MEDIA

Single-ply thermal paper roll Type Width 2.28" to 3.25" (58 to 82,5 mm)

Diameter Up to 4" (102 mm) Thickness 56 to 107 microns

COMMUNICATION INTERFACES

Communication Interfaces **USB 2.0**

Serial DB25 Ethernet

DRIVERS

Spooler for Microsoft Windows XP, Vista, and 7 (32 and 64-bit)

Spooler for Linux (CUPS) OPOS for Windows

Virtual Serial Drivers (32 and 64 bits)

POWER

100 -240 VAC 50/60Hz to 24VDC ± 10%, 2.5A (external)

ACCESSORIES

Power Supply, Communication Cable, Paper Roll

ENVIRONMENT

Operating temperature 32 to 122°F (0 to 50 °C) Operating Humidity

10 to 90% RH (non condensing)

CERTIFICATION

ROHS compliant, FCC, UL, CE





Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value.
 Legacy routinely purchases equipment from our clients around the globe.
 - · Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.









Toll Free: 866-271-9891

Fax: 888-522-4684



Smarter

www.LegacyGlobal.com
Some brands we carry



















