



HIGH PERFORMANCE FOR HIGH THROUGHPUT ENVIRONMENTS

MOTOROLA AN440 RFID ANTENNA

LARGE AREA COVERAGE IN NEARLY ANY ENVIRONMENT

Need to keep track of thousands of assets? High product density and heavy traffic across a large area? Get the capacity and range you demand for reliable RFID tag reading with the AN440 high-performance RFID area antenna. A good-looking, rugged general-purpose area antenna, the AN440 is designed to perform exceptionally in all environments, indoors and out.

The AN440 RFID Antenna gives you a wide read field and high-speed RF signal conversion, so data capture is fast and accurate, even in expansive, high-demand environments. The AN440 is easy to mount on ceilings and walls, and its rugged white housing is at home in both customer-facing and industrial settings. So you can achieve superior read zones around stockroom shelves, warehouse doorways and dock platforms – anywhere boxes and pallets are moving into and out of your facility.

HIGHEST PERFORMANCE, MEET LONGEST READ RANGE

The rectangular AN440 antenna is designed to deliver faster, more accurate communication of EPC-compliant passive tag data to your RFID readers. So even in RF-challenging environments, you get longer read ranges and higher levels of performance. Your workflow keeps flowing, your inventory count stays accurate and your productivity can reach new heights.

In addition, its dual-element architecture makes the AN440 suitable for bi-static operation. Or it can be used as two separate mono-static antennas in a single package. Deployment with Motorola fixed RFID readers is fast and easy, as the AN440 meets all standard technical requirements for any RFID implementation. So you can get your large-area application off the drawing board and into your production environment, quickly and efficiently.

FEATURES

- Dual-element, ideal for bi-static operation
- Can be used as two separate mono-static antennas in one package
- Rugged design suitable for industrial applications

APPLICATIONS

- Ceilings and walls to create superior read zones around shelves
- Doorways and chokepoints where boxes and pallets are moving through
- Portals, outdoor gates and conveyors
- RF-challenging environments

END-TO-END LIFECYCLE SUPPORT

No matter what help you might need, we have you covered. Our full suite of services offers 'from the manufacturer' expertise throughout the entire lifecycle of your RFID solution — from assessment, commissioning and rollout to ongoing training and day-to-day support. Our RFID Advanced Services provide the assistance you need to architect your solution for your business, processes and environment, ensuring that your pilot or full-scale rollout is designed to deliver peak performance — and maximum benefits. And post deployment, Motorola's Support Services provide the everyday support you need to keep your RFID solution up and running day in and day out, with service programs that include 24x7 on-site coverage and preventive maintenance visits.

For more information on how the AN440 RFID Reader can benefit your business, please visit us on the web at www.motorolasolutions.com/AN440 or access our global contact directory at www.motorolasolutions.com/contactus

AN440 RFID ANTENNA SPECIFICATIONS CHART

PHYSICAL		ENVIRONMENTAL	
Dimensions	22.6 inches L x 10.2 inches W x 1.32 inches D (575.1 mm L x 259.1 mm W x 33.52 mm D)	Environmental Sealing	IP-67
Connectors	2 x Type N female	RHOS Compliant	Yes
Connector Position	Back	Storage Temperatures	-40°F to +185°F (-40°C to +85°C)
Mounting Bracket	Integrated mounting holes	Vibration	IEC-68-2-6 (10 to 150 Hz, 05 g, 1 hour in each of two axes) (Random Vibration)
Weight	4.2 lbs (1.9 kg)	Humidity	MIL-Std 810G, METHOD 507.5, Procedure II - Aggravated
Casing	UV Stable ASA	Warranty	The AN440 is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.
Radome Material	UV Stable ASA, White		
OPERATIONAL		RECOMMENDED SERVICES	
Frequency Range	902 - 928 MHz	Support Services	Service from the Start Advance Exchange On-Site System Support
Gain	6 dBil	Advanced Services	RFID Design and Deployment Services
VSWR (Return Loss)	<1.4 : 1		
Front to Back Ratio	20 dB		
Polarization	1 x LHCP / 1 x RHCP		
3db Beam Width	70° in both phases		
Max Power	10 W		
Axial Ratio	1dB typical		
Operating Temperatures	-22°F to +158°F (-30°C to +70°C)		
DC Resistance	DC Grounded		

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.,
160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891
Fax: 888-522-4684