

NEC P Series

40", 46", 52", 55" and 70" professional-grade, full high-definition LCD displays ideal for digital signage applications

Expand your messaging options with superior screen performance. The NEC P Series, featuring the 40" P402, 46" P462, 52" P521, 55" P551 and 70" P701, provides a first-class solution for your digital signage applications. Its high contrast, industrial-strength design and Enhanced Digital Signage Technology Suite (DSTS), which boasts more than 30 advanced features, make these displays ideal for 24/7 operation in even the harshest environments. These include airports, public information, healthcare, retail and other areas that require a combination of dazzling images and the highest level of display management. The built-in expansion slot future-proofs your display investment, allowing for seamless integration of NEC and third-party components. Plus, the capability to easily integrate touchscreen technology or protective glass opens these models up to even more applications, including wayfinding and high-traffic areas. The P701's massive screen turns heads in corporate boardrooms as well as rental and staging applications. Advantages include a wide array of inputs, including DisplayPort, unrivaled control and communication options and enhanced video wall capabilities. The P551's 120 Hz refresh rate reduces typical blur seen in fast-moving images and text that is noticeable at the standard 60 Hz refresh rate. It also shows increased definition between images, giving you more lifelike viewing.



P SERIES HIGHLIGHTS

IMPROVED MECHANICAL DESIGN*

SLIMMER DEPTH

INTEGRATED SPEAKER

OPS & CURRENT SLOT SUPPORT

DIGITAL SIGNAGE TECHNOLOGY SUITE

INTEGRATED THERMAL PROTECTION

SEALED PANEL DESIGN

ENHANCED VIDEO WALL CAPABILITIES

ECO-FRIENDLY FEATURES

BUILT-IN EXPANSION SLOT

EXTENSIVE CONTROL, DIAGNOSTICS & COMMUNICATION

REAL-TIME CLOCK/ROUND-THE-CLOCK SCHEDULING

CABLECOMP+™ TECHNOLOGY


BUILT-IN TUNER (-AVT MODELS)

*available for select models

P Series Key Features

24/7 full-HD commercial SPVA panels

The professional-grade construction of P Series panels contributes to 24/7 usage, an overall longer panel life, lower likelihood of mura effect from localized heat, virtually no image retention and the ability to use in landscape or portrait orientations. The panel's thermal protection starts with an extra thermal layer on the display panel to diffuse heat, followed by multi-fan-based technology specially designed to work in both landscape and portrait modes and be controlled locally or remotely. Internal temperature sensors control self-protective circuits, while special self-diagnostics communicate the status of the thermal characteristics.



P Series panel construction includes:

- Thermal dissipation plate, placed behind the LCD lamps, conducts heat equally across the plate, preventing "hot spots" on the LCD
- Backlight layer (or lamps) determines the brightness of the display but is also a key heat component
- Wider air layer allows for increased airflow and improved heat dissipation
- Heat protection plate, located between the LCD panel and the lamps, provides added heat protection to the panel
- Panel is sealed, preventing contaminants like dust, grease or steam from damaging the panel*

Green technology helps lead to a lower total cost of ownership

Eco-friendly features are aplenty in the P Series, decreasing energy consumption, lowering your expenses over the lifecycle of the display and contributing to your environmental consciousness. These include:

- **Ambient light sensor** ensures consistent brightness no matter the lighting conditions, while allowing the user to set the brightness level to a pre-determined lower level in order to automatically compensate and reduce the brightness, thus decreasing power consumption
- **Carbon footprint meter** helps track and calculate the conservation of green gas emissions in real time
- **Real-time clock/round-the-clock scheduling** allows for advanced scheduling of monitor powering up/down, increasing panel lifetime, reducing power consumption and saving the time and expense of finding and purchasing a third-party scheduling solution
- **ENERGY STAR 5.0**** is proudly offered for most P Series displays, which meet strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and the U.S. Department of Energy, helping you save money and reduce greenhouse gas emissions



Built-in technology to support video wall configurations

Select P Series displays' thin-bezel design and enhanced video wall capabilities allow you to expand your messaging options. Technologies include:

- **TileMatrix™** allows you to create video walls (up to 100 displays in a 10x10 matrix)
- **TileComp™** works in tandem with TileMatrix to compensate for the bezel width and create a more seamless video wall
- **Copy function** allows the user to apply the settings from one display to all others in the RS-232 daisy chain, reducing setup time and saving money
- **Individual and Group ID functions** allow users to control settings for a defined individual display or group of displays within a video wall
- **Optional Display Wall Calibrator Kit (KT-46UN-CC; pictured)** provides a quick, accurate and easy-to-use means of automatically matching all displays in color and brightness to create uniformity across the video wall



*use under the environmental conditions noted in the specifications and user's manual
**available on select models

Full connectivity and control with the option for expansion in every display

The P Series touts the industry's most extensive control, diagnostics and communication, providing the highest level of remote display management. These include:


- **RS-232** enables multi-display control and daisy chain, allowing for individual and group-addressable control, and simple, effective setup and monitoring of the display
- **Ethernet connectivity** adds the same RS-232 control plus automatic email notification for diagnostic purposes
- **NaViSet™ software** offers an intuitive graphical interface, allowing for easy adjustment of display settings via mouse and keyboard. NaViSet Administrator provides all the advanced control to remotely located IT professionals.
- **DDC/CI standard** allows for PC control of the display based on the VESA command set
- **CableComp+** uses a digitized signal delay circuit to automatically compensate for each red, green and blue cable's length and video signal delay, ensuring sharp image reproduction despite long cables and low output level*
- **Expanded connectivity** with digital loop through (DVI-D and DisplayPort)**

A built-in expansion slot future-proofs your display investment, allowing for seamless integration of optional NEC and third-party components, including:


- **Open Pluggable Specification (OPS)**** is the first industry-wide standardization in option slots, simplifying installation, use and maintenance of digital signage.
- **HD-SDI card (SB-L007KK)**: Achieve broadcast-grade video with this internal card that provides an HD-SDI input without using additional space or power.
- **Single board computer (NET-SBC-01/02/03)**: This option provides for a seamless internal PC solution that is both cost-efficient and flexible. It eliminates the need for external cabling, mounting and power supply, providing for a clean look that simplifies installation and reduces maintenance.
- **DVI daisychain (SB-L008WU)****: Loop in and out a single digital video signal to up to nine displays with this option, which eliminates the need for external distribution equipment and power supply. These benefits make the board ideal for video banners, ribbons and walls in addition to back-to-back installations.
- **Digital IP tuner (MPD-DTi)**: This IPTV card enables you to stream up to 1080p content directly to the display as well as ATSC/NTSC/Clear QAM signals. Other features include auto scan, DTV signal strength, parental controls, closed caption and network settings—all adjustable from the display.
- **CAT5 receiver**: Using NEC-approved third-party solutions, you'll be able to safely send your video over longer distances.

The P Series sets the standard for connectivity. Improved input options include quick input change, customized detection and naming. See below for the complete list of P Series input/output terminals.

P521/P551/P701



P402/P462



*use under the environmental conditions noted in the specifications and user's manual

**available on select models

Specifications for P402/P462/P521/P551/P701

MODEL	P402	P462	P521	P551	P701
LCD MODULE					
Viewable Size (Diagonal)	40"	46"	52"	55"	70"
Panel Technology	SPVA				
Native Resolution	1920 x 1080				
Pixel Pitch	0.46mm	0.53mm	0.60mm	0.63mm	0.81mm
Brightness (Typical/Maximum)	500 cd/m ² / 650 cd/m ²		500 cd/m ² / 700 cd/m ²		420 cd/m ² / 600 cd/m ²
Contrast Ratio (Typical)	3000:1	3500:1	2000:1	3000:1	2000:1
Active Screen Area (W x H)	34.9 x 19.6 in. / 885.6 x 498.2mm	40.1 x 22.5 in. / 1018.1 x 572.7mm	45.4 x 25.5 in. / 1152 x 648mm	47.6 x 26.8 in. / 1209.6 x 680.4mm	61 x 34.3 in. / 1549 x 871.6mm
CONNECTIVITY					
Input Terminals					
Digital	DisplayPort, HDMI, DVI-D				
Analog	VGA 15-pin D-sub, 5 BNC (RGBHV, DVD/HD, or Video), BNC Composite, S-Video		VGA 15-pin D-sub, 5 BNC (RGBHV, DVD/HD, or Video), RCA Composite, BNC Composite, RCA (Y, Cb/Pb, Cr/Pr) Component, S-Video		
Audio	RCA Audio, Audio Mini-Jack x 2, DisplayPort Audio, HDMI Audio		RCA Audio x 2, Stereo Mini-Jack, DisplayPort Audio, HDMI Audio		
External Control	RS-232C, Ethernet (RJ45), IR Remote, DDC/CI (Standard)				
Output Terminals					
Digital	DisplayPort, DVI-D		NA		
Analog	BNC Composite		5 BNC (RGBHV, DVD/HD, or Video), BNC Composite		
Audio	Audio Mini-Jack, External Speaker Jack x 2		RCA Audio, External Speaker Jack x 2		
External Control	RS-232C, IR Remote				
Audio Amplifier	15W Stereo				
Digital Tuner	P402-AVT	P462-AVT	P521-AVT	P551-AVT	P701-AVT
FEATURES					
Additional Features	Thin bezel (P701-standard bezel), advanced thermal capabilities, sealed professional panel, expansion slot, Ethernet Control and Communication, CableComp+, TileMatrix (10x10), TileComp, programmable lookup tables, Plug and Play (DDC/CI, DDC2B), PIP (remote), POP, 6-axis color adjustment, multi-level programmable zoom, scheduler (w/ RTC), sharpness/softness, off-timer (countdown), screen saver, vacation switch, 10-bit gamma, AutoBright (signal input), Windows Vista-certified, IR, portrait-capable, metal rear cabinet, handles, touch- and protective screen-ready, ambient light sensor, carbon footprint meter, color temperature adjustment (2600-10,000K)				
Speakers	Integrated (10W x 2)		Optional (SP-5220)	Optional (SP-RM1)	
POWER					
Power Requirements	3.5 A@100-120V 1.45 A@220-240V	3.6 A@100-120V 1.5 A@220-240V	4.9 A@100-120V 2.0 A@220-240V	5.3A@100-120V 2.2A@220-240V	9.2 A@100-120V 3.7 A@220-240V
Power Consumption (Typical)	145W	155W	290W	280W	600W
Power Consumption - Standby Mode	< 1W				
PHYSICAL SPECIFICATIONS					
Bezel Width (L/R, T/B)	0.61 in./0.61 in., 0.61 in./0.61 in. ; 15.5mm/15.5mm, 15.5mm/15.5mm	0.65 in./0.65 in., 0.65 in./0.65 in. ; 16.5mm/16.5mm, 16.5mm/16.5mm	0.7 in./0.7 in., 0.7 in./0.7 in. ; 19mm/19mm, 19mm/19mm	0.8 in./0.8 in., 0.8 in./0.8 in. ; 20.3mm/20.3mm, 20.3mm/20.3mm	2.5 in./2.5 in., 2.5 in./2.5 in. ; 62.4mm/62.4mm, 63.4mm/63.4mm
Dimensions (without stand; WxHxD)	36.2 x 21 x 4.1 in. / 919.7 x 532.2 x 103mm	41.6 x 24 x 4.1 in. / 1055.4 x 608.6 x 103mm	47.2 x 27.4 x 5.8 in. / 1200 x 696 x 147.5mm	49.2 x 28.4 x 5.9 in. / 1250 x 721 x 150mm	66.1 x 39.5 x 7.8 in. / 1680 x 1004 x 198mm
Packaging Dimensions (WxHxD)	42 x 26.9 x 10.3 in. / 1066 x 682 x 261mm	47.6 x 30.8 x 10.3 in. / 1210 x 782 x 261mm	58.3 x 34.9 x 13.1 in. / 1481 x 886 x 334mm	60.5 x 37.1 x 13.1 in. / 1537 x 942 x 334mm	78 x 49.6 x 22 in. / 1980 x 1260 x 560mm
Net Weight (without stand)	45.9 lbs. / 20.8 kg	52.5 lbs. / 23.8 kg	83.3 lbs. / 37.8 kg	88.2 lbs. / 40 kg	211.6 lbs. / 96 kg
Gross Weight (with box)	59.1 lbs. / 26.8 kg	67.9 lbs. / 30.8 kg	110.2 lbs. / 50 kg	110.2 lbs. / 50 kg	253.5 lbs. / 115 kg
VESA Hole Configuration	300 x 300mm (4 hole)		400 x 400mm (4 hole)		
ENVIRONMENTAL CONDITIONS					
Operating Temperature	5-40°C / 41-104°F				
Operating Humidity	20-80%				
ACCESSORIES					
Included	Power cord, 15-pin D-sub cable, setup sheet, wireless remote control, batteries, main switch cover, CD-ROM (user manual)				
Optional					
NEC	Speakers (SP-4046PV); Stand (ST-4020/ST-4620); Single Board Computer (NET-SBC-01/02/03)*; External Single Board Computer (TNETPC-ION)*; Internal HD-SDI Card (SB-L007KK); Digital IP Tuner (MPD-DTI); External TV tuner (TVBOX); Wall Mount Kit (WMK-3257); Accessory pack for Wall Mount Kit (MIS513); Intel i5 OPS PC (N8000-8830)*; AMD Fusion OPS PC (SB-02SC-1/2/3/4)*; OPS Adaptor (SB-02AM), Adaptor Kit (AMK-P4046)		Stand (ST-5220), speaker (SP-P552), tilt wall mount kit (WMK-3257), display wall calibrator kit (KT-46UN-CC), SpectraView, color calibration kit (SVII-PRO-KIT), NEC internal DVI daisy chain (SB-L008WU), NEC internal HD/SDI card (SB-L007KK), digital IP tuner (MPD-DTI), internal single board computer (NET-SBC-01/02/03)*, external single board computer (TNETPC-ION)*	Stand (ST-5220), rear-mounted speaker (SP-RM1), tilt wall mount kit (WMK-3257), display wall calibrator kit (KT-46UN-CC), SpectraView, color calibration kit (SVII-PRO-KIT), NEC internal DVI daisy chain (SB-L008WU), NEC internal HD/SDI card (SB-L007KK), digital IP tuner (MPD-DTI), internal single board computer (NET-SBC-01/02/03)*, external single board computer (TNETPC-ION)*	Stand (ST-701), rear-mounted speaker (SP-RM1), display wall calibrator kit (KT-46UN-CC), SpectraView, color calibration kit (SVII-PRO-KIT), NEC internal DVI daisy chain (SB-L008WU), NEC internal HD/SDI card (SB-L007KK), digital IP tuner (MPD-DTI), internal single board computer (NET-SBC-01/02/03)*, external single board computer (TNETPC-ION)*
Third Party	TTUFF single board computer (APE-20HD-NEC; DPE-80HD-NEC), TTUFF media player (DMD-80HD-NEC), Magenta CAT5 receiver (NEC600), and Minicom CAT5 receiver (360': 0VS51010NEC, 1000': 0VS51001NEC)				
WARRANTY/SERVICE					
Limited Warranty	3 years parts and labor, including backlight*				

* Warranty restrictions apply. Contact your representative for details.



CableComp+, NaViSet, SpectraView, TileComp and TileMatrix are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change. 5/11 ver. 7.

©2011 NEC Display Solutions of America, Inc. All rights reserved.

NEC Display Solutions
500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

NEC

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684