



HS3510 Compact All-In-One 10" Touch Screen With Modular Design

KEY FEATURES

- Compact all-in-one terminal with integrated 10" display, printer, MSR
- Less than half the size of a standard POS configuration
- Modular design printer and MSR removable for serviceability
- Intel[®] Celeron[®] J1900, Quad Core, 2M Cache, up to 2.42GHz
- 10" TFT LCD display with bezel-free projected capacitive touch
- Ports: 4 x USB, 4 x Serial (3 x DB9 + 1 x RJ50), 1 x CR which controls 2 devices, 1 x LAN, PS/2 & Parallel

Options:

WiFi, 2D scanner, 2 x 20 VFD customer displays, LED LCD and secondary monitors, fingerprint reader*

Compact All-in-One Solution

Integrated Display with Modular MSR, Printer

About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

The HS3510 is an all-in-one compact POS terminal solution, which has a tiny 6" x 6" base footprint that allows every inch of valuable counter space to be used. The fan-free HS3510 is ideal for small or medium sized retail and hospitality POS, or a self service kiosk. Its innovative modular design greatly enhances ease of maintenance and maximizes terminal uptime.

HS3510's integrated design with modular serviceability address the industry's most common mechanical points of failure – printer and MSR. In the rare event of a mechanical component failure from HS3510's otherwise solid state design, a replacement module can be installed in minutes with the removal of a few screws and cables. It is that simple. This innovative modular printer design greatly enhances ease of maintenance and maximizes terminal uptime.

ProcessorIntel® Celeron® J1900, Quad Core, 2M Cache, up to 2.42GHzMemory4GB DDR3L 1333MHz SO-DIMM (Up to 8GB)Display9.7" LED Backlit LCD Panel (1024 x 768)TouchProjected Capacitive (10 point touch)Communications1 x Gigabit LAN PortStorage128GB Solid State Drive (Hard Drive optional)Passive CoolingYesOperating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x R-50 Serial 1 x VGA PortDisplay Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x GA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBull-In Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer DisplayScanner2D Imager / Scanner Module Upgrade Kit (Integrated)	Specifications	HS3510
Display9.7" LED Backlit LCD Panel (1024 x 768)TouchProjected Capacitive (10 point touch)Communications1 x Gigabit LAN PortStorage128GB Solid State Drive (Hard Drive optional)Passive CoolingYesOperating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RJ-50 Serial 1 x VGA PortDisplay Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x Line OutInternal Expansion1 x Line OutBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 Ibs.Operating Conditions0"C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions2X20 VFD Rear-Mount Customer Display	Processor	Intel [®] Celeron [®] J1900, Quad Core, 2M Cache, up to 2.42GHz
TouchProjected Capacitive (10 point touch)Communications1 x Gigabit LAN PortStorage128GB Solid State Drive (Hard Drive optional)Passive CoolingYesOperating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RI-50 SerialCR PortPort (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCIe slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 Ibs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Memory	4GB DDR3L 1333MHz SO-DIMM (Up to 8GB)
Communications1 x Gigabit LAN PortStorage128GB Solid State Drive (Hard Drive optional)Passive CoolingYesOperating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RJ-50 SerialCR Port1 Port (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x KI-60 ttParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCIe slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Display	9.7" LED Backlit LCD Panel (1024 x 768)
Storage128GB Solid State Drive (Hard Drive optional)Passive CoolingYesOperating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RJ-50 Serial 1 x RJ-50 SerialCR Port1 Port (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x nini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Touch	Projected Capacitive (10 point touch)
Passive CoolingYesOperating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RJ-50 Serial 1 x RJ-50 Serial Dual Independent Open SensorCR Port1 Port (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCIe slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions-20°C-70°C, 10%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Communications	1 x Gigabit LAN Port
Operating SystemsWindows Embedded POS Ready 7 / Windows 7 Professional / Windows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RJ-50 SerialCR Port1 Port (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCIe slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions-20°C-70°C, 10%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Storage	128GB Solid State Drive (Hard Drive optional)
Operating systemsWindows Embedded 8.1 Industry / Windows 10 IoT EnterpriseCOM Ports3 x DB9 Serial 1 x RI-50 SerialCR Port1 Port (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions-20°C-70°C, 10%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Passive Cooling	Yes
1 x RJ-50 SerialCR Port1 Port (Controls 2 Drawers) Dual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Operating Systems	
CR PortDual Independent Open SensorUSB Ports3 x USB 2.0 / 1 x USB 3.0Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	COM Ports	
Display Ports1 x VGA PortParallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	CR Port	
Parallel Port1Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative Humidity Optional Accessories 2X20 VFD Rear-Mount Customer Display	USB Ports	3 x USB 2.0 / 1 x USB 3.0
Audio Port1 x Line OutInternal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Display Ports	1 x VGA Port
Internal Expansion1 x mini-PCle slotBuilt-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityOptional Accessories2X20 VFD Rear-Mount Customer Display	Parallel Port	1
Built-in Printer3", 200 mms/s with auto-cutterMagnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityOptional AccessoriesPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Audio Port	1 x Line Out
Magnetic Stripe ReaderIntegrated 3 Track, Encryption CapableDimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityOptional Accessories2X20 VFD Rear-Mount Customer Display	Internal Expansion	1 x mini-PCle slot
Dimensions (W x D x H)8.8" x 7.3" x 15.2" (6" x 6" base footprint)Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityOptional AccessoriesPD2607UE011EP2X20 VFD Rear-Mount Customer Display	Built-in Printer	3", 200 mms/s with auto-cutter
Weight9.26 lbs.Operating Conditions0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)Storage Conditions-20°C-70°C, 10%-90% Relative HumidityOptional Accessories2X20 VFD Rear-Mount Customer Display	Magnetic Stripe Reader	Integrated 3 Track, Encryption Capable
Operating Conditions 0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD) Storage Conditions -20°C-70°C, 10%-90% Relative Humidity Optional Accessories PD2607UE011EP 2X20 VFD Rear-Mount Customer Display	Dimensions (W x D x H)	8.8" x 7.3" x 15.2" (6" x 6" base footprint)
Storage Conditions -20°C-70°C, 10%-90% Relative Humidity Optional Accessories PD2607UE011EP 2X20 VFD Rear-Mount Customer Display	Weight	9.26 lbs.
Optional Accessories PD2607UE011EP 2X20 VFD Rear-Mount Customer Display	Operating Conditions	0°C-50°C, 20%-90% Relative Humidity (Equipped with SSD)
PD2607UE011EP 2X20 VFD Rear-Mount Customer Display	Storage Conditions	-20°C-70°C, 10%-90% Relative Humidity
	Optional Accessories	
Scanner 2D Imager / Scanner Module Upgrade Kit (Integrated)	PD2607UE011EP	2X20 VFD Rear-Mount Customer Display
	Scanner	2D Imager / Scanner Module Upgrade Kit (Integrated)

Intel® 802.11 a/b/g/n/ac Wireless Module and Antenna Kit

Available Services

Standard and Extended Warranty Extend your depot warranty up to 5 years.

 Advance Exchange
We ship overnight replacement equipment directly to your business.
You return the faulty unit to Posiflex.

• OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process.

- Regional Repair Depots Three regional depots assure fast turn-around time on repairs.
- **Post Warranty Support** Spare parts, in addition to a flat rate repair program, for post warranty needs.
- Installation Services Let our nationwide network of experts stage and install your equipment.
- OEM Design and Integration Our Product Development Team helps design equipment, for custom hardware applications.



With fingerprint reader*



Posiflex Business Machines, Inc. 30689 Huntwood Ave. Hayward, CA 94544 P: 888-968-1668 F: 510-475-0982 sales.department@posiflexusa.com

* Factory installed

Wireless Module

Biometric MSR

** The product information and specifications are subject to change without prior notice.

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













