

TX-3100E Series



POSIFLEX
Your Success is Our Vision



TX-3100E Series

Advanced Fan-Free POS System

Key Features

- ▶ Equipped with Intel Pine View Dual Core D525 1.8 GHz (TX-3100E series) and DDR3 memory
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ Wide range of I/O supports for various applications
- ▶ Compact size and wall mount capability for easy space arrangement
- ▶ Rear cable cover for safety and neat outlook (Except TX-3100S-E)

Specification	TX-3100E / 3100S-E
Processor	Intel Pine View D525 1.8 GHz / 1 M Cache CPU (Dual Core)
System Memory	DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB
Storage Device	2.5" SATA HDD or SSD (Optional)
Power Supply	12V DC power adaptor, 60W
Audio	Buzzer Only
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux
Connectivity	
LAN Port	10 / 100 / 1000 Mb
Serial Port	DB9 x3, RJ-45x1 (Optional RJ45 to DB9 cable) with 5V support on COM2/COM3/COM4 12V support on COM2/COM3
PS/2 Keyboard	Yes
Standard USB Port	4
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD monitor
CR Port	1, control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	270 x 253 x 86 (TX-3100E / TX-3000E) 270 x 200 x 86 (TX-3100S-E / TX-3000S-E)
Weight (N. W. in kg)	2.29
Environment	
Operation Condition	0°C ~ +40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C ~ +50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
SSD	8 GB Minimum
2nd VGA Port	Yes, 2nd VGA port can't coexist with COM4
Wall Mounting Kit	WB-6812
Certifications	

Design and Manufacturing In Taiwan by Posiflex Technology Inc.



Posiflex delivers the fan-free TX-3100E series as advanced POS systems. The TX-3100E series come with modern and technical sensation. Their trim outline strike an impression upon first sight, and the aluminum die casting are adopted to show a glimpse of fashion and also enhance the thermal solution. Inside their compact figure, the TX-3100E series accommodate Dual Core D525 1.8 GHz CPU respectively, 2.5" HDD or SSD and a variety of connectivity like LAN, Serial, PS/2, USB, VGA and CR ports.

The TX-3100E series are flexible for space-sensitive retailers to deploy them.

POSIFLEX Posiflex Technology, Inc.
Headquarters
No.6, Wuquan Rd., Wugu Dist., New Taipei City
248, Taiwan (R.O.C.)
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684