



CL4NX™

SATO, Beyond Expectation


SATO's first truly UNIVERSAL Industrial Label Printer engineered for the most demanding printing applications

Simple-to-Operate



- Full Color Interactive LCD
- Videos that Offer Valuable Information on the Printer Operation
- Intuitive Menu Navigation
- Tool-less Maintenance

Plug-and-Play



- LTDS (Label Tension Damper System)
- Flexible Media Support - Use Wound In or Wound Out Media
- High Energy Mode - Prints on a Wide Variety of Stock Types

All-in-One



- Multiple Interfaces - Auto Switching
- Competitive Emulations On-board
- Multi-Language Support

GENERAL SPECIFICATIONS / CL4NX™

PRINTER MODEL

CL4NX

PRINT SPECIFICATIONS

Print Method

Direct Thermal or Thermal Transfer

Print Resolution

203 dpi (8 dots/mm) 305 dpi (12 dots/mm) 609 dpi (24 dots/mm)

Print Speed

10 ips (254.0 mm/sec) 8 ips (203.2 mm/sec) 6 ips (152.4 mm/sec)

Print Mode

Continuous, Tear-off, Cutter, Dispense

Print Area

Maximum Width

4.1" (104.0 mm)

Maximum Length (Continuous mode)

98.43" (2500.0 mm) 59.06" (1500.0 mm) 15.75" (400.0 mm)

MEDIA SPECIFICATIONS

Sensor Type

Adjustable Transmissive Sensor for Gap, Adjustable Reflective Sensor for Black Mark, Paper End, Ribbon Near-End/End

Media Type

Roll (Continuous, Die-cut), Fan-fold, Tag, Ticket

Media

Width

0.87" (22.0 mm) - 5.04" (128.0 mm)

Thickness (label & liner)

0.002" (0.060 mm) - 0.011" (0.268 mm)

Roll Diameter

Maximum 8" (203.2 mm) on 3" (76.0 mm) ID Core
Optional 10" OD

Wind

Face-in / Face-out, No Setting Change Required

Ribbon

Width

1.55" (39.5 mm) - 5.04" (128.0 mm)

Length

1,968.5 ft (600 m) on 1" (25.4 mm) ID Core

Roll Diameter

Maximum 3.54" (90.0 mm)

Wind

Face-in / Face-out, No Setting Change Required

SATO Genuine Consumables

For Maximum Print Quality and Optimum Use, SATO Recommends The Use of SATO Genuine Consumables

MEMORY & PROCESSING SPECIFICATIONS

Dual CPU

CPU1: 2GB ROM, 256MB RAM
CPU2: 4MB ROM, 64 MB RAM

USER FRIENDLY SUPPORT TOOLS

Large Status LED

Blue/Red

Alarm Sound

Beep (3 volume setting)

Self Diagnosis

Head Check, Cutter-Cover Open, Stand-by mode, Auto-Calibration

Display Panel

3.5" Full Color LCD

Tool-less Maintenance

Print Head Replacement and Adjustment, Platen Replacement

Multi National Language Support

47 Languages Scalable Fonts for Print
31 Languages for LCD Menu

Operation Video

Multiple Instructional Videos On-board (e.g. Error Resolution, Media Loading, Parts Replacement and Cleaning)

Emulation

Auto detect - SBPL®, SZPL®, SDPL®, SIPL® or STCL®

Remote Maintenance

SNMP Ver. 3, HTTPS

COMMUNICATION INTERFACES SPECIFICATIONS

Standard

USB 2.0 (Type A, Type B), Ethernet (IPv4/IPv6) on Rear Panel
USB 2.0 (Type A) on Front Panel
RS-232C, IEEE1284, EXT on Standard Interface Board
Bluetooth® Ver.3.0 (only for NA & EU)

Optional Wireless LAN Kit (Internal)

Wi-Fi® Certified, CCX (Cisco®) version 4 Certified, IEEE 802.11 a/b/g/n, Dual Band (2.4 GHz, 5 GHz)

OPTIONS

Cutter, Dispenser with Internal Liner Re-winder, Real-Time Clock, UHF RFID (ISO18000-6 Type C), W-LAN kit

FONT SPECIFICATIONS

Internal Fonts

Bitmap

U, S, M, WB, WL, XS, XU, XM, XB, XL, OCR-A, OCR-B, Chinese (GB18030, Big5), Korean (KSX1001)

Scalable

CG Times, CG Triumvirate™, 13 SATO Fonts - Unicode (47 Languages Supported)

BARCODE SYMBOLOGIES SPECIFICATIONS

Barcodes

Linear

Code 39, Code 93, Code 128, CODABAR (NW7), EAN8/13, GS1-Databar™, GS1-128 (UCC/EAN128), Interleaved 2/5, Industrial 2/5, JAN8/13, Matrix 2/5, MS1, Bookland, Postnet™, UPC-A/E

2D Symlogies

PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, QR Code, Micro QR Code and Composite Symlogies

User Downloadable Fonts, Graphics or Format

Maximum 100MB

OPERATING & ENVIRONMENT CHARACTERISTICS

Electrical Requirements

Universal Auto-ranging Power Supply, 100-240VAC +/- 10%, 50/60Hz
Energy Star - Compliant

Standards & Certification

EN60950-1, UL60950-1/CSA C22.2 No.60950-1, C-Tick, CCC, KC, S-Mark

Agency Approvals

cMETus, CE marking, FCC, NEMKO GS, ICES-003, NMB-003, KC, CCC, S-mark,

Environment

Operating

32 to 104°F (0 to 40°C), 30 - 80% RH, Non-Condensing

Storage

-4 to 140°F (-20 to 60°C), 30 - 90% RH, Non-Condensing

PHYSICAL CHARACTERISTICS

Dimensions

Width: 10.67" (271.0 mm)
Depth: 17.99" (457.0 mm)
Height: 12.63" (321.0 mm)

Construction

Die-cast Aluminum (Base, Frame, Front Cover, Ribbon Spindle, Print Head Mechanism)

Side-cover

Bi-fold for Space Saving with Large Clear Window

Mounting Chassis

3 Fixtures for Flat or Incline Setting

Weight

33.0 lbs. (15.1kg)

SATO AMERICA, INC.

CORPORATE

10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
Fax: (704) 644-1662
satosales@satoamerica.com

LABEL MANUFACTURING, SERVICE & SALES

NORTH AMERICA BRAZIL ARGENTINA
Illinois Sao Paulo Buenos Aires
Florida
New Jersey
North Carolina

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684