

# **Bluetooth** Cordless Hand Scanner (CHS) Series 7

### **1D MODELS**

### Small, Lightweight and Easy to Connect

Increase productivity and reduce data errors in mobile business applications with the Socket *Bluetooth* Cordless Hand Scanner (CHS), a wireless barcode reader for smartphones and tablets that's small, portable and provides fast, industrial-class scanning performance.















- Designed for Mobility Small, light, and portable with 19-hour battery life
- Comfortable Ergonomic for comfortable use over extended periods
- Easy to Connect Simply scan a barcode on the screen to quickly pair devices<sup>1</sup>



### **General Purpose Scanner - CHS 7Ci**

#1 Choice for Tablet-Based Retail Point of Sale

Smallest, lightest and most affordable CHS model, available in bright colors to enhance corporate branding in retail or customer service, enable personalization, and make scanner easy to find





7DiRx

### **Durable Scanners - CHS 7Di and 7DiRx**For More Rugged Environments

Ideal for field sales and field service, the CHS 7Di is durable to withstand multiple drops to concrete, with a protective rubber bumper and rubber sealings. The CHS 7DiRx is a white antimicrobial version for healthcare.



7Mi

7Di



### Laser Scanners - CHS 7Mi and 7Pi

For Special Lighting Conditions or Barcode Requirements

Featuring a Class 2 laser, the CHS 7Mi and 7Pi work well in bright sunlight, in low light, as well as with barcodes that are small, tightly spaced, on shiny surfaces or behind plastic / glass. The CHS 7Pi is a durable version that withstands multiple drops to concrete.

#### HARDWARE FEATURES

- Easily connect to Bluetooth enabled smartphones, tablets, PDAs, notebooks and desktop computers:
- Apple iOS and Mac OS
- Android OS
- Windows 8, RT, 7, Vista, XP
- Windows Embedded Handheld (Windows Mobile)
- BlackBerry OS, QNX, Linux
- Enjoy wireless freedom with a long-range *Bluetooth* connection up to 330 ft (100 m)
- Battery Friendly\* technology enables extensive
   19-hour battery life on a single charge
- Scanner automatically connects to the last device or computer it paired and connected to
- Wear around neck or attach to belt with included lanyard / belt clip for convenient access to scanner
- LED and beeps indicate good scan, connection, and power status
- Vibrate mode indicates good scans, ideal for noisy environments where beeps are hard to hear or applications where beeps must be disabled
- Supports both Bluetooth HID and SPP connections for easy setup with no software installation or advanced scanner control and SDK support<sup>2</sup>

#### **SPECIAL FEATURES FOR APPLE IOS**

- Certified by Apple for iPad, iPad mini, iPhone, and iPod touch
- Quickly access Apple iOS on-screen keyboard by pressing a scanner button
- Authentication chip enables two-way communications with Apple devices running a compatible app developed with SocketScan 10 SDK. View apps at: <a href="http://www.socketmobile.com/appstore">http://www.socketmobile.com/appstore</a>
- App to modify beep, LED, vibrate, and other settings

### **SOFTWARE - ANDROID, WINDOWS, BLACKBERRY**

- SocketScan™ 10 keyboard wedge enters scanned data into any app, no custom programming needed
- Socket EZ Pair automates *Bluetooth* setup just scan the barcode on the screen to connect<sup>1</sup>
- Suffix support automatically add a carriage return or tab after each scan of data
- Data editing reformat, extract or manipulate data
- Scanner configuration modify beep, LED, vibrate, and symbology settings. View scanner's battery level

### **SOFTWARE DEVELOPMENT KIT (SDK)**

 SocketScan 10 SDK available to members of Socket Mobile Developer Program (\$19.95/year) http://developer.socketmobile.com

<sup>1</sup>On-screen barcode not compatible with laser scanners. Requires installation of SocketScan 10 software for Android/ BlackBerry/Windows or iOS app developed with SDK.

<sup>2</sup>Some smartphones/devices do not support both HID and SPP

CHS Model	7Ci	7Di	7DiRx	7Mi	7Pi	
Scanner SKU #	Gray: CX2870-1409 Yellow: CX2883-1480 Red: CX2885-1484 Blue: CX2887-1486	CX2877-1472	CX2879-1474	CX2872-1411	CX2874-1413	
Dimensions	5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)	5.2 x 1.77 x 1.49 in. (132 x 45.1 x 37.9 mm)		5.07 x 1.57 x 1.36 in. (129 x 40.1 x 34.6 mm)	5.2 x 1.77 x 1.49 in. (132 x 45.1 x 37.9 mm)	
Total Mass	1.6 oz (45 g)	approx. 2.4 oz (68 g)		1.8 oz (51 g)	approx. 2.4 oz (68 g)	
Durable with Protective Rubber Bumper and Rubber Sealings		✓	✓		✓	
Drop Specification	Multiple 3.3 ft (1 m) drops to vinyl covered concrete	Multiple 6.6 ft (2 m) drops to concrete		Multiple 3.3 ft (1 m) drops to vinyl covered concrete	Multiple 6.6 ft (2 m) drops to concrete	
Antimicrobial Rating (JIS Z2801:2000 Test) Biosafe HM4100, EPA# 83019-1	N/A	N/A	2.49 on MRSA 6.07 if cleaned with Sani-Cloth Plus cloth wipes	N/A	N/A	
Temperature, <sup>1</sup> Relative Humidity	Operating Temperature: +32 to +122°F (0 to +50°C) Storage Temperature: -22 to +158°F (-30 to +70°C) Relative Humidity: 5% to 95% non-condensing					
Ambient Light	Sunlight: 0 - 110,000 lux			Sunlight: 100,000 lux Artific	ial light: 4,844 lux	
Battery Type	Two AAA NiMH rechargeable batteries					
Battery Life	19 hours or 11,000 scans <sup>2</sup>			19 hours or 15,000 scans <sup>2</sup>		
Barcode Scanner Performance	15 110413 61 117000 354113			13 110 013 01 13/000 300113		
Scanner Type	Imager (1D)			Class 2 laser (1D)		
Scans Barcodes on Device Screens		<b>√</b>	<b></b> ✓	Class 2 laser (1D)		
	V	V	V			
Scans VIN through Windshield				✓	✓	
Vibrate Mode for Good Scans	✓	✓	✓	✓	✓	
Symbologies Decoded	Same as 7Mi/Pi plus: UPC/EAN/JAN supplemental redundancy, Coupon Report, ISSN EAN, Inverse 1D, ISBT concatenations, Matrix 2 of 5  GS1 DataBar (RSS), GS1-128 (UCC-128/EAN-128), Interleaved 2 of 5 (ITF-14), MSI, Plessey, UPC/EAN					
Scan Repetition Rate	5 scans/sec			5 scans/sec bi-directional		
Optical Resolution	5 mil minimum			0.004 inch (0.102 mm) min./barcode element width		
Print Contrast	Minimum 20%			Minimum 25% MRD at 650 nm		
Scan Angle	53.3° ± 3°			Wide (default): 47° ±3° Narrow: 35° ±3°		
Decode Distance <sup>3</sup>	5.7 to 50.8 cm (2.25 to 20 in.) 3.8 to 114+ cm (1.5 to 45+ inches)					
Bluetooth Profile Support	Human Interface Device (HID) and Serial Port Profile (SPP) Some OS versions or smartphone/tablet models support only one profile.					
Bluetooth Version	Bluetooth 2.1 + EDR (Enhanced Data Rates) with 56 bit data encryption, Bluetooth QD ID B0164000					
Radio Range	Class 1 Bluetooth: Up to 100 m (330 ft), depending on environment					
OS Support	Please use online compatibility checker for specific device models, OS versions, etc. <a href="http://www.socketmobile.com/compatibilitychecker/">http://www.socketmobile.com/compatibilitychecker/</a>					
Apple iOS, Mac OS	<b>✓</b>	✓	✓	✓	✓	
Android OS	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	
BlackBerry OS	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>	
• Windows 8, RT, 7, Vista, XP	<b>√</b>	<b>√</b>	<b>√</b>	✓	<b>√</b>	
Windows Embedded Handheld, Mobile, CE	✓	✓	✓	✓	<b>√</b>	
SocketScan™ 10 Software	Keyboard wedge software featuring Socket EZ Pair for Android, BlackBerry, Windows. Scanner Settings configuration utility also included.					
SocketScan 10 SDK	For Apple iOS, Android, BlackBerry, Windows. Available to members of Socket Mobile Developer Program (\$19.95/year) <a href="http://developer.socketmobile.com">http://developer.socketmobile.com</a>					
Included Items	CHS barcode scanner, AAA rechargeable batteries (2), USB AC charger kit, lanyard/belt clip with retractable tether, software					
Warranty	Scanner: One year Accessories: 90 days					
SocketCare Extended Warranty	Sold separately. SocketCare Pl	Sold separately. SocketCare Plus 2 Year - SKU# SC1804-1349 SocketCare Plus 3 Year - SKU# SC1805-1350 <a href="http://www.socketcare.com/">http://www.socketcare.com/</a>				
Regulatory Compliance						
Electrical Safety	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2					
Environmental	RoHS					
EMI / RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC					
Laser / LED Safety	IEC 60825-1, EN 60825-1					

<sup>&</sup>lt;sup>1</sup>Temperature ranges may vary with battery shelf life. <sup>2</sup>Battery life may vary with vibrate settings and work environment. <sup>3</sup>Depends on symbol size, symbology, label media, W-N ratio, scan angle.



sales@socketmobile.com

Worldwide +1-510-933-3000 Toll-Free

+1-800-552-3300 (USA/Canada)

**EMEA** +32 479 49 64 54 +44 7787 112109 UK Asia Pacific +1 510 933 3122 Latin America +1 510 933 3153

# **Legacy Technology Services**

## We Rent & Sell All Types Of Barcode Equipment

# Call now to talk to an expert

866-271-9891

### About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

### **Latest Hardware from top manufacturers**

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

### **Discontinued product sourcing**

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

### **Trade-in and Disposal services**

- That old equipment laying around your facility may still have some value.
   Legacy routinely purchases equipment from our clients around the globe.
  - · Data destruction
  - · Hardware disposal
  - Auditing services

### Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.









Toll Free: 866-271-9891

Fax: 888-522-4684



Smarter

www.LegacyGlobal.com
Some brands we carry



















