





TX200 SERIES – Desktop Thermal Transfer Bar Code Printer HIGH PERFORMANCE FOR A NEW GENERATION



KEY FEATURES

- Up to 203 mm (8") per sec. print speed
- 128 MB Flash memory and 128 MB SDRAM memory
- microSD Flash memory expansion up to 32 GB
- User-friendly clamshell design
- Serial, internal Ethernet USB 2.0 & USB host interfaces standard
- 3.5" color TFT Display (Standard for TX600, Optional for TX200 & TX300)
- Label capacity up to 127 mm (5") OD
- Ribbon capacity up to 300 m (984')
- TSPL-EZTM firmware for plug-n-play ease
- Optional peel-off module, cutter module, external Bluetooth module, external 802.11 b/g/n wireless module, stand-alone keyboard

APPLICATIONS

- Business/Office
- Product Marking
- Compliance Labeling
- Asset Tracking
- Document Management
- Shelf-Labeling
- Shipping/Receiving
- Specimen Labeling
- Inventory Control
- Patient Tracking

TX200 SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TX200	TX300	TX600	1 the contract of the contract	
solution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)	24 dots/mm (600 DPI)	and the second	
inting method		Thermal Transfer & Direct	Thermal		
ax. print speed	203 mm (8")/second	152 mm (6″)/second	102 mm (4″)/second		
ax. print width	108 mm (4.25")	106 mm (4.17")	106 mm (4.17")		
lax. print length	25,400 mm (1,000")	11,430 mm (450")	2,540 mm (100")		
nclosure	00/ 000 400	Clamshell with double-wall			
hysical dimension	226 mm (W) x 198 mm (H) x 332 mm (D) 8.90" (W) x 7.80" (H) x 13.07" (D) 226 mm (W) x 200 mm (H) x 332 mm (D) 8.90" (W) x 7.87" (H) x 13.07" (D)		Transformer		
/eight	3.75 kg		4.08 kg (8.99 lbs)		
bel roll capacity	127 mm (5") OD			Tri-	
bbon bbon width	300 m long, max. OD 67 mm, 1" core (ink coated outside) 40 mm ~ 110 mm (1.6" ~ 4.3")			Months : DOOD Services	
rocessor	32-bit RISC CPU				
10003501	128 MB Flash memory				
1emory nterface	 128 MB SDRAM microSD card reader for Flash memory expansion, up to 32 GB USB 2.0 RS-232 Internal Ethernet, 10/100 Mbps USB Host 			TSC The Smarter Choice	
	 Centronics (factory option) External Bluethooth (user op External 802.11 b/g/n wirele 			CELEBRATING	
	 1 power switch 		• 1 power switch	CORPORATE HEADQUARTERS	
Operation switch, button,	 1 feed/pause button 		 6 operation buttons 	TSC Auto ID Technology Co., Ltd.	
LÉD/LCD	 LED panel with 8 big icons 		(menu, feed/pause, up, down, left, right) • 3.5" color TFT display, 320 x 240 pixel	Tel: +886 2 2218 6789 E-mail: apac_sales@tscprinters.com	
ower	External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz		External universal switching power supply • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 5.41A, 130W	LI ZE PLANT TSC Auto ID Technology Co., Ltd.	
	 Output: DC 24V, 3.75A, 90W Transmissive gap sensor 		Output: DC 24V, 5.4TA, 150W Transmissive gap sensor	Tel: +886 3 990 6677	
	 Black mark reflective sensor 	(position adjustable)	 Black mark reflective sensor (position) 	E-mail: apac_sales@tscprinters.com	
ensors	 Ribbon encode sensor 	1	adjustable)	AMERICAS	
			Ribbon end sensor	TSC Auto ID Technology America Inc	
			Ribbon encode sensorHead open sensor	Corporate Office Tel: +1 909 612 9606	
eal time clock	Factory Option		Standard	E-mail: americas_sales@tscprinters.com	
	8 alpha-numeric bitmap fonts			• Orlando Office	
ternal fonts	 Monotype Image[®] true type font engine with one CG Triumvirate Bold Condensed scalable font 			Tel: +1 407 704 8918	
ar code	 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subsets A.B.C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS 2D bar code TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, Code 1, Der Code 			E-mail: americas_sales@tscprinters.com CANADA TSC Auto ID Technology America Inc Tel: +1 909 612 9606 E-mail: americas_sales@tscprinters.com MEXICO	
ont and barcode rotation	GS1 DataBar (RSS barcode) 0, 90, 180, 270 degree			TSC Mexico Representative Office	
rinter language	TSPL-EZ™ (Compatible to EPL, ZPL II)			Tel: +52 (33) 3836 6682	
ledia type	Continuous, die-cut, black mark, fan-fold, notch (outside wound)			E-mail: americas_sales@tscprinters.com	
ledia width	19 ~112 mm (0.75" ~ 4.4")			BRAZIL	
ledia thickness	0.055 ~ 0.254 mm (2.17 ~ 10 mil)			TSC Brazil Representative Office Tel: +55 (11) 9597 8098	
ledia core diameter	25.4 ~ 38.1 mm (1" ~ 1.5")			E-mail: americas_sales@tscprinters.com	
abel length	3 ~ 25,400 mm (0.1" ~ 1,000") 3 ~ 11,430 mm (0.1" ~ 450") 3 ~ 2,540 mm (0.1" ~ 100")				
nvironment condition	Operation: $5 \sim 40^{\circ}$ C, $25 \sim 85\%$ non-condensing				
	Storage: -40 ~ 60°C, 10 ~ 90% non-condensing			 TSC Auto ID Technology EMEA GmbH Tel: +49 (0) 8106 37979 00 	
afety regulation	FCC	Class B, CE Class B, RCM, UL, cl		E-mail: emea_sales@tscprinters.com	
nvironmental concern	- 14/2 L L L L L L	Comply with RoHS, W	/EEE	RUSSIA	
	 Windows labeling software Quick start quide 	U disk		 TSC Auto ID Technology EMEA GmbH 	
ccessories	• USB cable			Tel: +7 915 422 8889	
	 Power cord 			E-mail: emea_sales@tscprinters.com	
	External universal switching	power supply		MIDDLE EAST	
Limited warranty	 Printer: 2 years Print head: 25 km (1 million inches) or 12 months which comes first 			TSC Auto ID Technology ME Ltd, FZE	
	Platen: 50 km (2 million inches) or 12 months which comes first			Tel: +971 4 2533 069 E-mail: emea_sales@tscprinters.com	
	 Centronics parallel interface 		Centronics parallel interface	•	
actory options	 Real time clock 			ASIA PACIFIC	
actory options	• 3.5" color TFT display			TSC Auto ID Technology Co., Ltd.	
	Ribbon end sensor			Tel: +886 2 2218 6789 E-mail: apac_sales@tscprinters.com	
Dealer options	 Peel-off module Guillotine cutter (full cut) 			- mail apac_suics@cseprinters.com	
	 Guillotine cutter (full cut) Bluetooth module (serial int 	erface)		CHINA	
	 Bluetooth module (serial int 802.11 b/g/n wireless modu 	e (serial interface)		Tianjin TSC Auto ID Technology Co., Lto	
Jser options	 KP-200 Plus keyboard displate 	y unit		Tel: +86 22 5981 6661 E-mail: apac_sales@tscprinters.com	
		smart keyboard		= _ man apac_sales@cseprinters.com	

TSC® is a trademark of TSC Auto ID Technology Co., Ltd. TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company. © 2014 TSC Auto ID Technology Co., Ltd. Product models and Specifications are subject to change without notice. Contact your TSC sales representative for specific information.

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













