TOUCH DYNAMIC

Breeze 185 All-In-One

A sleek All-In-One for Big Tasks

Highlights

- Rackable Motherboard
- Up to 6 USB Ports
- Up to 16GB Ram
- Fanless CPU's up to Intel i3

Intel CPU Choices

- Atom Dual Core D2550 1.86G Fanless
- Celeron Dual Core 1037U 1.8G Fanless
- i3-3217U Dual Core 1.8G Fanless

Widescreen Touch Display Options

- 18.5" LED Bezel-less Resistive Touch
- 18.5" LED Bezel-less Projected Capacitive Touch (PCAP)

Peripheral Options

- Integrated 3 Track MSR
- Integrated 3 Track MSR Encrypted
- Integrated Biometric Reader
- Integrated Internal Wireless LAN 802.11 a/b/g/n
- Integrated Customer Display's 2x20 VFD, 8", 12" or 15" Rear LCD
- Up to 2 additional Video Ports
- Integrated Web Camera
- Universal Printer Base with Integrated Thermal Printer

The Breeze 185 All-In-One is an advanced next generation design. The Breeze 185 boasts a 18.5" LED LCD with either bezel-less resistive touch or projected capacitive touch. The Breeze 185 boasts CPU's up to Intel i3-1.8 with a fanless cooling solution. The Breeze 185 leverages Touch Dynamic's legendary rackable motherboard design found in the Breeze and Breeze *Performance* All-In-One making the Breeze 185 All-In-One field upgradeable and easy to service.



Breeze 185 All-In-One

TOUCH DYNAMIC



	Breeze 185 All-In-	One
CPU	Intel Atom D2550 Dual Core 1.86Ghz, L2 Cache 1MB	Intel Ivy Bridge Celeron 1037u Dual Core 1.8Ghz Intel Smart Cache 2MB i3-3217u Dual Core 1.8Ghz Intel Smart Cache 3MB
Chipset	Intel NM10 express chipset	Intel HM76 express chipset
System Memory	2x DDR3 So-DIMM up to 4GB, 1066Mhz	2xDDR3 So-DIMM up to 16GB, 1333/1600Mhz
Graphics	Intel GMA 3650 640Mhz, DX9	Intel HD Graphics 4000, 350-1350Mhz,DX11
Cooling type	Fanless	Fanless
32/64 bit support	32Bit OS support	32 and 64Bit OS support
	Display	
Screen size	18.5"	18.5"
Aspect Ratio	16:9	16:9
Native Screen Resolution	1366x768 (widescreen)	1366x768 (widescreen)
LCD backlight type	LED	LED
LCD Brightness	250cd/m2	250cd/m2
Touch Glass	True Flat Resistive or Projected Capacitive	True Flat Resistive or Projected Capacitive
	Storage	
Hard Drive	2 x 2.5" Sata HDD	2 x 2.5" Sata HDD
Flash Memory	SATA SSD (Option)	SATA SSD (Option)
Hashiweniory		SATA 350 (Option)
	Expansion	
Mini-PCI express slot	1	1
	External I/O	
USB	4 (USB2.0)	6 (4xUSB2.0, 2xUSB3.0)
Serial Ports	4 x RJ45 (COM2,3,4 Power option 5V/12V)	4 x RJ45 (COM2,3,4 Power option 5V/12V)
Parallel Port	1 (DB25 Female)	1 (DB25 Female)
PS/2 Keyboard port	1	1
Network	Gigabit LAN	Gigabit LAN, 2nd LAN available as an option
Audio	3.5mm jack line-out and 3.5 jack line-in (MIC)	3.5mm jack line-out and 3.5 jack line-in (MIC-option)
2nd VGA	1x DB15 (power option available)	1x DB15 (power option available)
3rd VGA	Not Available	1x DVI-D (option)
Cash Drawer Port	1 x (12V/24V)	1 x (12V/24V)
DC Jack	1 x DC 19V	1 x DC 19V
Power Button	1	1
Wireless Antenna	1 (option)	1 (option)
	Outhered Device	
MCD	Optional Peripher	
MSR Fire en	IDTech ISO 3-Track USB MSR	IDTech ISO 3-Track USB MSR
Fingerprint Reader	Digital Persona U.R.U.	Digital Persona U.R.U.
Wireless LAN	miniPCI-express Wireless lan module 802.11 a/b/g/n	miniPCI-express Wireless Ian module 802.11 a/b/g/n
2nd LAN	Not available	available via mPCIe expansion
Front Camera	2MP with TrueFlat P-CAP	2MP with TrueFlat P-CAP
Scanner	2D Barcode scanner	2D Barcode scanner
Customer Display	2x20 Display or 8", 12", 15" Rear LCD Secured with 2 screws	2x20 Display or 8", 12", 15" Rear LCD Secured with 2 screws
Cable Manager	Secured with 2 screws	Secured with 2 screws
	Audio	
Internal Speaker	(2) Internal 3W Speakers	(2) Internal 3W Speakers
	Power	
Power Adapter	External 90W 19V 3.4A DIN connector	External 90W 19V 3.4A DIN connector
	Certificate	
EMC & Safety	FCC Class A, CE, LVD	FCC Class A, CE, LVD
	Environment	
Operating Temperature	32°F ~ 95°F	32°F ~ 95°F
Storage Temperature	-4°F ~ 140°F	-4°F ~ 140°F
Operating Humidity	20% ~ 85% RH non condensing	20% ~ 85% RH non condensing
Storage Humidity	20% ~ 85% RH non condensing	20% ~ 85% RH non condensing
Dimension (no base)	18.2x2.4x11.2 inches	18.2x2.4x11.2 inches
	18.2x2.4x11.2 incres 12 lbs	18.2x2.4x11.2 inches 12 lbs
Weight Stand	With built-in power supply (optional)	12 lbs With built-in power supply (optional)
Mounting	100 x 100 mm, 75 x 75 mm VESA Standard	100 x 100 mm, 75 x 75 mm VESA Standard
woulding	100 x 100 mm, / 5 x / 5 mm vesA stanuaru	
OS Support	Windows XP, POSReady09, Windows7, POSReady7	Windows XP, POSReady09, Windows7, POSReady7, Windows 8, Windows 8 Embedded Industry Retail



Microsoft GOLD CERTIFIED
Partner



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













