



MS916

Wireless (BT) Pocket Laser Scanner

The new MS916 Wireless Pocket Laser Scanner is part of Unitech's latest generation of advanced handheld barcode readers. A wireless device, this pocket-sized scanner offers several outstanding features.

High Precision

The MS916 features a high-performance laser engine that gives it excellent scanning performance—up to 104 scans per second. The result is the ability to scan, capture and transmit even lower-quality barcodes at high resolution. Equipped with 650 nm visible laser diode, the MS916 can read and capture 1D barcode data—including GS1 data barcodes—at up to 4 mil resolution. Designed specifically for mobile users and business professionals, the MS916 is a lightweight stylish design that slips easily into the average-sized pocket. Measuring just 36.9 x 95.9 x 21.1mm, it offers users a high degree of portability and versatility.

Durability

IP42-rated, the solidly constructed MS916 has been built to withstand mechanical shock. It has been shown to pass the rigorous 1.5 meter drop test onto hard concrete, with the scanner's functionality unaffected by the impact. Ruggedly designed, field-tested, durable, and reliable, it will work in temperatures ranging anywhere from 50°C all the way down to 0°C.

Simplicity of Use

The MS916 offers mobile workers a user-friendly, three-button operation that is very easy to use, requiring no special training. The bright, easy-to-read 1-inch OLED display gives feedback of the scanned information to reduce errors. It supports real-time data transmission, and the 128 x 64 resolution display makes it easy for the user to configure the scanner. Through its wireless technology, the MS916 connects quickly and easily to virtually any laptop, tablet, or smart phone host—Windows, Android or Apple iOS. It can operate for distance up to 30-feet in open space.

Adding to its versatility, the MS916 also allows you to charge its built-in lithium-ion battery through any standard USB port. A 1-slot or 5-slot charging cradle is an optional accessory. The battery is fully charged within three hours. The unit comes standard with a strap and a micro USB-to-USB cable.

Additionally, the MS916 has a flash memory storage capacity of 2MB (the equivalent of over 100,000 scans), making data loss extremely unlikely, even when it is out of range of the wireless signal. This allows mobile users to complete long tasks without interruption. At the rate of one scan every five seconds, the battery will last 8 hours on a single charge.

Versatility

The MS916 series has a wide range of potential applications:

- Retail and government workers can use it for access control, logistics, ticket and gaming applications, and other field service activities
- Pharmacy and medical store staff can employ it for medication inventory and warehousing
- It can be used for account management or as a personal identification device
- Courier services can employ it for proof of delivery functions

The bottom line: Wherever the MS916 is employed, it is bound to make data transmission smoother and more efficient.

Features

- Easy-to-use, user-friendly design with high-performance laser engine
- Bright, easy-to-read 1-inch OLED display with 128 x 64 resolution
- Windows, Android and Apple compatible
- 2MB flash ROM memory
- Rugged design that meets the 1.5 meter drop threshold; IP42-rated
- Bluetooth V2.1+EDR, Class 2, & HID/SPP support

Wireless(BT) Pocket Laser Scanner



System

Display	1" OLED, 128 x 64
OS	Proprietary, Connect to host with Windows, Android and iOS
Memory	64 Kbytes SRAM / 2MB Flash ROM
Key	3 keys: Page up, Page down, Scan with power on/off feature

Optical & Performance

Receiving Device	Laser Engine
Light Source	650 nm visible laser diode
Max. Resolution	4mil
Scan Rate	104 scans/second
Skew Angle	47±3 degrees
Pitch Angle	35±3 degrees
Printing Contrast Scale	minimum 25%
Depth of Field (DOF PCS=80%)	Symbology Density Near Far
	Code 39, 4 mils 2.5 cm 13.97 cm
	Code 39, 5 mils 3.18 cm 20.32 cm
	Code 39, 7.5 mils 3.81 cm 33.02 cm
	Code 39, 10 mils 3.81 cm 45.72 cm
	Code 39, 15 mils 3.81 cm 71.72 cm
	Code 39, 20 mils 4.45 cm 83.82 cm
	Code 39, 40 mils x 91.44 cm
	Code 39, 55 mils x 114.3 cm
	UPC, 13 mils 3.81 cm 60.96 cm

Regulation Approvals

CE, FCC, BSMI, VCCI

Accessories

Whist Strap, Micro USB to USB cable
1 & 5 Slot Charging cradle (optional)



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

Unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> info@mideast.ute.com

Functionality

Symbologies

1D

Code 39, Full ASCII Code39, Interleave 2 of 5, UPC A/E/E1, MSI, Codabar, Code 11, EAN8/13, Code 93, Code 128, EAN128, Code32, GS1 databar Code, Bookland EAN, Discreate 2 of 5, Chinese 2 of 5, ISBT 128, UCC Coupon Extended Code, Bookland 128

Operation Mode

Trigger mode, Pulse mode, Flash mode, Continuous Mode, Buffer mode

Data Formatting

Prefix, Suffix, Code ID, Reformatting Date

Environmental

ESD Protection

Functional after 8K Contact and 12K Air

Mechanical Shock

1.5m onto concrete (scanner only)

IP Rate

IP42

Operating Temperature

0°C to 50°C

Storage Temperature

-30°C to 70°C

Relative Humidity

95% non-condensing

Electrical

Operation Voltage

DC 3V to 5V

Current Consumption

Operation mode: <125mAh, Standby mode: < 39mAh

Battery Type

Rechargeable Li-ion battery

Battery Capacity

680 mAh

Battery Charging time

Fully charged in about 3 hours

Operating Time

8 hours at condition of 1 scan/5 sec

Communication

Radio Frequency

Bluetooth V2.1+EDR, Class 2

Protocol

Wireless SPP & HID profiles

Range

Up to 30 Feet (Open space)

Host Interface supported

USB

Mechanical

Scanner Dimension

36.9mm x 95.9mm x 21.1mm

Scanner Weight

63g

Switch life

10 million times

Unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

Unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> info@cn.ute.com
Taipei <http://tw.ute.com> info@tw.ute.com



Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGIC™

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.,
160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891
Fax: 888-522-4684