

### 10.4" Panel Mount LCD

artistry in technolog





# Speakers Included!

- Vesa Mount
- Base OPTIONAL

#### **REAR VIEW**



#### **SIDE VIEW**



### **TOUCH PART NUMBERS**

Resistive USB Touch		
Resistive Serial Touch		
Capacitive USB Touch		
ACCESSORIES		
Adjustable Base		
Adjustable Black Polemount		
8 Kg Wall Mount Bracket		

Visit us: **www.unytouch.ca** sales@unytouch.ca

### APPLICATIONS:

- Industrial
- Gaming
- Custom or OEM Applications
- Retail

### MAIN SPECIFICATIONS U14-OC104-B

PANEL   Color active matrix TFT (Thin-Film-Transistor) LCD Panel		
Pixel Arrangement   RGB vertical stripe   Glass Surface   Anti-Glare coating   Pixel Number   800(H) x 600(V)   Pixel Pitich   0.264(H) mm x 0.264(V) mm   Display Size   10.4" viewable diagonal area   Active Area   211.2(H) x 158.4(V) mm   Color Depth   262K Colors   Light Source   Long life, 50,000 hours (typ)   Brightness   350 cd/m²   Contrast Ratio   150:1   Viewing Angle   Horizontal (typ) (L - R: -50° - +50° ), Vertical (typ) (U - D: -35° - +35°)   INPUT SIGNAL   Video   Analog RGB (0.7/1.0 Vp-p, 75 ohms)   Sync   Composite Sync   Frequency   Fh: 30 - 82 Khz, Fv: 60 - 75Khz   RESOLUTION   1024 x 768 @ 60/70/75 Hz   800 x 600 @ 60/70/75 Hz   800 x 600 @ 60/70/75 Hz   800 x 600 @ 60/70 Hz   800 x 600 @ 60 Hz	PANEL	
Glass Surface	Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD Panel
Pixel Number   800(H) x 600(V)	Pixel Arrangement	RGB vertical stripe
Pixel Pitch	Glass Surface	Anti-Glare coating
Display Size	Pixel Number	800(H) x 600(V)
Active Area 211.2(H) x 158.4(V) mm  Color Depth 262K Colors  Light Source Long life, 50,000 hours (typ)  Brightness 350 cd/m²  Contrast Ratio 150:1  Viewing Angle Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)  INPUT SIGNAL  Video Analog RGB (0.7/1.0 Vp-p, 75 ohms)  Sync Composite Sync  Frequency Fh: 30 - 82 Khz, Fv: 60 - 75Khz  RESOLUTION  1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 640 x 480 @ 60/70/75 Hz 640 x 350 @ 70 Hz 800 x 600 @ 60 Hz  Recommended 800 x 600 @ 60 Hz  CONTROL  Top Back (OSD) Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall  POWER  Input Voltage AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A  Operating Operating Operation: 25 Watt, Off: < 5 Watt  OPERATING CONDITION  Temperature -10° C ~ 65° C  Humidity 10% ~ 90% (no condensation)  STORAGE CONDITION  Temperature -30° C ~ 70° C  Humidity 10% ~ 90% (no condensation)  OTHER  Audio 2W x 1 Speaker  Dimensions (W x H x D) 264 x 225 x 40.5 mm  Weight (Net/Gross) 3 Kg/4Kg  Options Video-In: 1 x RCA Connector, 1 x S-Video	Pixel Pitch	0.264(H) mm x 0.264(V) mm
Color Depth         262K Colors           Light Source         Long life, 50,000 hours (typ)           Brightness         350 cd/m²           Contrast Ratio         150:1           Viewing Angle         Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)           INPUT SIGNAL         Video         Analog RGB (0.7/1.0 Vp-p, 75 ohms)           Sync         Composite Sync           Frequency         Fh: 30 - 82 Khz, Fv: 60 - 75Khz           RESOLUTION         1024 × 768 @ 60/70/75 Hz           Supported         400 × 480 @ 60/70/75 Hz           Supported         640 × 480 @ 60/70/75 Hz           Supported         800 × 600 @ 60/70 Hz           404 × 350 @ 70 Hz         640 × 480 @ 70/70 Hz           404 × 350 @ 70 Hz         800 × 600 @ 60 Hz           Recommended         800 × 600 @ 60 Hz           CONTROL         Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER         Input Voltage         AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           POPERATING CONDITION         Contrast Question: 25 Watt, Off: < 5 Watt	Display Size	10.4" viewable diagonal area
Light Source  Brightness  350 cd/m²  Contrast Ratio  150:1  INPUT SIGNAL  Video  Analog RGB (0.7/1.0 Vp-p, 75 ohms)  Sync  Frequency  Fh: 30 - 82 Khz, Fv: 60 - 75 Khz  RESOLUTION  1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 800 x 600 @ 60 Hz  CONTROL  Recommended  800 x 600 @ 60 Hz  CONTROL  Top Back (OSD)  POWER  Input Voltage Power Rating Operatines  Operatines  Operatines  Operatines  10°C ~ 65°C  Humidity  Tom Humidity  STORAGE CONDITION  Log May be deep see when the power of the powe	Active Area	211.2(H) x 158.4(V) mm
Brightness         350 cd/m²           Contrast Ratio         150:1           Viewing Angle         Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)           INPUT SIGNAL         Video           Video         Analog RGB (0.7/1.0 Vp-p, 75 ohms)           Sync         Composite Sync           Frequency         Fh: 30 - 82 Khz, Fv: 60 - 75Khz           RESOLUTION         1024 × 768 @ 60/70/75 Hz 800 × 600 @ 60/70/75 Hz 900 @ 60/70 Hz 640 × 480 @ 60/70/75 Hz 900 @ 60/70 Hz 640 × 350 @ 70 Hz 800 × 600 @ 60 Hz           Recommended         800 × 600 @ 60 Hz           CONTROL         Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER         Input Voltage           AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           Operation: 25 Watt, Off: < 5 Watt	Color Depth	262K Colors
Contrast Ratio         150:1           Viewing Angle         Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)           INPUT SIGNAL         Analog RGB (0.7/1.0 Vp-p, 75 ohms)           Sync         Composite Sync           Frequency         Fh: 30 - 82 Khz, Fv: 60 - 75Khz           RESOLUTION         1024 × 768 @ 60/70/75 Hz 800 × 600 @ 60/70/75 Hz 800 × 600 @ 60/70/75 Hz 720 × 400 @ 60/70 Hz 640 × 480 @ 60/70/75 Hz 720 × 400 @ 60/70 Hz 640 × 480 @ 60/70/75 Hz 720 × 400 @ 60/70 Hz 720 × 400 @ 60 Hz           Recommended         800 × 600 @ 60 Hz           CONTROL         Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER         Input Voltage           Input Voltage         AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           Power Rating         Operation: 25 Watt, Off: < 5 Watt	Light Source	Long life, 50,000 hours (typ)
Viewing Angle         Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)           INPUT SIGNAL         Analog RGB (0.7/1.0 Vp-p, 75 ohms)           Video         Analog RGB (0.7/1.0 Vp-p, 75 ohms)           Sync         Composite Sync           Frequency         Fh: 30 - 82 Khz, Fv: 60 - 75Khz           RESOLUTION         1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 640 x 350 @ 70 Hz 640 x 350 @ 70 Hz 640 x 350 @ 70 Hz 800 x 600 @ 60 Hz           Supported         400 x 600 @ 60 Hz           Recommended         800 x 600 @ 60 Hz           CONTROL         Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER         Input Voltage         AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           Power Rating         Operation: 25 Watt, Off: < 5 Watt           OPERATING CONDITION           Temperature         -10°C ~ 65°C           Humidity         10% ~ 90% (no condensation)           STORAGE CONDITION         Temperature         -30°C ~ 70°C           Humidity         10% ~ 90% (no condensation)           OTHER         Audio         2W x 1 Speaker           Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options	Brightness	350 cd/m <sup>2</sup>
INPUT SIGNAL	Contrast Ratio	150:1
Video         Analog RGB (0.7/1.0 Vp-p, 75 ohms)           Sync         Composite Sync           Frequency         Fh: 30 - 82 Khz, Fv: 60 - 75Khz           RESOLUTION           1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 640 x 480 @ 60/70/75 Hz 720 x 400 @ 60/70 Hz 640 x 350 @ 70 Hz 800 x 600 @ 60 Hz           Recommended           CONTROL           Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER           Input Voltage         AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           Operation: 25 Watt, Off: < 5 Watt	Viewing Angle	Horizontal (typ) (L ~ R: -50° ~ +50°), Vertical (typ) (U ~ D: -35° ~ +35°)
Sync         Composite Sync           Frequency         Fh: 30 - 82 Khz, Fv: 60 - 75 Khz           RESOLUTION         1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 720 x 400 @ 60/70 Hz 640 x 350 @ 70 Hz 800 x 600 @ 60 Hz           Supported         800 x 600 @ 60 Hz           Recommended         800 x 600 @ 60 Hz           CONTROL         Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER         Input Voltage           Input Voltage         AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           Power Rating         Operation: 25 Watt, Off: < 5 Watt	INPUT SIGNAL	
Frequency	Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)
RESOLUTION           1024 x 768 @ 60/70/75 Hz           800 x 600 @ 60/70/75 Hz           640 x 480 @ 60/70/75 Hz           720 x 400 @ 60/70 Hz           640 x 350 @ 70 Hz           800 x 600 @ 60 Hz           CONTROL           Top Back (OSD)         Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall           POWER           Input Voltage         AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A           Power Rating         Operation: 25 Watt, Off: < 5 Watt	Sync	Composite Sync
1024 x 768 @ 60/70/75 Hz   800 x 600 @ 60/70/75 Hz   800 x 600 @ 60/70/75 Hz   640 x 480 @ 60/70/75 Hz   720 x 400 @ 60/70 Hz   640 x 350 @ 70 Hz   800 x 600 @ 60 Hz   800 x 600 @ 60 Hz   800 x 600 @ 60 Hz	Frequency	Fh: 30 - 82 Khz, Fv: 60 - 75Khz
Supported       800 x 600 @ 60/70/75 Hz         640 x 480 @ 60/70/75 Hz       720 x 400 @ 60/70 Hz         640 x 350 @ 70 Hz       800 x 600 @ 60 Hz         Recommended       800 x 600 @ 60 Hz         CONTROL         Top Back (OSD)       Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall         POWER         Input Voltage       AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A         Power Rating       Operation: 25 Watt, Off: < 5 Watt	RESOLUTION	
CONTROL  Top Back (OSD)  Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall  POWER  Input Voltage  AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A  Power Rating  Operation: 25 Watt, Off: < 5 Watt  OPERATING CONDITION  Temperature  -10°C ~ 65°C  Humidity  10% ~ 90% (no condensation)  STORAGE CONDITION  Temperature  -30°C ~ 70°C  Humidity  10% ~ 90% (no condensation)  OTHER  Audio  2W x 1 Speaker  Dimensions (W x H x D)  Weight (Net/Gross)  3 Kg/4Kg  Options  Video-In: 1 x RCA Connector, 1 x S-Video	Supported	800 x 600 @ 60/70/75 Hz 640 x 480 @ 60/70/75 Hz 720 x 400 @ 60/70 Hz 640 x 350 @ 70 Hz
Top Back (OSD)  Auto Adjust, Brightness, Contrast, H-Position, V-Position, Phase, Color, Default, Volume, Language, Memory recall  POWER  Input Voltage  AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A  Operation: 25 Watt, Off: < 5 Watt  OPERATING CONDITION  Temperature  -10°C ~ 65°C  Humidity  10% ~ 90% (no condensation)  STORAGE CONDITION  Temperature  -30°C ~ 70°C  Humidity  10% ~ 90% (no condensation)  OTHER  Audio  2W x 1 Speaker  Dimensions (W x H x D)  Weight (Net/Gross)  3 Kg/4Kg  Options  Video-In: 1 x RCA Connector, 1 x S-Video	Recommended	800 x 600 @ 60 Hz
Default, Volume, Language, Memory recall	CONTROL	
Input Voltage AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A  Power Rating Operation: 25 Watt, Off: < 5 Watt  OPERATING CONDITION  Temperature -10°C ~ 65°C  Humidity 10% ~ 90% (no condensation)  STORAGE CONDITION  Temperature -30°C ~ 70°C  Humidity 10% ~ 90% (no condensation)  OTHER  Audio 2W x 1 Speaker  Dimensions (W x H x D) 264 x 225 x 40.5 mm  Weight (Net/Gross) 3 Kg/4Kg  Options Video-In: 1 x RCA Connector, 1 x S-Video	Top Back (OSD)	
Power Rating         Operation: 25 Watt, Off: < 5 Watt           OPERATING CONDITION         -10°C ~ 65°C           Humidity         10% ~ 90% (no condensation)           STORAGE CONDITION           Temperature         -30°C ~ 70°C           Humidity         10% ~ 90% (no condensation)           OTHER           Audio         2W x 1 Speaker           Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options         Video-In: 1 x RCA Connector, 1 x S-Video	POWER	
OPERATING CONDITION           Temperature         -10°C ~ 65°C           Humidity         10% ~ 90% (no condensation)           STORAGE CONDITION         -30°C ~ 70°C           Humidity         10% ~ 90% (no condensation)           OTHER         Audio           Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options         Video-In: 1 x RCA Connector, 1 x S-Video	Input Voltage	AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A
Temperature       -10°C ~ 65°C         Humidity       10% ~ 90% (no condensation)         STORAGE CONDITION       Temperature       -30°C ~ 70°C         Humidity       10% ~ 90% (no condensation)         OTHER         Audio       2W x 1 Speaker         Dimensions (W x H x D)       264 x 225 x 40.5 mm         Weight (Net/Gross)       3 Kg/4Kg         Options       Video-In: 1 x RCA Connector, 1 x S-Video	Power Rating	Operation: 25 Watt, Off: < 5 Watt
Humidity       10% ~ 90% (no condensation)         STORAGE CONDITION       -30°C ~ 70°C         Temperature       -30°C ~ 70°C         Humidity       10% ~ 90% (no condensation)         OTHER       Audio         Dimensions (W x H x D)       264 x 225 x 40.5 mm         Weight (Net/Gross)       3 Kg/4Kg         Options       Video-In: 1 x RCA Connector, 1 x S-Video	OPERATING CONDITION	
STORAGE CONDITION           Temperature         -30°C ~ 70°C           Humidity         10% ~ 90% (no condensation)           OTHER         Audio           Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options         Video-In: 1 x RCA Connector, 1 x S-Video	Temperature	-10°C ~ 65°C
Temperature       -30°C ~ 70°C         Humidity       10% ~ 90% (no condensation)         OTHER         Audio       2W x 1 Speaker         Dimensions (W x H x D)       264 x 225 x 40.5 mm         Weight (Net/Gross)       3 Kg/4Kg         Options       Video-In: 1 x RCA Connector, 1 x S-Video	Humidity	10% ~ 90% (no condensation)
Humidity       10% ~ 90% (no condensation)         OTHER         Audio       2W x 1 Speaker         Dimensions (W x H x D)       264 x 225 x 40.5 mm         Weight (Net/Gross)       3 Kg/4Kg         Options       Video-In: 1 x RCA Connector, 1 x S-Video	STORAGE CONDITION	
OTHER           Audio         2W x 1 Speaker           Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options         Video-In: 1 x RCA Connector, 1 x S-Video	Temperature	-30°C ~ 70°C
Audio         2W x 1 Speaker           Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options         Video-In: 1 x RCA Connector, 1 x S-Video	Humidity	10% ~ 90% (no condensation)
Dimensions (W x H x D)         264 x 225 x 40.5 mm           Weight (Net/Gross)         3 Kg/4Kg           Options         Video-In: 1 x RCA Connector, 1 x S-Video	OTHER	
Weight (Net/Gross) 3 Kg/4Kg Options Video-In: 1 x RCA Connector, 1 x S-Video	Audio	2W x 1 Speaker
Weight (Net/Gross) 3 Kg/4Kg Options Video-In: 1 x RCA Connector, 1 x S-Video	Dimensions (W x H x D)	264 x 225 x 40.5 mm
Options Video-In: 1 x RCA Connector, 1 x S-Video		3 Kg/4Kg
		Video-In: 1 x RCA Connector, 1 x S-Video

### Unytouch Manufacturing, Inc.

27 Armthorpe Road Brampton, Ontario, L6T 5M4

Phone: (905) 792-0542 Toll Free: (800) 260 6249

Fax: (905) 792-2843

# **Legacy Technology Services**

### We Rent & Sell All Types Of Barcode Equipment

## Call now to talk to an expert

866-271-9891

### About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

### Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

### **Expert Repair and Maintenance services**

· Legacy is one of the best repair facilities in North America

### Discontinued product sourcing

 They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

#### **Trade-in and Disposal services**

- That old equipment laying around your facility may still have some value.
   Legacy routinely purchases equipment from our clients around the globe.
  - · Data destruction
  - · Hardware disposal
  - Auditing services

#### Dedicated client account team

 Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

### **Equipment rental services**

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.











(AAA) POOL

Toll Free: 866-271-9891 Fax: 888-522-4684 www.LegacyGlobal.com
Some brands we carry





















