

12.1" Panel Mount LCD

			MAIN SPEC	IFICATIONS U14-OC121-B	
			PANEL		
			Cell Type	Color active matrix TFT (Thin-Film-Transistor) LCD Panel	
			Pixel Arrangement	RGB vertical stripe	
	and the second		Glass Surface	Anti-Glare coating	
		N'	Pixel Number	800(H) x 600(V)	
			Pixel Pitch	0.3075(H) mm x 0.3075(V) mm	
the second se		< 3 YEAR 🔶	Display Size	12.1" viewable diagonal area	
the second se	<pre></pre>		Active Area	264.0(H) x 184.5(V) mm	
the second se		🗲 WARRANTY <	Color Depth	262K Colors	
the second se		\leq \sim	Light Source	Long life, 50,000 hours (typ)	
the state of the second s		4 1	Brightness	370 cd/m ²	
the second se	and the second second		Contrast Ratio	450:1	
the second se			Viewing Angle	Horizontal (typ) (L ~ R: -70° ~ +70°), Vertical (typ) (U ~ D: -50° ~ +60°)	
the second se			INPUT SIGNAL		
the second se	and the second se	r v v v	Video	Analog RGB (0.7/1.0 Vp-p, 75 ohms)	
the second se	and the second se		Sync	Composite Sync	
the second se	the second se		Frequency	Fh: 30 - 82 Khz, Fv: 60 - 75Khz	
			RESOLUTION		
			Supported	1024 x 768 @ 60/70/75 Hz 800 x 600 @ 60/70/75 Hz 640 x 480 @ 60/70/75 Hz 720 x 400 @ 60/70 Hz 640 x 350 @ 70 Hz 640 x 350 @ 70 Hz	
		VESA Mount	Recommended	800 x 600 @ 60 Hz ed 800 x 600 @ 60 Hz	
			CONTROL	800 X 800 @ 80 HZ	
		Speakers	Front Panel Winsticker (OSD)	Power, Menu Select, + (Inc), - (Dec), Auto Adjust, Brightness, Contrast, H- Position, V-Position, Phase, Color, Default, Volume, Language, Memory Recall	
			POWER		
	REAR VIEW	SIDE VIEW	Input Voltage	AC: 90 to 260 VAC, 50/60 Hz DC: 12V/1.2A	
			Power Rating	Operation: 30 Watt, Off: < 5 Watt	
			OPERATING CONDITION		
			Temperature	-10°C ~ 65°C	
			Humidity	10% ~ 90% (no condensation)	
TOUCH PART NUMBERS			STORAGE CONDITION		
			Temperature	-30°C ~ 70°C	
5 Wire Resistive USB Touch U14-OC121UR-B			Humidity	10% ~ 90% (no condensation)	
			OTHER		
			Audio	2W x 1 Speaker	
	I The second		Dimensions (W x H x D)	264 x 225 x 40.5 mm	
	A CONTRACTOR		Weight (Net/Gross)	3 Kg/4Kg	
			Options	Video-In: 1 x RCA Connector, 1 x S-Video	
			Certification	FCC, CE	

Unytouch Manufacturing, Inc.

27 Armthorpe Road Brampton, Ontario, L6T 5M4 Phone: (905) 792-0542 Toll Free: (800) 260 6249 Fax: (905) 792-2843

Visit us: **www.unytouch.ca** sales@unytouch.ca

APPLICATIONS:

- Industrial
- Gaming
- Custom or OEM Applications
- Retail

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert 866-271-9891

About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

• Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

· Legacy is one of the best repair facilities in North America

Discontinued product sourcing

• They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - · Hardware disposal
 - Auditing services

Dedicated client account team

• Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

• Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.





<u>Legacy, Inc.,</u> 160 West Road, Ellington, CT 06029

Toll Free: 866-271-9891 Fax: 888-522-4684

www.LegacyGlobal.com

Some brands we carry







Honeywell













